


8-RED 1-BLU 2-WHT 3-ORG 4-YEL J-BRN 5-BLK




|          | LINE A | LINE B | JOIN  | JOIN  |
|----------|--------|--------|-------|-------|
| HIGH STD | 1      | 4      | 2,3,8 | J,5   |
| HIGH OPP | 1      | 4      | 2,3,5 | J,8   |
| LOW STD  | 1,3,8  | 4      | —     | 2,J,5 |
| LOW OPP  | 1,3,5  | 4      | —     | 2,J,8 |

## NOTES:

1. STANDARD ROTATION IS CCW FACING END OPPOSITE SHAFT EXTENSION.
2. MULTIPLE CAPACITORS ARE CONNECTED IN PARALLEL UNLESS OTHERWISE SPECIFIED.
3. LEAD COLORS ARE OPTIONAL. LEADS MUST ALWAYS BE NUMBERED AS SHOWN.

## CONNECTIONS FOR TWO-TERMINAL THERMAL

4-YEL J-BRN



REV. DESC: REVISE TO SHOW OPTIONAL COLORS

REV. LTR: C BY: JLP REVISED: 04/08/99 3:25 TDR: 0178636

BALDOR ELECTRIC Co.

S9S0D0

FILE: AAA00014311

MDL: —

MTL: —

TYPE L, DV, REV, THERMAL, 7 LD, 34XP