

ACCESSORIES: AIR FILTERED
PROVISION FOR
TACHOMETER MOUNTING
ONLY WHEN SPECIFIED

DIMENSIONS ARE IN INCHES

FRAME	METHOD OF DRIVE	C(7)	B	BS	2F	DRIVE END SHAFT AND KEY						(S)OPPOSITE DRIVE END SHAFT AND KEY						WT. LBS.		
						N	N-W	UC2	V	R(3)	SQ	LGTH.	FN	FN-FW	FUK(2)	FV	FR(3)		SQ	LGTH.
C4011ATZ	COUPLED	52.10	42.06	16.00	28.00	7.62	7.25	3.625	7.00	1.334	875	5.75	7.62	7.25	3.625	7.00	1.334	875	5.75	2500.
UC4011ATZ	BELTED	53.10	42.06	16.00	28.00	8.62	8.25	4.125	8.00	3.5631	0.00	6.50	7.62	7.25	3.625	7.00	1.334	875	5.75	2500.
MC4013ATZ	COUPLED	56.82	46.81	20.75	36.00	7.62	7.25	3.625	7.00	1.334	875	5.75	7.62	7.25	3.625	7.00	1.334	875	5.75	2800.
UC4013ATZ	BELTED	57.62	46.91	20.75	36.00	8.62	8.25	4.125	8.00	3.5631	0.00	6.50	7.62	7.25	3.625	7.00	1.334	875	5.75	2800.
LC4013ATZ	BELTED	60.09	50.06	24.00	36.00	7.62	7.25	3.625	7.00	1.334	875	5.75	7.62	7.25	3.625	7.00	1.334	875	5.75	3100.
ULC4013ATZ	BELTED	61.09	50.06	24.00	36.00	8.62	8.25	4.125	8.00	3.5631	0.00	6.50	7.62	7.25	3.625	7.00	1.334	875	5.75	3100.

5.88
DIA.
B.C.

45°

3/8-16 TAP
.62 DEEP
4 HOLES

PROV.
FOR
TACH

6.750 $\begin{smallmatrix} +.003 \\ -.000 \end{smallmatrix}$
DIA.

.19

1.00

2.00

GUARD

STUB SHAFT
SUPPLIED ONLY
WHEN SPECIFIED

.6250 $\pm .0005$
DIA.
STUB SHAFT WITH 1.88 SQ. X 1.00 LG. KEY

- (1) "D" DIMENSION WILL NOT BE EXCEEDED. SHIMS UP TO .06 INCHES IN THICKNESS
ARE USUALLY REQUIRED FOR COUPLED OR GEARED MACHINES.
- (2) "U" AND "FU" VARY -----, 000 - .001
- (3) "R" AND "FR" VARY -----, 000 - .015
- (4) CUSTOMER TO PROVIDE HOLE IN TERMINAL BOX FOR CONDUIT.
- (5) OPPOSITE DRIVE END SHAFT SUPPLIED ONLY WHEN SPECIFIED.
- (6) MOTOR SHAFT ADAPTED FOR SCREW-IN SHAFT.
- (7) WHEN THE MOTOR APPLICATION DOES NOT REQUIRE THE USE OF
DPP, DRIVE END, .25 TO "C" DIM. FOR BRACKET COVER.

TERMINAL BOX LOCATED ON OPPOSITE SIDE WHEN F-2, W-1, W-4, W-5, W-7, OR C-1 MOUNTING IS SPECIFIED. BOX LOCATED ON TOP WHEN SPECIFIED. BLOWER ASSEMBLY CAN BE LOCATED AT POSITIONS 1, 2, OR 4, EXCEPT BLOWER ASSEMBLY AND TERMINAL BOX CAN NOT BE LOCATED AT THE SAME POSITION. MOTOR WEIGHT MAY VARY 15% FOR NON-STANDARD RATINGS AND/OR ACCESSORIES. IF MOUNTING CLEARANCE DETAILS ARE REQUIRED, CONSULT FACTORY.

CUSTOMER IS RESPONSIBLE FOR DETERMINING THAT BALDOR'S PRODUCT WILL PERFORM SUITABLY IN THE INTENDED APPLICATION.

REV. LTR: -	VERSION: 00	TDR: 000000577407
FILE: \RGG\00015\598	REVISED: 12: 02: 57 01/26/2011	BY: CONNAS
MTL: -		

BALDOR

DIMENSION DRAWING.C4011ATZ - ULC4013ATZ.DPP.FOOT MTG.

SH 1 of 1