


DUTY MASTER ALTERNATING CURRENT MOTORS
SQUIRREL-CAGE INDUCTION
CAST IRON CONSTRUCTION
ENCLOSURE: TOTALLY ENCLOSED
MOUNTING: FOOT
COOLING: FAN COOLED

FRAMES 250T THRU 440T



DIMENSIONS ARE IN INCHES; SEE SHEET 2 FOR DIMENSIONS IN MILLIMETERS

FRAME	A	D(2)	E	G	H	J	K	O	P	T	CAST IRON TERMINAL BOX				(7) AUX. CONDUIT BOX		BA	EV	
											AA	AB	AC	AF	AAX	LX (7)			PX (7)
254T-256T	12.50	6.25	5.00	.75	.56	2.50	--	13.25	13.25	2.44	1-1/4	10.81	8.81	2.50	3/4	6.31	9.31	4.25	1.00
284T-286TS	13.75	7.00	5.50	.75	.56	2.50	--	14.75	14.88	2.44	1-1/2	12.62	10.19	3.00	3/4	6.88	10.50	4.75	1.00
324T-326TS	15.50	8.00	6.25	.88	.69	2.75	4.50	16.69	17.00	2.44	2	15.44	11.69	3.62	3/4	8.00	10.50	5.25	1.38
364T-365TS	17.00	9.00	7.00	.88	.69	2.75	3.88	18.50	19.50	2.94	3	18.00	13.81	4.12	3/4	8.38	11.62	5.88	1.38
404T-405TS	19.00	10.00	8.00	1.12	.81	3.25	4.62	21.31	22.50	2.94	3	19.25	15.06	4.12	3/4	9.62	14.44	6.62	1.13
444T-445TS	21.00	11.00	9.00	1.12	.81	3.25	5.25	23.38	25.25	3.25	3	22.19	17.44	6.00	3/4	11.12	15.25	7.50	1.25
(1)																			

FRAME SIZE	C	BS	B	2F	(4)				SHAFT AND KEY		WGHT LBS. (5)	
					2XF	N	N-W(6)	U(3)	V	SO.		LGTH.
254T	24.56	5.00	12.00	----	8.25	4.12	4.00	1.625	3.75	.375	2.88	335
256T	24.56	5.00	12.00	10.00	----	4.12	4.00	1.625	3.75	.375	2.88	345
284T	27.44	5.50	13.00	----	9.50	5.00	4.62	1.875	4.38	.500	3.25	475
284TS	26.06	5.50	13.00	----	9.50	3.62	3.25	1.625	3.00	.375	1.88	475
286T	27.44	5.50	13.00	11.00	----	5.00	4.62	1.875	4.38	.500	3.25	490
286TS	26.06	5.50	13.00	11.00	----	3.62	3.25	1.625	3.00	.375	1.88	490
324T	30.44	6.00	14.75	----	10.50	5.62	5.25	2.125	5.00	.500	3.88	590
324TS	28.94	6.00	14.75	----	10.50	4.12	3.75	1.875	3.50	.500	2.00	590
326T	30.44	6.00	14.75	12.00	----	5.62	5.25	2.125	5.00	.500	3.88	630
326TS	28.94	6.00	14.75	12.00	----	4.12	3.75	1.875	3.50	.500	2.00	630
364T	33.44	6.12	15.00	----	11.25	6.25	5.88	2.375	5.62	.625	4.25	865
364TS	31.31	6.12	15.00	----	11.25	4.12	3.75	1.875	3.50	.500	2.00	859
365T	33.44	6.12	15.00	12.25	----	6.25	5.88	2.375	5.62	.625	4.25	890
365TS	31.31	6.12	15.00	12.25	----	4.12	3.75	1.875	3.50	.500	2.00	884
404T	38.31	6.88	16.00	----	12.25	7.50	7.25	2.875	7.00	.750	5.62	1220
404TS	35.31	6.88	16.00	----	12.25	4.50	4.25	2.125	4.00	.500	2.75	1211
405T	38.31	6.88	16.00	13.75	----	7.50	7.25	2.875	7.00	.750	5.62	1260
405TS	35.31	6.88	16.00	13.75	----	4.50	4.25	2.125	4.00	.500	2.75	1251
444T	44.62	8.25	19.00	----	14.50	8.94	8.50	3.375	8.25	.875	6.88	1670
444TS	40.88	8.25	19.00	----	14.50	5.19	4.75	2.375	4.50	.625	3.00	1654
445T	44.62	8.25	19.00	16.50	----	8.94	8.50	3.375	8.25	.875	6.88	1860
445TS	40.88	8.25	19.00	16.50	----	5.19	4.75	2.375	4.50	.625	3.00	1844

- (1) SPECIAL DIMENSIONS APPLYING TO THIS ORDER ON THIS LINE.
- (2) "D" VARIES — 250T - 320T +.00, -.03.
— 360T - 440T +.00, -.06.
- (3) "U" VARIES — HP TO 1.625 DIA. +.0000, -.0005
— 1.625 AND LARGER +.000, -.001.
- (4) ALL FRAMES HAVE EIGHT MOUNTING HOLES FOR DUAL MOUNTING.
- (5) MOTOR WEIGHTS MAY VARY BY 15% DEPENDING UPON RATING.
- (6) "N-W" VARIES +.00, -.25.
- (7) AUXILIARY CONDUIT BOX SUPPLIED WHEN SPECIFIED
CONDUIT BOXES LOCATED ON OPPOSITE SIDE WHEN F-2-W-1,
W-4-W-5-W-7, OR C-1 MOUNTING IS SPECIFIED.
IF MOUNTING CLEARANCE DETAILS ARE REQUIRED, CONSULT
FACTORY.
MAXIMUM PERMISSIBLE SHAFT RUNOUT WHEN MEASURED
AT END OF STD. SHAFT EXTENSION IS .002 I.R. UP TO
AND INCLUDING 1.625 DIA. AND .003 I.R. 1.625 DIA.
TO 5 INCH DIA.

FRAME — TYPE — CERTIFIED FOR —
ORDER — ITEM — HP — RPM — PH — HZ — VOLTS —
SALES ORDER — APPROVED BY — DATE —

CUSTOMER IS RESPONSIBLE FOR DETERMINING THAT MOTOR PERFORMANCE IS SUITABLE IN THE APPLICATION.

REV. DESC: REMOVING TITLEBLOCK		
REV. LTR: A	VERSION: 01	TDR: 000000448517
FILE: \RAG\00004\525	REVISED: 14:06:59 11/07/2007	BY: CONBPM
MTL: -		

BALDOR • DODGE • RELIANCE

DIM SHT 250T-440T TEFC FT MTG STD T & TS SGL EXT XT