

8 7 6 5 4 3 2 1

617600-001

RPM-AC VARIABLE SPEED ALTERNATING CURRENT MOTOR
RL4440Z

ENCLOSURE: DRIP PROOF

COOLING: FORCE VENTILATED

MOUNTING: FOOT

ACCESSORIES: PROVISIONS FOR TACHOMETER MOUNTING ONLY WHEN SPECIFIED

59.39

18.89

9.45

35.00

45.22

9.13

8.50

1.00" SQ KEY X 7.00" LONG

4.250

4.249

7.50

8.75

28.65

20.50

44.14

21.82

11.00 NOTE 2

1.00

9.00

9.00

21.62

1.06

NOTE 1: O.D.E. C-FACE & TACHOMETER MOUNTING 1/2-13 TAP, 1.00 DEEP, ON A $\phi 7.25$ B.C. FACE RUNOUT AND ECCENTRICITY 0.004 MAX. T.I.R.

NOTE 2: SHAFT HEIGHT WILL NOT BE EXCEEDED SHIMS UP TO 0.06 INCHES IN THICKNESS ARE USUALLY REQUIRED FOR COUPLED OR GEARED MACHINES

NOTE 3: REMOVEABLE COVER PLATE FOR CUSTOMER DRILLING

NOTE 4: TERMINAL BOX CAN BE LOCATED F1 OR F2 IF SPECIFIED.

MOTOR WEIGHT: 3330 LBS. MAY VARY 15% FOR NON-STANDARD RATINGS AND/OR ACCESSORIES.

REFER TO 616779-55 FOR SPECIFIED TACHOMETER DIMENSIONS

IF MOUNTING DETAILS ARE REQUIRED, CONSULT FACTORY.

CUSTOMER IS RESPONSIBLE FOR DETERMINING THAT THE PRODUCT WILL PERFORM SUITABLY IN THE INTENDED APPLICATION

REV. DESC: CORRECT O.D.E. FLANGE TOLERANCE			
REV: D	VERSION: 04	REVISED: 12:46:42 11/21/2022	TDR: 000001200321
MODEL NO. 617600-001			REF: -
BY: USWATUR			B

BALDOR - RELIANCE®

DIM SHT, RL4440Z,DPFV, STD

617600-001

8 7 6 5 4 3 2 1

ACCESSORIES: PROVISIONS FOR
TACHOMETER MOUNTING
ONLY WHEN SPECIFIED

MOUNTING: FOOT

— 1.00" SQ KEY
X 7.00" LONG

NOTE 1

MOTOR WEIGHT: 3330 LBS.
MAY VARY 15% FOR NON-STANDARD RATINGS AND/OR ACCESSORIES.

IF MOUNTING DETAILS ARE REQUIRED, CONSULT FACTORY.

REV. DESC: CORRECT O.D.E. FLANGE TOLERANCE

MODEL NO. 617600-001

--	--

DIM SHT, RL4440Z ,DPFV, STD

617600-001