








ABB Motors and Generators		Technical Data Sheet - DOL				
		Project		Location		
Department/Author		Customer name		Customer ref.		Item name
Our ref.		Rev/Changed by	Date of issue	Saving ident		Pages 1(3)

No.	Definition	Data	Unit	Remarks	
1	Product	TEFC, 3-phase, squirrel cage induction motor			
2	Product code	MM10034-EX3 (3GKP102520-ASH+332+461)			
3	Type/Frame	M3KP 100 LB 4			
4	Mounting	IM1001, B3(foot)			
5	Rated output P _N	3	kW		
6	Service factor	1			
7	Type of duty	S1(IEC) 100%			
8	Rated voltage U _N	400	VY	± 5 % (IEC 60034-1)	
9	Rated frequency f _N	50	Hz	± 2 % (IEC 60034-1)	
10	Rated speed n _N	1442	r/min		
11	Rated current I _N	6	A		
12	No-load current	3.1	A		
13	Starting current I _s /I _N	7.3		Fullfilled IEC 60034-12 design N,H	
14	Nominal torque T _N	19.9	Nm		
15	Locked rotor torque T _s /T _N	2.7			
16	Maximum torque T _{max} /T _N	3.4			
17	Minimum torque T _{min} /T _N	2.4			
18	Speed at minimum torque	225	r/min		
19	Load characteristics (IEC 60034-2-1:2007)	Load %	Current A	Efficiency %	Power factor
20	PLL determined from residual loss	100	6	86.5 / IE2	0.83
21		75	4.7	87.2	0.78
22		50	3.8	86.3	0.66
23		Start	44		0.55
24	Maximum starting time from hot	15	s		
25	Maximum starting time from cold	27	s		
26	Insulation class / Temperature class	F / B			
27	Ambient temperature	40	°C		
28	Altitude	1000	m.a.s.l.		
29	Enclosure	IP55			
30	Cooling system	IC411 self ventilated			
31	Bearing DE/NDE	6206-2Z/C3 - 6206-2Z/C3			
32	Type of Grease	Greased for life			
33	Sound pressure level (LP dB(A) 1m)	52	dB(A)	at load	
34	Moment of inertia J = ¼ GD2	0.0081	kg-m2		
35	Balancing	Half Key			
36	Vibration class	Grade A			
37	Position of terminal box	Top			
38	Terminal box entries; no, dims.	2xM32x1.5 + 1xM20x1.5			
39	Number of power terminals	6			
40	Direction of rotation	CW or CCW			
41	Weight of rotor	10	kg		
42	Total weight of motor	63	kg		
43					
Ex-motors					
44	Type of protection	*Ex de IIC T4			
45					
Variant Codes / Definition					
	332 = Baldor catalog number				
	461 = Exde design, group IIC				
Remarks:					
Data based on situation 11/4/2012					
All data subject to tolerances in accordance with IEC					
Guaranteed values on request					
* For more information on the Atex/IECEx rating, please contact your local Baldor representative.					






ABB Motors and Generators		Technical Data Sheet - DOL				
		Project		Location		
Department/Author		Customer name		Customer ref.		Item name
Our ref.		Rev/Changed by	Date of issue	Saving ident		Pages 1(3)

No.	Definition	Data	Unit	Remarks	
1	Product	TEFC, 3-phase, squirrel cage induction motor			
2	Product code	MM10034-EX3 (3GKP102520-ASH+332+461)			
3	Type/Frame	M3KP 100 LB 4			
4	Mounting	IM1001, B3(foot)			
5	Rated output P _N	3	kW		
6	Service factor	1			
7	Type of duty	S1(IEC) 100%			
8	Rated voltage U _N	415	VY	± 5 % (IEC 60034-1)	
9	Rated frequency f _N	50	Hz	± 2 % (IEC 60034-1)	
10	Rated speed n _N	1444	r/min		
11	Rated current I _N	5.8	A		
12	No-load current	3.3	A		
13	Starting current I _s /I _N	7.4		Fullfilled IEC 60034-12 design N,H	
14	Nominal torque T _N	19.8	Nm		
15	Locked rotor torque T _S /T _N	2.9			
16	Maximum torque T _{max} /T _N	3.7			
17	Minimum torque T _{min} /T _N	2.6			
18	Speed at minimum torque	225	r/min		
19	Load characteristics (IEC 60034-2-1:2007)	Load %	Current A	Efficiency %	Power factor
20	PLL determined from residual loss	100	5.8	86.7 / IE2	0.82
21		75	4.7	87.1	0.75
22		50	3.9	85.8	0.62
23		Start	43		0.56
24	Maximum starting time from hot	15	s		
25	Maximum starting time from cold	30	s		
26	Insulation class / Temperature class	F / B			
27	Ambient temperature	40	°C		
28	Altitude	1000	m.a.s.l.		
29	Enclosure	IP55			
30	Cooling system	IC411 self ventilated			
31	Bearing DE/NDE	6206-2Z/C3 - 6206-2Z/C3			
32	Type of Grease	Greased for life			
33	Sound pressure level (LP dB(A) 1m)	52	dB(A)	at load	
34	Moment of inertia J = ¼ GD2	0.0081	kg-m2		
35	Balancing	Half Key			
36	Vibration class	Grade A			
37	Position of terminal box	Top			
38	Terminal box entries; no, dims.	2xM32x1.5 + 1xM20x1.5			
39	Number of power terminals	6			
40	Direction of rotation	CW or CCW			
41	Weight of rotor	10	kg		
42	Total weight of motor	63	kg		
43					
Ex-motors					
44	Type of protection	*Ex de IIC T4			
45					
Variant Codes / Definition					
	332 = Baldor catalog number				
	461 = Exde design, group IIC				
Remarks:					
Data based on situation 11/4/2012					
All data subject to tolerances in accordance with IEC					
Guaranteed values on request					
* For more information on the Atex/IECEx rating, please contact your local Baldor representative.					

