




|          | LINE A | LINE B | JOIN  |
|----------|--------|--------|-------|
| HIGH STD | 1      | 4,5    | 2,3,8 |
| HIGH OPP | 1      | 4,8    | 2,3,5 |
| LOW STD  | 1,3,8  | 2,4,5  | —     |
| LOW OPP  | 1,3,5  | 2,4,8  | —     |

- NOTES:
1. STANDARD ROTATION IS CCW FACING END OPPOSITE SHAFT EXTENSION.
  2. OPTIONAL THERMOSTAT IS PROVIDED WHEN SPECIFIED.
  3. MULTIPLE CAPACITORS ARE CONNECTED IN PARALLEL UNLESS OTHERWISE SPECIFIED.
  4. USE STEARNS ELECTRONIC START SWITCH OR EQUIVALENT.
  5. LEAD COLORS ARE OPTIONAL. LEADS MUST ALWAYS BE NUMBERED AS SHOWN.

|                                     |         |                         |              |
|-------------------------------------|---------|-------------------------|--------------|
| REV. DESC: ADD OPTIONAL LEAD COLORS |         |                         |              |
| REV. LTR: B                         | BY: JLP | REVISED: 12/04/00 10:12 | TDR: 0226347 |
| CD0648                              |         | FILE: AAA00011416       | REF: —       |
|                                     |         | MTL: —                  |              |

BALDOR ELECTRIC Co.

TYPE L, DV, REV, 6 LEAD, SEPERATE CAP AND ELECTRONIC SWITCH