

ABB BALDOR RELIANCE III

Customer information packet 1453

7.5HP, 3000/3600RPM, 3PH, 50/60HZ, 3735M

Specifications

Enclosure	TENV
Frame Material	Steel
Frequency	50.00 Hz
	60.00 Hz
	50.00 Hz
	60.00 Hz
Motor Letter Type	Three Phase
Nameplate Output	7.5
Number of Poles	2
	2
Output @ Frequency	7.500 HP @ 60 HZ
	7.500 HP @ 50 HZ
Phase	3
	3
Product Style	GRINDER
Speed	3000 rpm
	3600 rpm
	3000 rpm
	3600 rpm
Synchronous Speed @ Frequency	3600 RPM @ 60 HZ
Voltage	208 V
	230 V
	460 V
Voltage @ Frequency	208.0 V @ 60 HZ
	230.0 V @ 50 HZ
	230.0 V @ 60 HZ
	460.0 V @ 50 HZ
	460.0 V @ 60 HZ
	208.0 V @ 50 HZ
Agency Approvals	CSA
	UR
Ambient Temperature	40 °C
Base Indicator	Rigid

Part Detail

Revision	Z
Type	AC
Mech. spec.	G14-117
Base	
Status	PRD/A
Elec. spec.	G4WG0046
Layout	G4LY0117
Eff. date	12-15-2021
CD Diagram	CD0258
Poles	02
Leads	9#14 11"FROM ENDTURN Y
Proprietary	False
Created date	01-01-0001

Current @ Voltage	20.000 A @ 230.0 V
	20.000 A @ 208.0 V
	10.000 A @ 460.0 V
	10.000 A @ 230.0 V
Design Code	B
Duty Rating	CONT
Insulation Class	B
KVA Code	-
Motor Lead Quantity/Wire Size	9 @ 14 AWG
Motor Standards	Other
Motor Type	3735M
Mounting Arrangement	F1
Product Family	Buffer
Service Factor	1.00
Shaft Extension Location	Double Shaft
Shaft Rotation	Phase Seq-Opp Std Rot (CWOE)
Speed Code	Single Speed
Starting Method	Direct on line

Nameplate

NP3411L			
CAT.NO.	1453		
HP	7.5	VOLTS	230
PHASE	3	AMPS	20
HZ	50//60	RPM	3000//3600
SER.NO			
SPEC.	G14-117A-0046G1		
BLANK			

Accessories

Part number	Description	Multiplier
GA20	PEDESTAL INDUSTRIAL, CAST IRON 8"-14"	A8



