

ABB BALDOR RELIANCE III

Customer information packet

3AUA0000134339

ACS250-03U-04A1-4+B063+D150

Specifications

Base Type Code	ACS250-03U-04A1-4+B063+D150
Enclosure	IP??, UL TYPE 4
Frame	E1
Input Phase	3
Mounting Method	3 PHASE
Normal Duty Continuous Current	4.10 a
Normal Duty Power	2.00 HP
Output Phase	3
Product Series	ACS250 DRIVE
Rated Input Voltage	480.00 V
ACB Block Diagram	3AXD10000323098.PDF
Dimensional Drawing Numbers	3AXD10000274009.PDF
Input Current Constant Torque	5.10 a
Input Frequency Max.	63 Hz
Input Frequency Min.	48 Hz
Input Voltage Max.	480.00 V
Input Voltage Min.	380.00 V
Output Frequency Max.	500 Hz
Rated Output Voltage Max.	480.00 V

Accessories

Part number	Description	Multiplier
3AUA0000150907	ACS250-DEMOCASE	
3AUA0000135610	RCRP-01 EXTERNAL LED KEYPAD	
3AUA0000135608	RCCS-01 COPYING TOOL	
3AUA0000135609	RCRO-01 RELAY OUTPUT CARD	ES
3AUA0000149995	RCRJ-01 RJ45 Y-CABLE SPLITTER	
3AUA0000149996	RCNT-01 RJ45 Y-CABLE SPLITTER W/ TERM	