

ABB BALDOR RELIANCE III

Customer information packet

3AUA0000134368

ACS250-03U-06A5-6

Specifications

Base Type Code	ACS250-03U-06A5-6
Enclosure	IP20, UL TYPE OPEN
Frame	P2
Input Phase	3
Mounting Method	3 PHASE
Normal Duty Continuous Current	6.50 a
Normal Duty Power	5.00 HP
Output Phase	3
Product Series	ACS250 DRIVE
Rated Input Voltage	600.00 V
ACB Block Diagram	3AXD10000323098.PDF
Dimensional Drawing Numbers	3AXD10000274014.PDF
Input Current Constant Torque	7.10 a
Input Frequency Max.	63 Hz
Input Frequency Min.	48 Hz
Input Voltage Max.	600.00 V
Input Voltage Min.	500.00 V
Output Frequency Max.	500 Hz
Rated Output Voltage Max.	600.00 V

Accessories

Part number	Description	Multiplier
3AUA00000150907	ACS250-DEMOCASE	
3AUA00000135610	RCRP-01 EXTERNAL LED KEYPAD	
3AUA00000135608	RCCS-01 COPYING TOOL	
3AUA00000135609	RCRO-01 RELAY OUTPUT CARD	ES
3AUA00000149995	RCRJ-01 RJ45 Y-CABLE SPLITTER	
3AUA00000149996	RCNT-01 RJ45 Y-CABLE SPLITTER W/ TERM	
3AUA00000064072	P14494-CR-22	
3AUA00000015096	P14494-13	
3AUA00000015097	P14494-14	
3AUA00000015100	P14494-18	