

ABB BALDOR RELIANCE III

Customer information packet

3AUA0000143114

ACS250-03U-02A3-2+B063

Specifications

Base Type Code	ACS250-03U-02A3-2+B063
Enclosure	IP??, UL TYPE 4
Frame	E1
Input Phase	3
Mounting Method	3 PHASE
Normal Duty Continuous Current	2.30 a
Normal Duty Power	0.50 HP
Output Phase	3
Product Series	ACS250 DRIVE
Rated Input Voltage	240.00 V
ACB Block Diagram	3AXD10000323098.PDF
Dimensional Drawing Numbers	3AXD10000274009.PDF
Input Current Constant Torque	3.80 a
Input Frequency Max.	63 Hz
Input Frequency Min.	48 Hz
Input Voltage Max.	240.00 V
Input Voltage Min.	208.00 V
Output Frequency Max.	500 Hz
Rated Output Voltage Max.	240.00 V

Accessories

Part number	Description	Multiplier
3AUA0000150907	ACS250-DEMOCASE	
3AUA0000135610	RCRP-01 EXTERNAL LED KEYPAD	
3AUA0000135608	RCCS-01 COPYING TOOL	
3AUA0000135609	RCRO-01 RELAY OUTPUT CARD	ES
3AUA0000149995	RCRJ-01 RJ45 Y-CABLE SPLITTER	
3AUA0000149996	RCNT-01 RJ45 Y-CABLE SPLITTER W/ TERM	