

ABB BALDOR RELIANCE III

Customer information packet

68582121

ACS150-03U-05A6-4

Specifications

Base Type Code	ACS150-03U-05A6-4
Enclosure	IP20, UL TYPE OPEN
Frame	R1
Input Phase	3
Mounting Method	3 PHASE
Normal Duty Continuous Current	5.60 a
Normal Duty Power	3.00 HP
Output Phase	3
Product Series	ACS150 DRIVE
Rated Input Voltage	480.00 V
ACB Block Diagram	68647398.PDF
Dimensional Drawing Numbers	68637902.PDF
Input Current Constant Torque	8.00 a
Input Frequency Max.	63 Hz
Input Frequency Min.	48 Hz
Input Voltage Max.	480.00 V
Input Voltage Min.	380.00 V
Output Frequency Max.	500 Hz
Rated Output Voltage Max.	480.00 V

Accessories

Part number	Description	Multiplier
68566380	FLASHDROP MFDT-01	ES
68566398	MUL1-R1 R1 UL TYPE 1 OPTI	ES
3AUA0000064061	P14494-CR-11	
3AUA0000064080	P14494-CR-30	
3AUA0000013679	P14494-15	
3AUA0000013865	P14494-16	
3AUA0000064072	P14494-CR-22	