

ABB BALDOR RELIANCE III

Customer information packet

68582199

ACS150-01U-07A5-2

Specifications

Base Type Code	ACS150-01U-07A5-2
Enclosure	IP20, UL TYPE OPEN
Frame	R2
Input Phase	3
Mounting Method	1 PHASE
Normal Duty Continuous Current	7.50 a
Normal Duty Power	2.00 HP
Output Phase	3
Product Series	ACS150 DRIVE
Rated Input Voltage	240.00 V
ACB Block Diagram	68647398.PDF
Dimensional Drawing Numbers	68613264.PDF
Input Current Constant Torque	16.80 a
Input Frequency Max.	63 Hz
Input Frequency Min.	48 Hz
Input Voltage Max.	240.00 V
Input Voltage Min.	208.00 V
Output Frequency Max.	500 Hz
Rated Output Voltage Max.	240.00 V

Accessories

Part number	Description	Multiplier
68566380	FLASHDROP MFDT-01	ES
68566398	MUL1-R1 R1 UL TYPE 1 OPTI	ES
3AUA0000064053	P14494-CR-04	
3AUA0000064072	P14494-CR-22	
3AUA0000015112	P14494-31	
3AUA0000064066	P14494-CR-16	
3AUA0000064080	P14494-CR-30	
3AUA0000013872	P14494-32	