

ABB BALDOR RELIANCE III

Customer information packet 68582288

ACS150-03U-09A8-2

Specifications

Base Type Code	ACS150-03U-09A8-2
Enclosure	IP20, UL TYPE OPEN
Frame	R2
Input Phase	3
Mounting Method	3 PHASE
Normal Duty Continuous Current	9.80 a
Normal Duty Power	3.00 HP
Output Phase	3
Product Series	ACS150 DRIVE
Rated Input Voltage	240.00 V
ACB Block Diagram	68647398.PDF
Dimensional Drawing Numbers	68613264.PDF
Input Current Constant Torque	14.30 a
Input Frequency Max.	63 Hz
Input Frequency Min.	48 Hz
Input Voltage Max.	240.00 V
Input Voltage Min.	208.00 V
Output Frequency Max.	500 Hz
Rated Output Voltage Max.	240.00 V

Accessories

Part number	Description	Multiplier
68566380	FLASHDROP MFDT-01	ES
68566398	MUL1-R1 R1 UL TYPE 1 OPTI	ES
3AUA0000064062	P14494-CR-12	
3AUA0000064083	P14494-CR-32	EF
3AUA0000015112	P14494-31	
3AUA0000013872	P14494-32	
3AUA0000064074	P14494-CR-24	