

ABB BALDOR RELIANCE III

Customer information packet

AOM3546T

1HP, 1725RPM, 3PH, 60HZ, 143T, 3428M, TEAO, F1

Class - None

Division - Not Applicable

Specifications

Enclosure	TEAO
Frame	143T
Frame Material	Steel
Frequency	60.00 Hz
Haz Area Class and Group	None
Haz Area Division	Not Applicable
Motor Letter Type	Three Phase
Output @ Frequency	1.000 HP @ 60 HZ
Phase	3
Synchronous Speed @ Frequency	1800 RPM @ 60 HZ
Voltage @ Frequency	460.0 V @ 60 HZ 230.0 V @ 60 HZ 208.0 V @ 60 HZ
Agency Approvals	CSA UR
Ambient Temperature	40 °C
Auxiliary Box	NO AUXILLARY BOX
Auxiliary Box Lead Termination	None
Base Indicator	Rigid
Bearing Grease Type	Polyrex EM (-20F +300F)
Blower	None
Current @ Voltage	3.800 A @ 208.0 V 3.600 A @ 230.0 V 1.800 A @ 460.0 V
Design Code	B
Drip Cover	No Drip Cover
Duty Rating	CONT
Efficiency @ 100% Load	75.5 %
Electrically Isolated Bearing	Not Electrically Isolated
Feedback Device	NO FEEDBACK
Front Face Code	Standard
Front Shaft Indicator	None

Part Detail

Revision	Z
Type	AC
Mech. spec.	34T061
Base	
Status	PRD/A
Elec. spec.	34WG3254
Layout	34LYT061
Eff. date	10-28-2024
CD Diagram	CD0005
Poles	04
Leads	9#18 36" LG Y
Proprietary	False
Created date	01-01-0001

Heater Indicator	No Heater
High Voltage Full Load Amps	1.8 a
Insulation Class	B
Inverter Code	Not Inverter
KVA Code	L
Lifting Lugs	No Lifting Lugs
Locked Bearing Indicator	No Locked Bearing
Motor Lead Exit	Ko Box
Motor Lead Quantity/Wire Size	9 @ 18 AWG
Motor Lead Termination	Flying Leads
Motor Standards	NEMA
Motor Type	3428M
Mounting Arrangement	F1
Number of Poles	4
Overall Length	11.81 IN
Power Factor	64
Product Family	General Purpose
Pulley End Bearing Type	Ball
Pulley Face Code	Standard
Pulley Shaft Indicator	Standard
Rodent Screen	None
Service Factor	1.15
Shaft Diameter	0.875 IN
Shaft Extension Location	Pulley End
Shaft Ground Indicator	No Shaft Grounding
Shaft Rotation	Reversible
Shaft Slinger Indicator	No Slinger
Speed	1725 rpm
Speed Code	Single Speed
Starting Method	Direct on line
Thermal Device - Bearing	None
Thermal Device - Winding	None
Vibration Sensor Indicator	No Vibration Sensor
Winding Thermal 1	None

Winding Thermal 2

None

Nameplate

NP1256L											
CAT.NO.	AOM3546T										
SPEC.	34T61-3254										
HP	1 AIR OVER										
VOLTS	208-230/460										
AMP	3.8-3.6/1.8										
RPM	1725										
FRAME	143T		HZ	60				PH	3		
SER.F.	1.00	CODE	L	DES	B	CLASS			B		
NEMA-NOM-EFF	75.5	PF	64								
RATING	40C AMB-CONT										
CC											
DE	6205		ODE	6203							
ENCL	TEAO	SN									
	1000 FPM AT 44 CFM										

Accessories

Part number	Description	Multiplier
34-3903T	C FACE KIT	A8

AC Induction Motor Performance Data

Record # 30736

Typical performance - not guaranteed values

Winding: 34WG3254-R014		Type: 3428M	Enclosure: XPFC
Nameplate Data		460 V, 60 Hz: High Voltage Connection	
Rated Output (HP)	1	Full Load Torque	3 LB-FT
Volts	208-230/460	Start Configuration	direct on line
Full Load Amps	3.8-3.6/1.8	Breakdown Torque	14.6 LB-FT
R.P.M.	1725	Pull-up Torque	12.5 LB-FT
Hz	60 Phase	Locked-rotor Torque	15.8 LB-FT
NEMA Design Code	B KVA Code	Starting Current	14.6 A
Service Factor (S.F.)	1	No-load Current	1.3 A
NEMA Nom. Eff.	75.5 Power Factor	Line-line Res. @ 25°C	12.3 Ω
Rating - Duty	40C AMB-CONT	Temp. Rise @ Rated Load	66°C
		Locked-rotor Power Factor	54
		Rotor inertia	0.0667 LB-FT2

Load Characteristics 460 V, 60 Hz, 1 HP

% of Rated Load	25	50	75	100	125	150
Power Factor	31	46	57	66	72	76
Efficiency	57.8	70.5	76	77.3	78.6	76.5
Speed	1786	1773	1760	1747	1734	1716
Line amperes	1.35	1.47	1.63	1.84	2.06	2.38


ABB Motors and Mechanical Inc.


WINDING # 34WG3254


Typical performance - not guaranteed values.

1 HP 3 PH 60 HZ 1725 RPM 460 V 3428M

TORQUES (LB-FT): PO=14.6 PU=12.5 LR=15.8 LRA=14.6







CD0005