

ABB BALDOR RELIANCE III

Customer information packet

CECP83660T-4

3HP, 3450RPM, 3PH, 60HZ, 182TC, 0632M, TEFC, F1

Class - CLI GP A,B,C,D

Division - Division II

Specifications

Enclosure	TEFC
Frame	182TC
Frame Material	Iron
Frequency	60.00 Hz
Haz Area Class and Group	CLI GP A,B,C,D
Haz Area Division	Division II
Motor Letter Type	Three Phase
Output @ Frequency	3.000 HP @ 60 HZ
Phase	3
Synchronous Speed @ Frequency	3600 RPM @ 60 HZ
Voltage @ Frequency	460.0 V @ 60 HZ
Agency Approvals	CCSA US CSA CSA EEV NEMA PREMIUM NEMA_PREMIUM UR
Ambient Temperature	40 °C
Auxiliary Box	NO AUXILLARY BOX
Auxiliary Box Lead Termination	None
Base Indicator	Rigid
Bearing Grease Type	Polyrex EM (-20F +300F)
Blower	None
Constant Torque Speed Range	6
Current @ Voltage	3.400 A @ 460.0 V
Design Code	B
Drip Cover	No Drip Cover
Duty Rating	CONT
Efficiency @ 100% Load	88.5 %
Electrically Isolated Bearing	Not Electrically Isolated
Feedback Device	NO FEEDBACK
Front Face Code	Standard

Part Detail

Revision	AW
Type	AC
Mech. spec.	06H770
Base	
Status	PRD/A
Elec. spec.	06WGW822
Layout	06LYH770
Eff. date	01-29-2026
CD Diagram	CD0006
Poles	02
Leads	3#16
Proprietary	False
Created date	06-20-2005

Front Shaft Indicator	None
Haz Area Temp Code	T3C
Heater Indicator	No Heater
High Voltage Full Load Amps	3.4 a
Insulation Class	F
Inverter Code	Inverter Duty
KVA Code	K
Lifting Lugs	Standard Lifting Lugs
Locked Bearing Indicator	Locked Bearing
Max Speed	5400 rpm
Motor Lead Exit	Ko Box
Motor Lead Quantity/Wire Size	3 @ 16 AWG
Motor Lead Termination	Flying Leads
Motor Standards	NEMA
Motor Type	0632M
Mounting Arrangement	F1
Number of Poles	2
Overall Length	16.69 IN
Power Factor	94
Product Family	Chem Process S/P 32-8 IEEE 841
Pulley End Bearing Type	Ball
Pulley Face Code	C-Face
Pulley Shaft Indicator	Standard
Rodent Screen	None
Service Factor	1.15
Shaft Diameter	1.125 IN
Shaft Extension Location	Pulley End
Shaft Ground Indicator	No Shaft Grounding
Shaft Rotation	Reversible
Shaft Slinger Indicator	Shaft Slinger
Speed	3450 rpm
Speed Code	Single Speed
Starting Method	Direct on line
Thermal Device - Bearing	None

Thermal Device - Winding	None
Vibration Sensor Indicator	No Vibration Sensor
Winding Thermal 1	None
Winding Thermal 2	None

Nameplate

NP4328									
CAT.NO.	CECP83660T-4								
SPEC.	06H770W822								
HP	3 TE				IP	56			
VOLTS	460								
AMPS	3.4								
R.P.M.	3450								
FRAME	182TC		HZ		60		PH	3	
SER.F.	1.15	CODE	K	DES.	B	CLASS		F	
RATING	40C AMB-CONT								
SN									
DE	6206		ODE		6206				
NEMA NOM. EFF.	88.5		P.F.		94				
GUAR. MIN. EFF.	86.5		CC		010A				
T. CODE	T3C		TEMP=		160				

NP3186					
SPEC.	06H770W822				
ABMA DE BRG	30BC02XP30X				
ABMA ODE BRG	30BC02X30X				
GREASE	POLYREX EM				
MOTOR WEIGHT	121	ROTOR BARS	28	STATOR BARS	36
MAX. R.P.M.	5400	MAX. KVAR	N/A		
INV.TYPE	PWM				
T=	160				
CHP	60	TO	90		
CT	6	TO	60		
VT	3	TO	60		
HTR-VOLTS	N/A	HTR-AMPS	N/A		
HTR-WATTS		MAX. SPACE HEATER TEMP.			N/A

AC Induction Motor Performance Data

Record # 47353

Typical performance - not guaranteed values

Winding: 06GW822-R012			Type: 0632M		Enclosure: TEFC	
Nameplate Data			460 V, 60 Hz: Single Voltage Motor			
Rated Output (HP)		3	Full Load Torque		4.52 LB-FT	
Volts		460	Start Configuration		direct on line	
Full Load Amps		3.4	Breakdown Torque		19.1 LB-FT	
R.P.M.		3450	Pull-up Torque		12.9 LB-FT	
Hz	60	Phase	Locked-rotor Torque		15.1 LB-FT	
NEMA Design Code	B	KVA Code	Starting Current		32.2 A	
Service Factor (S.F.)		1.15	No-load Current		0.8 A	
NEMA Nom. Eff.	88.5	Power Factor	Line-line Res. @ 25°C		4.03 Ω	
Rating - Duty		40C AMB-CONT	Temp. Rise @ Rated Load		35°C	
S.F. Amps			Temp. Rise @ S.F. Load		43°C	
			Locked-rotor Power Factor		42.1	
			Rotor inertia		0.144 LB-FT2	

Load Characteristics 460 V, 60 Hz, 3 HP

% of Rated Load	25	50	75	100	125	150	S.F.
Power Factor	72	86	92	94	95	95	95
Efficiency	82	87.8	88.8	88.4	87.4	85.9	87.8
Speed	3569	3542	3512	3480	3447	3409	3460
Line amperes	1.18	1.85	2.58	3.4	4.25	5.13	3.91


ABB Motors and Mechanical Inc.


WINDING # 06WGW822

Typical performance - not guaranteed values.




3 HP 3 PH 60 HZ 3450 RPM 460 V 0632M

TORQUES (LB-FT): PO=19.1 PU=12.9 LR=15.1 LRA=32.2





CD0006


NOTES:

1. THREE LEAD MOTOR MAY BE EITHER WYE CONNECTED OR DELTA CONNECTED.
2. INTERCHANGE ANY TWO LINE LEADS TO REVERSE ROTATION.
3. OPTIONAL THERMOSTATS ARE PROVIDED WHEN SPECIFIED.
4. ACTUAL NUMBER OF INTERNAL PARALLEL CIRCUITS MAY VARY.
5. LEAD COLORS ARE OPTIONAL. LEADS MUST BE NUMBERED AS SHOWN.

CD0006

REV. DESC: ADD CLASS CONN00000007

REV. LTR: E

VERSION: 01

TDR: 000001099922

FILE: \AAA\00005\141

REVISED: 10:24:49 02/19/2019

BY: ENBRIRO

MTL: —


BALDOR - RELIANCE®

3PH, SV, 3 LEADS, WYE OR DELTA CONNECTED

SH 1 of 1