

ABB BALDOR RELIANCE III

Customer information packet

CECR9154T

15HP, 1765RPM, 3PH, 60HZ, 254T, TEFC, F1

Class - None

Division - Not Applicable

Specifications

Enclosure	TEFC
Frame	254TC
Frame Material	Iron
Frequency	60.00 Hz
Haz Area Class and Group	None
Haz Area Division	Not Applicable
Motor Letter Type	Three Phase
Output @ Frequency	15.000 HP @ 60 HZ
Phase	3
Synchronous Speed @ Frequency	1800 RPM @ 60 HZ
Voltage @ Frequency	460.0 V @ 60 HZ 230.0 V @ 60 HZ
Agency Approvals	UR CCSA US NEMA_PREMIUM NEMA PREMIUM CSA EEV
Ambient Temperature	40 °C
Auxiliary Box	NO AUXILLARY BOX
Auxiliary Box Lead Termination	None
Base Indicator	Rigid
Bearing Grease Type	Polyrex EM (-20F +300F)
Blower	None
Constant Torque Speed Range	6
Current @ Voltage	18.600 A @ 460.0 V 37.200 A @ 230.0 V 40.000 A @ 208.0 V
Design Code	A
Drip Cover	No Drip Cover
Duty Rating	CONT
Efficiency @ 100% Load	92.4 %
Electrically Isolated Bearing	Not Electrically Isolated

Part Detail

Revision	N
Type	AC
Mech. spec.	09M408
Base	
Status	PRD/A
Elec. spec.	09WGT152
Layout	09LYM408
Eff. date	11-14-2023
CD Diagram	CD0180
Poles	04
Leads	9#12
Proprietary	False
Created date	02-21-2019

Enclosure Modification	Severe Duty Features
Feedback Device	NO FEEDBACK
Front Shaft Indicator	None
Heater Indicator	No Heater
High Voltage Full Load Amps	18.6 a
Insulation Class	F
Inverter Code	Inverter Duty
IP Rating	IP55
KVA Code	H
Lifting Lugs	Standard Lifting Lugs
Locked Bearing Indicator	Locked Bearing
Max Speed	2700 rpm
Motor Lead Quantity/Wire Size	9 @ 12 AWG
Motor Lead Termination	Flying Leads
Motor Standards	NEMA
Motor Type	0948M
Mounting Arrangement	F1
Number of Poles	4
Overall Length	25.28 IN
Power Factor	82
Product Family	Super-E Chemical Processing
Pulley End Bearing Type	Ball
Pulley Face Code	C-Face
Pulley Shaft Indicator	Standard
Rodent Screen	None
Service Factor	1.25
Shaft Diameter	1.625 IN
Shaft Ground Indicator	No Shaft Grounding
Shaft Rotation	Reversible
Shaft Slinger Indicator	Shaft Slinger
Speed	1765 rpm
Speed Code	Single Speed
Starting Method	Direct on line
Thermal Device - Bearing	None



Thermal Device - Winding	None
Vibration Sensor Indicator	No Vibration Sensor
Winding Thermal 1	None
Winding Thermal 2	None

Nameplate

NP3293																	
CAT.NO.	CECR9154T			P/N					ENCLOSURE		TEFC						
SPEC.	09M408T152G1		CC	010A	FRAME		254TC		S/N								
HP	15		CLASS		F	HZ		60	DES		A						
RPM	1765		RPM MAX		2700		PH		3	KVA-CODE		H					
VOLT	230/460					I.P.		55									
AMP	37.2/18.6			SER.F.		1.25		PF		82	ODE BRG		6309		DE BRG		6311
RATING	40C AMB-CONT			NEMA-NOM-EFF				92.4		GREASE		POLYREX EM					
HTR-VOLTS	HTR-AMPS		HTR-WATTS					INV.TYPE									
	SFA 46/23																
				C HP FR		60		C HP TO		90							
				CT HZ FROM			6		CT HZ TO			60					
				MOTOR WEIGHT				286		VT HZ FROM			6		VT HZ TO		60

AC Induction Motor Performance Data

Record # 48597

Typical performance - not guaranteed values

Winding: 09WGT152-R001			Type: 0948M		Enclosure: TEFC		
Nameplate Data			460 V, 60 Hz: High Voltage Connection				
Rated Output (HP)		15	Full Load Torque		44.7 LB-FT		
Volts		230/460	Start Configuration		direct on line		
Full Load Amps		37.2/18.6	Breakdown Torque		145 LB-FT		
R.P.M.		1765	Pull-up Torque		78.4 LB-FT		
Hz	60	Phase	3	Locked-rotor Torque		119 LB-FT	
NEMA Design Code		A	KVA Code	H		Starting Current	120 A
Service Factor (S.F.)		1.25	No-load Current		7.67 A		
NEMA Nom. Eff.		92.4	Power Factor	82		Line-line Res. @ 25°C	0.548 Ω
Rating - Duty		40C	AMB-CONT		Temp. Rise @ Rated Load		53°C
S.F. Amps		46/23	Temp. Rise @ S.F. Load		65°C		
			Locked-rotor Power Factor		39.5		
			Rotor inertia		2.09 lb-ft²		

Load Characteristics 460 V, 60 Hz, 15 HP

% of Rated Load	25	50	75	100	125	150	S.F.
Power Factor	45	67	77	82	84	84	83
Efficiency	89	92.5	93	92.6	91.7	90.5	92.1
Speed	1793	1786	1777	1768	1758	1747	1762
Line amperes	8.81	11.3	14.7	18.6	23	27.7	21.2


ABB Motors and Mechanical Inc.


WINDING # 09WGT152

Typical performance - not guaranteed values.


15 HP 3 PH 60 HZ 1765 RPM 460 V 0948M

TORQUES (LB-FT): PO=145 PU=78.4 LR=119 LRA=120







CD0180



LOW VOLTAGE
(2D)



HIGH VOLTAGE
(1D)



NOTES:

1. INTERCHANGE ANY TWO LINE LEADS TO REVERSE ROTATION.
2. OPTIONAL THERMOSTATS ARE PROVIDED WHEN SPECIFIED.
3. ACTUAL NUMBER OF INTERNAL PARALLEL CIRCUITS MAY BE A MULTIPLE OF THOSE SHOWN ABOVE.
4. LEAD COLORS ARE OPTIONAL. LEADS MUST ALWAYS BE NUMBERED AS SHOWN.

CD0180

REV. DESC: ADD CLASS CONN00000007

REV. LTR: D

VERSION: 01

TDR: 000001099922

FILE: \AAA\00005\148

REVISED: 10: 25: 29 02/19/2019

BY: ENBRIRO

MTL: -



BALDOR - RELIANCE®

3PH, DV, 9 LEADS, DELTA CONNECTION

SH 1 of 1