

# ABB BALDOR RELIANCE III

---

## Customer information packet

### CEM3771T

10HP, 3485RPM, 3PH, 60HZ, 215TC, 0730M, TEFC, F

Class - None

Division - Not Applicable

**Specifications**

|                                |                                                                |
|--------------------------------|----------------------------------------------------------------|
| Enclosure                      | TEFC                                                           |
| Frame                          | 215TC                                                          |
| Frame Material                 | Iron                                                           |
| Frequency                      | 60.00 Hz                                                       |
| Haz Area Class and Group       | None                                                           |
| Haz Area Division              | Not Applicable                                                 |
| Motor Letter Type              | Three Phase                                                    |
| Output @ Frequency             | 10.000 HP @ 60 HZ                                              |
| Phase                          | 3                                                              |
| Synchronous Speed @ Frequency  | 3600 RPM @ 60 HZ                                               |
| Voltage @ Frequency            | 230.0 V @ 60 HZ<br>460.0 V @ 60 HZ                             |
| Agency Approvals               | CURUSEEV<br>NEMA PREMIUM                                       |
| Ambient Temperature            | 40 °C                                                          |
| Auxiliary Box                  | NO AUXILLARY BOX                                               |
| Auxiliary Box Lead Termination | None                                                           |
| Base Indicator                 | Rigid                                                          |
| Bearing Grease Type            | Polyrex EM (-20F +300F)                                        |
| Blower                         | None                                                           |
| Current @ Voltage              | 11.700 A @ 460.0 V<br>23.400 A @ 230.0 V<br>25.200 A @ 208.0 V |
| Design Code                    | B                                                              |
| Drip Cover                     | No Drip Cover                                                  |
| Duty Rating                    | CONT                                                           |
| Efficiency @ 100% Load         | 90.2 %                                                         |
| Electrically Isolated Bearing  | Not Electrically Isolated                                      |
| Feedback Device                | NO FEEDBACK                                                    |
| Front Shaft Indicator          | None                                                           |
| Heater Indicator               | No Heater                                                      |
| High Voltage Full Load Amps    | 11.7 a                                                         |

**Part Detail**

|              |            |
|--------------|------------|
| Revision     | E          |
| Type         | AC         |
| Mech. spec.  | 07H058     |
| Base         |            |
| Status       | PRD/A      |
| Elec. spec.  | 07WGT516   |
| Layout       | 07LYH058   |
| Eff. date    | 08-10-2026 |
| CD Diagram   | CD0005     |
| Poles        | 02         |
| Leads        | 9#14       |
| Proprietary  | False      |
| Created date | 01-05-2021 |

|                                      |                       |
|--------------------------------------|-----------------------|
| <b>Insulation Class</b>              | F                     |
| <b>Inverter Code</b>                 | Inverter Ready        |
| <b>KVA Code</b>                      | G                     |
| <b>Lifting Lugs</b>                  | Standard Lifting Lugs |
| <b>Locked Bearing Indicator</b>      | Locked Bearing        |
| <b>Motor Lead Quantity/Wire Size</b> | 9 @ 14 AWG            |
| <b>Motor Lead Termination</b>        | Flying Leads          |
| <b>Motor Standards</b>               | NEMA                  |
| <b>Motor Type</b>                    | 0730M                 |
| <b>Mounting Arrangement</b>          | F1                    |
| <b>Number of Poles</b>               | 2                     |
| <b>Overall Length</b>                | 19.20 IN              |
| <b>Power Factor</b>                  | 88                    |
| <b>Product Family</b>                | General Purpose       |
| <b>Pulley End Bearing Type</b>       | Ball                  |
| <b>Pulley Face Code</b>              | C-Face                |
| <b>Pulley Shaft Indicator</b>        | Standard              |
| <b>Rodent Screen</b>                 | None                  |
| <b>Service Factor</b>                | 1.15                  |
| <b>Shaft Diameter</b>                | 1.375 IN              |
| <b>Shaft Ground Indicator</b>        | No Shaft Grounding    |
| <b>Shaft Rotation</b>                | Reversible            |
| <b>Shaft Slinger Indicator</b>       | No Slinger            |
| <b>Speed</b>                         | 3485 rpm              |
| <b>Speed Code</b>                    | Single Speed          |
| <b>Starting Method</b>               | Direct on line        |
| <b>Thermal Device - Bearing</b>      | None                  |
| <b>Thermal Device - Winding</b>      | None                  |
| <b>Vibration Sensor Indicator</b>    | No Vibration Sensor   |
| <b>Winding Thermal 1</b>             | None                  |
| <b>Winding Thermal 2</b>             | None                  |

Nameplate

| NP3441LUA                 |                              |  |      |      |     |   |       |       |  |
|---------------------------|------------------------------|--|------|------|-----|---|-------|-------|--|
| CAT.NO.                   | CEM3771T                     |  |      |      |     |   |       |       |  |
| SPEC                      | 07H058T516G1                 |  |      |      |     |   |       |       |  |
| HP                        | 10                           |  |      |      |     |   |       |       |  |
| VOLTS                     | 230/460                      |  |      |      |     |   |       |       |  |
| AMPS                      | 23.4/11.7                    |  |      |      |     |   |       |       |  |
| RPM                       | 3485                         |  |      |      |     |   |       |       |  |
| FRAME                     | 215TC                        |  | HZ   | 60   |     |   | PH    | 3     |  |
| SF                        | 1.15                         |  | CODE | G    | DES | B | CLASS | F     |  |
| NEMA NOM. EFF             | 90.2                         |  | PF   | 88   |     |   |       |       |  |
| RATING                    | 40C AMB-CONT                 |  |      |      |     |   |       |       |  |
| CC                        | 010A                         |  |      |      |     |   |       |       |  |
| ENCL                      | TEFC                         |  | SER  |      |     |   |       |       |  |
| DE                        | 6307                         |  | ODE  | 6206 |     |   |       |       |  |
| VPWM INVERTER READY       |                              |  |      |      |     |   |       |       |  |
| CT6-60H(10:1)VT3-60H(20:1 |                              |  |      |      |     |   |       |       |  |
|                           | 50HZ 10HP 190/380V 30/15.0 A |  |      |      |     |   |       | SF1.0 |  |

**AC Induction Motor Performance Data**

Record # 86063

Typical performance - not guaranteed values

| Winding: 07WGT516-R001 |      |              | Type: 0730M                              |                       | Enclosure: TEFC |  |
|------------------------|------|--------------|------------------------------------------|-----------------------|-----------------|--|
| Nameplate Data         |      |              | 460 V, 60 Hz:<br>High Voltage Connection |                       |                 |  |
| Rated Output (HP)      |      | 10           | Full Load Torque                         |                       | 15.1 LB-FT      |  |
| Volts                  |      | 230/460      | Start Configuration                      |                       | direct on line  |  |
| Full Load Amps         |      | 23.4/11.7    | Breakdown Torque                         |                       | 44.8 LB-FT      |  |
| R.P.M.                 |      | 3485         | Pull-up Torque                           |                       | 16.4 LB-FT      |  |
| Hz                     | 60   | Phase        | 3                                        | Locked-rotor Torque   | 23.5 LB-FT      |  |
| NEMA Design Code       | B    | KVA Code     | G                                        | Starting Current      | 75.4 A          |  |
| Service Factor (S.F.)  |      | 1.15         | No-load Current                          |                       | 3.77 A          |  |
| NEMA Nom. Eff.         | 90.2 | Power Factor | 88                                       | Line-line Res. @ 25°C | 1.13 Ω          |  |
| Rating - Duty          |      | 40C AMB-CONT | Temp. Rise @ Rated Load                  |                       | 68°C            |  |
| S.F. Amps              |      | 27/13.5      | Temp. Rise @ S.F. Load                   |                       | 91°C            |  |
|                        |      |              | Locked-rotor Power Factor                |                       | 39.1            |  |
|                        |      |              | Rotor inertia                            |                       | 0.273 lb-ft²    |  |

**Load Characteristics 460 V, 60 Hz, 10 HP**

| % of Rated Load | 25   | 50   | 75   | 100  | 125  | 150  | S.F. |
|-----------------|------|------|------|------|------|------|------|
| Power Factor    | 57   | 78   | 85   | 88   | 89   | 89   | 89   |
| Efficiency      | 87.7 | 91.1 | 91.1 | 90.2 | 88.5 | 86.6 | 89.3 |
| Speed           | 3573 | 3547 | 3518 | 3486 | 3451 | 3410 | 3466 |
| Line amperes    | 4.65 | 6.59 | 9.02 | 11.7 | 14.8 | 18.1 | 13.5 |


ABB Motors and Mechanical Inc.


WINDING # 07WGT516

Typical performance - not guaranteed values.



10 HP 3 PH 60 HZ 3485 RPM 460 V 0730M

TORQUES (LB-FT) : PO=44.8 PU=16.4 LR=23.5 LRA=75.4





CD0005



- NOTES:
- 1. INTERCHANGE ANY TWO LINE LEADS TO REVERSE ROTATION.
  - 2. OPTIONAL THERMOSTATS ARE PROVIDED WHEN SPECIFIED.
  - 3. ACTUAL NUMBER OF INTERNAL PARALLEL CIRCUITS MAY BE A MULTIPLE OF THOSE SHOWN ABOVE.
  - 4. LEAD COLORS ARE OPTIONAL. LEADS MUST ALWAYS BE NUMBERED AS SHOWN.

|                                           |         |                         |              |
|-------------------------------------------|---------|-------------------------|--------------|
| REV. DESC: REVISE TO SHOW OPTIONAL COLORS |         |                         |              |
| REV. LTR: E                               | BY: JLP | REVISED: 01/19/99 10:15 | TDR: 0171435 |
| S00000                                    |         | FILE: AAA00005140       | MDL: -       |
|                                           |         | MTL: -                  |              |

**BALDOR ELECTRIC Co.**

3PH, DV, 9 LEADS

CD0005