

ABB BALDOR RELIANCE III

Customer information packet

CESSWDM3550T

1.5HP, 3500RPM, 3PH, 60HZ, 143TC, 3532M, TENV

Class - None

Division - Not Applicable

Specifications

Enclosure	TENV
Frame	143TC
Frame Material	Stainless Steel
Frequency	60.00 Hz
Haz Area Class and Group	None
Haz Area Division	Not Applicable
Motor Letter Type	Three Phase
Output @ Frequency	1.500 HP @ 60 HZ
Phase	3
Synchronous Speed @ Frequency	3600 RPM @ 60 HZ
Voltage @ Frequency	460.0 V @ 60 HZ 230.0 V @ 60 HZ 208.0 V @ 60 HZ
Agency Approvals	CSA UR
Ambient Temperature	40 °C
Auxiliary Box	NO AUXILLARY BOX
Auxiliary Box Lead Termination	None
Base Indicator	Rigid
Bearing Grease Type	Polyrex EM (-20F +300F)
Blower	None
Current @ Voltage	3.700 A @ 208.0 V 3.600 A @ 230.0 V 1.800 A @ 460.0 V
Design Code	B
Drip Cover	No Drip Cover
Duty Rating	CONT
Efficiency @ 100% Load	85.5 %
Electrically Isolated Bearing	Not Electrically Isolated
Feedback Device	NO FEEDBACK
Front Face Code	Standard
Front Shaft Indicator	None

Part Detail

Revision	U
Type	AC
Mech. spec.	35WW513
Base	
Status	PRD/A
Elec. spec.	35WGR929
Layout	35LYWW513
Eff. date	06-14-2024
CD Diagram	CD0005
Poles	02
Leads	9#18
Proprietary	False
Created date	02-17-2010

Heater Indicator	No Heater
High Voltage Full Load Amps	1.8 a
Insulation Class	F
Inverter Code	Inverter Ready
KVA Code	M
Lifting Lugs	No Lifting Lugs
Locked Bearing Indicator	Locked Bearing
Motor Lead Exit	Ko Box
Motor Lead Quantity/Wire Size	9 @ 18 AWG
Motor Lead Termination	Flying Leads
Motor Standards	NEMA
Motor Type	3532M
Mounting Arrangement	F1
Number of Poles	2
Overall Length	13.23 IN
Power Factor	90
Product Family	Wash Down All Stainless Steel
Pulley End Bearing Type	Sealed Bearing
Pulley Face Code	C-Face
Pulley Shaft Indicator	Standard
Rodent Screen	None
Service Factor	1.15
Shaft Diameter	0.875 IN
Shaft Extension Location	Pulley End
Shaft Ground Indicator	No Shaft Grounding
Shaft Rotation	Reversible
Shaft Slinger Indicator	No Slinger
Speed	3500 rpm
Speed Code	Single Speed
Starting Method	Direct on line
Thermal Device - Bearing	None
Thermal Device - Winding	None
Vibration Sensor Indicator	No Vibration Sensor
Winding Thermal 1	None

Winding Thermal 2

None

Nameplate

NP1953A01											
CAT.NO.	CESSWDM3550T										
SPEC.	35WW513R929G1										
HP	1.5										
VOLTS	230/460										
AMP	3.6/1.8										
RPM	3500										
FRAME	143TC			HZ		60		PH		3	
SER.F.	1.15		CODE		M	DES		B	CLASS		F
NEMA-NOM-EFF	85.5			PF		90					
RATING	40C AMB-CONT										
CC											
DE	6205			ODE		6203					
ENCL	TENV		SN								
	4:1CT 20:1VT										

AC Induction Motor Performance Data

Record # 69834

Typical performance - not guaranteed values

Winding: 35WGR929-R010			Type: 3532M		Enclosure: TENV		
Nameplate Data			460 V, 60 Hz: High Voltage Connection				
Rated Output (HP)		1.5	Full Load Torque		2.31 LB-FT		
Volts		230/460	Start Configuration		direct on line		
Full Load Amps		3.6/1.8	Breakdown Torque		10.9 LB-FT		
R.P.M.		3500	Pull-up Torque		5.2 LB-FT		
Hz	60	Phase	3	Locked-rotor Torque		10.2 LB-FT	
NEMA Design Code		B	KVA Code	M	Starting Current		20.6 A
Service Factor (S.F.)		1.15	No-load Current		0.694 A		
NEMA Nom. Eff.		85.5	Power Factor	90	Line-line Res. @ 25°C		7.64 Ω
Rating - Duty		40C	AMB-CONT		Temp. Rise @ Rated Load		78°C
S.F. Amps					Temp. Rise @ S.F. Load		90°C
					Locked-rotor Power Factor		45.7
					Rotor inertia		0.0885 LB-FT2

Load Characteristics 460 V, 60 Hz, 1.5 HP

% of Rated Load	25	50	75	100	125	150	S.F.
Power Factor	55	77	86	92	93	90	93
Efficiency	73.8	82.3	85.2	86.1	85.9	85.5	86
Speed	3564	3536	3507	3476	3444	3406	3457
Line amperes	0.907	1.15	1.48	1.81	2.23	2.75	2.06

ABB Motors and Mechanical Inc.

WINDING # 35WGR929

Typical performance - not guaranteed values.

1.5 HP 3 PH 60 HZ 3500 RPM 460 V 3532M

TORQUES (LB-FT): PO=10.9 PU=5.2 LR=10.2 LRA=20.6





