

ABB BALDOR RELIANCE III

Customer information packet CL3507

.75HP, 1725RPM, 1PH, 60HZ, 56C, 3428LC, TEFC, F

Class - None

Division - Not Applicable

Specifications

Enclosure	TEFC
Frame	56C
Frame Material	Steel
Frequency	60.00 Hz
Haz Area Class and Group	None
Haz Area Division	Not Applicable
Motor Letter Type	Cap Start, Cap Run
Output @ Frequency	.750 HP @ 60 HZ
Phase	1
Synchronous Speed @ Frequency	1800 RPM @ 60 HZ
Voltage @ Frequency	115.0 V @ 60 HZ 208.0 V @ 60 HZ 230.0 V @ 60 HZ
Agency Approvals	C UR US
Ambient Temperature	40 °C
Auxiliary Box	NO AUXILLARY BOX
Auxiliary Box Lead Termination	None
Base Indicator	Rigid
Bearing Grease Type	Polyrex EM (-20F +300F)
Blower	None
Current @ Voltage	4.200 A @ 230.0 V 5.400 A @ 208.0 V 8.400 A @ 115.0 V
Design Code	N
Drip Cover	No Drip Cover
Duty Rating	CONT
Efficiency @ 100% Load	72.0 %
Electrically Isolated Bearing	Not Electrically Isolated
Feedback Device	NO FEEDBACK
Front Face Code	Standard
Front Shaft Indicator	None
Heater Indicator	No Heater

Part Detail

Revision	AF
Type	AC
Mech. spec.	34G451
Base	
Status	PRD/A
Elec. spec.	34WGY094
Layout	34LYG451
Eff. date	02-25-2025
CD Diagram	CD0055
Poles	04
Leads	6#18
Proprietary	False
Created date	01-01-0001

High Voltage Full Load Amps	4.2 a
Insulation Class	F
Inverter Code	Not Inverter
KVA Code	J
Lifting Lugs	No Lifting Lugs
Locked Bearing Indicator	Locked Bearing
Motor Lead Exit	Ko Box
Motor Lead Quantity/Wire Size	6 @ 18 AWG
Motor Lead Termination	Flying Leads
Motor Standards	NEMA
Motor Type	3428LC
Mounting Arrangement	F1
Number of Poles	4
Overall Length	12.47 IN
Power Factor	78
Product Family	General Purpose
Pulley End Bearing Type	Ball
Pulley Face Code	C-Face
Pulley Shaft Indicator	Standard
Rodent Screen	None
Service Factor	1.15
Shaft Diameter	0.625 IN
Shaft Extension Location	Pulley End
Shaft Ground Indicator	No Shaft Grounding
Shaft Rotation	Reversible
Shaft Slinger Indicator	No Slinger
Speed	1725 rpm
Speed Code	Single Speed
Starting Method	Direct on line
Thermal Device - Bearing	None
Thermal Device - Winding	None
Vibration Sensor Indicator	No Vibration Sensor
Winding Thermal 1	None
Winding Thermal 2	None

Nameplate

NP1256L											
CAT.NO.	CL3507										
SPEC.	34G451Y094										
HP	.75										
VOLTS	115/208-230										
AMP	8.4/5.4-4.2										
RPM	1725										
FRAME	56C		HZ	60				PH	1		
SER.F.	1.15	CODE	J	DES	N			CLASS	F		
NEMA-NOM-EFF	72	PF	78								
RATING	40C AMB-CONT										
CC											
DE	6203		ODE	6203							
ENCL	TEFC	SN									

AC Induction Motor Performance Data

Record # 50661

Typical performance - not guaranteed values

Winding: 34WGY094-R011			Type: 3428LC		Enclosure: TEFC	
Nameplate Data			230 V, 60 Hz: High Voltage Connection			
Rated Output (HP)		.75	Full Load Torque		2.25 LB-FT	
Volts		115/208-230	Start Configuration		direct on line	
Full Load Amps		8.4/5.4-4.2	Breakdown Torque		5.7 LB-FT	
R.P.M.		1725	Pull-up Torque		5 LB-FT	
Hz		60	Phase		1	
NEMA Design Code		N	KVA Code		J	
Service Factor (S.F.)		1.15	No-load Current		2.8 A	
NEMA Nom. Eff.		72	Power Factor		78	
Rating - Duty		40C	AMB-CONT		Temp. Rise @ Rated Load	
S.F. Amps			Temp. Rise @ S.F. Load		82°C	

Load Characteristics 230 V, 60 Hz, 0.75 HP

% of Rated Load	25	50	75	100	125	150	S.F.
Power Factor	43	57	70	78	82	86	80
Efficiency	50.2	66.1	71.1	72.3	72	68.6	72.1
Speed	1780	1766	1749	1729	1707	1675	1716
Line amperes	2.9	3.2	3.7	4.3	5.1	6.2	4.78


ABB Motors and Mechanical Inc.

WINDING # 34WGY094

Typical performance - not guaranteed values.

0.75 HP 1 PH 60 HZ 1725 RPM 230 V 3428LC

TORQUES (LB-FT) : PO=5.7 PU=5 LR=6.9 LRA=24.7





CD0055

