

ABB BALDOR RELIANCE III

Customer information packet

CSPM3611T

3HP, 1765RPM, 3PH, 60HZ, 182TC, 3642M, TEFC, F1

Class - None

Division - Not Applicable

Specifications

Enclosure	TEFC
Frame	182TC
Frame Material	Steel
Frequency	60.00 Hz
Haz Area Class and Group	None
Haz Area Division	Not Applicable
Motor Letter Type	Three Phase
Output @ Frequency	3.000 HP @ 60 HZ
Phase	3
Synchronous Speed @ Frequency	1800 RPM @ 60 HZ
Voltage @ Frequency	230.0 V @ 60 HZ 460.0 V @ 60 HZ
Agency Approvals	WEEE NEMA PREMIUM 4
Ambient Temperature	40 °C
Auxiliary Box	NO AUXILLARY BOX
Auxiliary Box Lead Termination	None
Base Indicator	Rigid
Bearing Grease Type	Polyrex EM (-20F +300F)
Blower	None
Current @ Voltage	4.200 A @ 460.0 V 8.400 A @ 230.0 V
Design Code	A
Drip Cover	No Drip Cover
Duty Rating	CONT
Efficiency @ 100% Load	91.0 %
Electrically Isolated Bearing	Not Electrically Isolated
Feedback Device	NO FEEDBACK
Front Shaft Indicator	None
Heater Indicator	No Heater
High Voltage Full Load Amps	4.2 a
Insulation Class	F

Part Detail

Revision	B
Type	AC
Mech. spec.	36P427
Base	
Status	PRD/A
Elec. spec.	36WGZ631
Layout	36LYP427
Eff. date	11-19-2025
CD Diagram	CD0005
Poles	04
Leads	9#16
Proprietary	False
Created date	01-02-2024

Inverter Code	Inverter Duty
KVA Code	L
Lifting Lugs	Standard Lifting Lugs
Locked Bearing Indicator	Locked Bearing
Max Speed	2700 rpm
Motor Lead Quantity/Wire Size	9 @ 16 AWG
Motor Lead Termination	Flying Leads
Motor Standards	NEMA
Motor Type	3642M
Mounting Arrangement	F1
Number of Poles	4
Overall Length	18.04 IN
Power Factor	74
Product Family	General Purpose
Pulley End Bearing Type	Ball
Pulley Face Code	C-Face
Pulley Shaft Indicator	Standard
Rodent Screen	None
RoHS Status	ROHS COMPLIANT
Service Factor	1.15
Shaft Diameter	1.125 IN
Shaft Ground Indicator	No Shaft Grounding
Shaft Rotation	Reversible
Shaft Slinger Indicator	No Slinger
Speed	1765 rpm
Speed Code	Single Speed
Starting Method	Direct on line
Thermal Device - Bearing	None
Thermal Device - Winding	None
Vibration Sensor Indicator	No Vibration Sensor
Winding Thermal 1	None
Winding Thermal 2	None

Nameplate

NP4423A01A01L														
CAT #	CSPM3611T					WGT	93	LBS						
SPEC	36P427Z631					ENCL	TEFC							
SER #						CC	010A	IP	54					
HP	3					MAG CUR	4.8/2.4							
VOLTS	230/460									NEMA NOM. EFF	91			
AMPS	8.4/4.2							PF	74					
RATING	40C AMB-CONT													
RPM	1765									MAX RPM	2700			
FRAME	182TC	HZ		60		CODE		L	CLASS		F			
SER.F.	1.15	SF AMP		9.4/4.7				PH		3	DES		A	
DE	6206			ODE		6205								
LUBRICATION	POLYREX EM													
ID LOGO	INVERTER TYPE				VPWM		CHP		60	TO		90	1.5:1	
ID LOGO	WK2	0.39	CT		6	TO		60	10:1					
ID LOGO	SL HZ	1.2	VT		3	TO		60	20:1					
								QR						
YR														

AC Induction Motor Performance Data

Record # 96363

Typical performance - not guaranteed values

Winding: 36WGZ631-R001			Type: 3642M		Enclosure: TEFC		
Nameplate Data			460 V, 60 Hz: High Voltage Connection				
Rated Output (HP)		3	Full Load Torque		8.92 LB-FT		
Volts		230/460	Start Configuration		direct on line		
Full Load Amps		8.4/4.2	Breakdown Torque		37.4 LB-FT		
R.P.M.		1765	Pull-up Torque		21.2 LB-FT		
Hz		60	Phase		3	Locked-rotor Torque	25.1 LB-FT
NEMA Design Code		A	KVA Code		L	Starting Current	34.6 A
Service Factor (S.F.)		1.15				No-load Current	2.42 A
NEMA Nom. Eff.		91	Power Factor		74	Line-line Res. @ 25°C	2.59 Ω
Rating - Duty		40C	AMB-CONT			Temp. Rise @ Rated Load	39°C
S.F. Amps		9.4/4.7				Temp. Rise @ S.F. Load	45°C
						Locked-rotor Power Factor	39
						Rotor inertia	0.391 lb-ft²

Load Characteristics 460 V, 60 Hz, 3 HP

% of Rated Load	25	50	75	100	125	150	S.F.
Power Factor	32	52	65	74	77	80	76
Efficiency	83	89	91	91	90	89	90.4
Speed	1794	1785	1777	1767	1756	1745	1760
Line amperes	2.58	3.01	3.55	4.18	5.01	5.87	4.68

ABB Motors and Mechanical Inc.

WINDING # 36WGZ631

Typical performance - not guaranteed values.

3 HP 3 PH 60 HZ 1765 RPM 460 V 3642M

TORQUES (LB-FT): PO=37.4 PU=21.2 LR=25.1 LRA=34.6





