

ABB BALDOR RELIANCE III

Customer information packet

CSPM3611T-G

3HP, 1765RPM, 3PH, 60HZ, 182TC, 3642M, TEFC, F1

Class - None

Division - Not Applicable

Specifications

Enclosure	TEFC
Frame	182TC
Frame Material	Steel
Frequency	60.00 Hz
Haz Area Class and Group	None
Haz Area Division	Not Applicable
Motor Letter Type	Three Phase
Output @ Frequency	3.000 HP @ 60 HZ
Phase	3
Synchronous Speed @ Frequency	1800 RPM @ 60 HZ
Voltage @ Frequency	230.0 V @ 60 HZ 460.0 V @ 60 HZ
Agency Approvals	WEEE NEMA PREMIUM
Ambient Temperature	40 °C
Auxiliary Box	NO AUXILLARY BOX
Auxiliary Box Lead Termination	None
Base Indicator	Rigid
Bearing Grease Type	Polyrex EM (-20F +300F)
Blower	None
Current @ Voltage	4.200 A @ 460.0 V 8.400 A @ 230.0 V
Design Code	A
Drip Cover	No Drip Cover
Duty Rating	CONT
Efficiency @ 100% Load	91.0 %
Electrically Isolated Bearing	Not Electrically Isolated
Feedback Device	NO FEEDBACK
Front Shaft Indicator	None
Heater Indicator	No Heater
High Voltage Full Load Amps	4.2 a
Insulation Class	H

Part Detail

Revision	A
Type	AC
Mech. spec.	36P495
Base	
Status	PRD/A
Elec. spec.	36WGZ631
Layout	36LYP495
Eff. date	11-19-2025
CD Diagram	CD0005
Poles	04
Leads	9#16
Proprietary	False
Created date	05-23-2025

Inverter Code	Inverter Duty
KVA Code	L
Lifting Lugs	Standard Lifting Lugs
Locked Bearing Indicator	Locked Bearing
Max Speed	2700 rpm
Motor Lead Quantity/Wire Size	9 @ 16 AWG
Motor Lead Termination	Flying Leads
Motor Standards	NEMA
Motor Type	3642M
Mounting Arrangement	F1
Number of Poles	4
Overall Length	18.04 IN
Power Factor	74
Product Family	General Purpose
Pulley End Bearing Type	Ball
Pulley Face Code	C-Face
Pulley Shaft Indicator	Standard
Rodent Screen	None
RoHS Status	ROHS COMPLIANT
Service Factor	1.25
Shaft Diameter	1.125 IN
Shaft Ground Indicator	Shaft Grounding
Shaft Rotation	Reversible
Shaft Slinger Indicator	No Slinger
Speed	1765 rpm
Speed Code	Single Speed
Starting Method	Direct on line
Thermal Device - Bearing	None
Thermal Device - Winding	None
Vibration Sensor Indicator	No Vibration Sensor
Winding Thermal 1	None
Winding Thermal 2	None

Nameplate

NP4423A01A01L															
CAT #	CSPM3611T-G					WGT	93		LBS						
SPEC	36P495Z631G1					ENCL	TEFC								
SER #						CC	010A		IP	54					
HP	3		MAG CUR			5.6/2.8									
VOLTS	230/460					NEMA NOM. EFF							91		
AMPS	8.4/4.2						PF	74							
RATING	40C AMB-CONT														
RPM	1765					MAX RPM			2700						
FRAME	182TC	HZ		60		CODE		L	CLASS			H			
SER.F.	1.25	SF AMP		10.2/5.1				PH	3	DES		A			
DE	6206			ODE		6205									
LUBRICATION	POLYREX EM														
ID LOGO	INVERTER TYPE				VPWM		CHP	60	TO		90	1.5:1			
ID LOGO	WK2	0.39		CT	6	TO	60	10:1							
ID LOGO	SL HZ	1.2		VT	3	TO	60	20:1							
							QR								
YR															

AC Induction Motor Performance Data

Record # 112292

Preliminary Data Sheet

Winding: 36WGZ631-R004			Type: 3642M		Enclosure: TEFC		
Nameplate Data			460 V, 60 Hz: High Voltage Connection				
Rated Output (HP)		3	Full Load Torque		8.92 LB-FT		
Volts		230/460	Start Configuration		direct on line		
Full Load Amps		8.4/4.2	Breakdown Torque		45.1 LB-FT		
R.P.M.		1765	Pull-up Torque		23 LB-FT		
Hz	60 Phase	3	Locked-rotor Torque		28.5 LB-FT		
NEMA Design Code		A	KVA Code		L	Starting Current	41.8 A
Service Factor (S.F.)		1.25	No-load Current		2.76 A		
NEMA Nom. Eff.		91	Power Factor		74	Line-line Res. @ 25°C	2.78 Ω
Rating - Duty		40C	AMB-CONT		Temp. Rise @ Rated Load		39°C
S.F. Amps		10.2/5.1	Temp. Rise @ S.F. Load		49°C		
			Locked-rotor Power Factor		40		
			Rotor inertia		0.391 lb-ft²		

Load Characteristics 460 V, 60 Hz, 3 HP

% of Rated Load	25	50	75	100	125	150	S.F.
Power Factor	30	49	62	71	76	80	76
Efficiency	81.5	88.6	90.6	91.2	91.1	90.6	91.1
Speed	1792	1786	1779	1772	1765	1757	1765
Line amperes	2.91	3.26	3.75	4.37	5.07	5.83	5.07

ABB Motors and Mechanical Inc.

WINDING # 36WGZ631

Typical performance - not guaranteed values.

3 HP 3 PH 60 HZ 1765 RPM 460 V 3642M

TORQUES (LB-FT): PO=45.1 PU=23 LR=28.5 LRA=41.8





