

ABB BALDOR RELIANCE III

Customer information packet

CSPM4115T

50HP, 1775RPM, 3PH, 60HZ, 326TC, 1288M, TEFC, F

Class - CLI GP A,B,C,D CLII GP F,G

Division - Division II

Specifications

Enclosure	TEFC
Frame	326TC
Frame Material	Cast Iron
Frequency	60.00 Hz
Haz Area Class and Group	CLI GP A,B,C,D CLII GP F,G
Haz Area Division	Division II
Motor Letter Type	Three Phase
Output @ Frequency	50.000 HP @ 60 HZ
Phase	3
Synchronous Speed @ Frequency	1800 RPM @ 60 HZ
Voltage @ Frequency	460.0 V @ 60 HZ 230.0 V @ 60 HZ
Agency Approvals	CSA CURUSEEV NEMA_PREMIUM WEEE
Ambient Temperature	40 °C
Auxiliary Box	NO AUXILLARY BOX
Auxiliary Box Lead Termination	None
Base Indicator	Rigid
Bearing Grease Type	Polyrex EM (-20F +300F)
Blower	None
Current @ Voltage	120.000 A @ 230.0 V 60.000 A @ 460.0 V
Design Code	A
Drip Cover	No Drip Cover
Duty Rating	CONT
Efficiency @ 100% Load	95.4 %
Electrically Isolated Bearing	Not Electrically Isolated
Feedback Device	NO FEEDBACK
Front Shaft Indicator	None
Haz Area Temp Code	T3C

Part Detail

Revision	C
Type	AC
Mech. spec.	12T118
Base	
Status	PRD/A
Elec. spec.	12WGZ340
Layout	12LYT118
Eff. date	04-17-2026
CD Diagram	CD0180
Poles	04
Leads	9#6
Proprietary	False
Created date	09-20-2024

Heater Indicator	No Heater
High Voltage Full Load Amps	60.0 a
Insulation Class	F
Inverter Code	Inverter Duty
KVA Code	J
Lifting Lugs	Standard Lifting Lugs
Locked Bearing Indicator	Locked Bearing
Max Speed	2700 rpm
Motor Lead Quantity/Wire Size	9 @ 6 AWG
Motor Lead Termination	Flying Leads
Motor Standards	NEMA
Motor Type	1288M
Mounting Arrangement	F1
Number of Poles	4
Overall Length	30.71 IN
Power Factor	84
Product Family	Chemical Processing (Not DC)
Pulley End Bearing Type	Ball
Pulley Face Code	C-Face
Pulley Shaft Indicator	Standard
Rodent Screen	None
RoHS Status	ROHS COMPLIANT
Service Factor	1.15
Shaft Diameter	2.125 IN
Shaft Ground Indicator	No Shaft Grounding
Shaft Rotation	Reversible
Shaft Slinger Indicator	No Slinger
Speed	1775 rpm
Speed Code	Single Speed
Starting Method	Direct on line
Thermal Device - Bearing	None
Thermal Device - Winding	None
Vibration Sensor Indicator	No Vibration Sensor
Winding Thermal 1	None

Winding Thermal 2

None

Nameplate

NP4439B05C23L

[illegible]

YR

AC Induction Motor Performance Data

Record # 107565

Typical performance - not guaranteed values

Winding: 12WGZ340-R001			Type: 1288M		Enclosure: TEFC		
Nameplate Data				460 V, 60 Hz: High Voltage Connection			
Rated Output (HP)		50		Full Load Torque		147.7 LB-FT	
Volts		230/460		Start Configuration		direct on line	
Full Load Amps		120/60		Breakdown Torque		506 LB-FT	
R.P.M.		1775		Pull-up Torque		272 LB-FT	
Hz	60	Phase	3	Locked-rotor Torque		269 LB-FT	
NEMA Design Code		A	KVA Code	J	Starting Current		436 A
Service Factor (S.F.)		1.15		No-load Current		21.8 A	
NEMA Nom. Eff.		95.4	Power Factor	84	Line-line Res. @ 25°C		0.094907 Ω
Rating - Duty		40C AMB-CONT		Temp. Rise @ Rated Load		57°C	
S.F. Amps				Temp. Rise @ S.F. Load		70°C	
				Locked-rotor Power Factor		25.3	

Load Characteristics 460 V, 60 Hz, 50 HP

% of Rated Load	25	50	75	100	125	150	S.F.
Power Factor	49	71	81	85	86	87	86
Efficiency	93.3	95.5	95.9	95.7	95.2	94.6	95.4
Speed	1794.8	1790	1784.7	1779.7	1772.9	1766.3	1776
Line amperes	25.7	34.4	45.4	57.7	71.2	85.5	65.8


ABB Motors and Mechanical Inc.


WINDING # 12WGZ340

Typical performance - not guaranteed values.


50 HP 3 PH 60 HZ 1775 RPM 460 V 1288M

TORQUES (LB-FT): PO=506 PU=272 LR=269 LRA=436







CD0180



LOW VOLTAGE
(2D)



HIGH VOLTAGE
(1D)



NOTES:

1. INTERCHANGE ANY TWO LINE LEADS TO REVERSE ROTATION.
2. OPTIONAL THERMOSTATS ARE PROVIDED WHEN SPECIFIED.
3. ACTUAL NUMBER OF INTERNAL PARALLEL CIRCUITS MAY BE A MULTIPLE OF THOSE SHOWN ABOVE.
4. LEAD COLORS ARE OPTIONAL. LEADS MUST ALWAYS BE NUMBERED AS SHOWN.

REV. DESC: ADD CLASS CONN00000007

REV. LTR: D

VERSION: 01

TDR: 000001099922

FILE: \AAA\00005\148

REVISED: 10: 25: 29 02/19/2019

BY: ENBRIRO

MTL: -



BALDOR - RELIANCE®

3PH, DV, 9 LEADS, DELTA CONNECTION

SH 1 of 1

CD0180