

ABB BALDOR RELIANCE III

Customer information packet

CZDNM3614T

2HP, 1175RPM, 3PH, 60HZ, 184TC, 3644M, TENV, F1

Class - None

Division - Not Applicable

Specifications

Enclosure	TENV
Frame	184TC
Frame Material	Steel
Frequency	60.00 Hz
Haz Area Class and Group	None
Haz Area Division	Not Applicable
Motor Letter Type	Three Phase
Output @ Frequency	2.000 HP @ 60 HZ
Phase	3
Synchronous Speed @ Frequency	1200 RPM @ 60 HZ
Voltage @ Frequency	230.0 V @ 60 HZ 460.0 V @ 60 HZ
Agency Approvals	CSA EEV NEMA_PREMIUM UR
Ambient Temperature	40 °C
Auxiliary Box	NO AUXILLARY BOX
Auxiliary Box Lead Termination	None
Base Indicator	Rigid
Bearing Grease Type	Polyrex EM (-20F +300F)
Blower	None
Current @ Voltage	3.500 A @ 460.0 V 7.000 A @ 230.0 V
Design Code	A
Drip Cover	No Drip Cover
Duty Rating	CONT
Efficiency @ 100% Load	88.5 %
Electrically Isolated Bearing	Not Electrically Isolated
Feedback Device	ENCODER
Front Shaft Indicator	None
Heater Indicator	No Heater
High Voltage Full Load Amps	3.5 a

Part Detail

Revision	B
Type	AC
Mech. spec.	36T621
Base	
Status	PRD/A
Elec. spec.	36WGS917
Layout	36LYT621
Eff. date	08-05-2026
CD Diagram	CD0005
Poles	06
Leads	9#16
Proprietary	False
Created date	04-22-2025

Insulation Class	H
Inverter Code	Inverter Duty
KVA Code	M
Lifting Lugs	No Lifting Lugs
Locked Bearing Indicator	Locked Bearing
Max Speed	1800 rpm
Motor Lead Quantity/Wire Size	9 @ 16 AWG
Motor Lead Termination	Flying Leads
Motor Standards	NEMA
Motor Type	3644M
Mounting Arrangement	F1
Number of Poles	6
Overall Length	19.28 IN
Power Factor	60
Product Family	General Purpose
Pulley End Bearing Type	Sealed Bearing
Pulley Face Code	C-Face
Pulley Shaft Indicator	Standard
Rodent Screen	None
Service Factor	1.00
Shaft Diameter	1.103 IN
Shaft Ground Indicator	Shaft Grounding
Shaft Rotation	Reversible
Shaft Slinger Indicator	No Slinger
Speed	1175 rpm
Speed Code	Single Speed
Starting Method	Direct on line
Thermal Device - Bearing	None
Thermal Device - Winding	Normally Closed Thermostat
Vibration Sensor Indicator	No Vibration Sensor
Winding Thermal 1	None
Winding Thermal 2	None

Nameplate

NP3943L									
CAT.NO.	CZDNM3614T								
SPEC.	36T621S917Z1								
FRAME	184TC			H.P.	2 TE				
VOLTS	230/460 ENCL TENV								
MAG. CUR.	4.8/2.4				F.L. AMPS			7/3.5	
R.P.M.	1175		R.P.M. MAX			1800			
HZ.	60		PH.	3	CLASS		H		
SER.F.	1.00			SL HZ		1.25			
NEMA NOM. EFF.	88.5		WK2		0.413				
RATING	40C AMB-CONT								
DE	6206	ODE		6205					
CC	010A	SN							
	1000:1 CT 1.5:1 CHP								
	1.15 SF ON SINEWAVE								

AC Induction Motor Performance Data

Record # 108118

Typical performance - not guaranteed values

Winding: 36WGS917-R038				Type: 3644M		Enclosure: TENV		
Nameplate Data				460 V, 60 Hz: High Voltage Connection				
Rated Output (HP)		2		Full Load Torque		8.97 LB-FT		
Volts		230/460		Start Configuration		direct on line		
Full Load Amps		7/3.5		Breakdown Torque		41.8 LB-FT		
R.P.M.		1175		Pull-up Torque		21.4 LB-FT		
Hz	60	Phase	3	Locked-rotor Torque		26.1 LB-FT		
NEMA Design Code		A	KVA Code	M		Starting Current		27.7 A
Service Factor (S.F.)		1.15		No-load Current		2.43 A		
NEMA Nom. Eff.		88.5	Power Factor	60		Line-line Res. @ 25°C		4.02 Ω
Rating - Duty		40C AMB-CONT		Temp. Rise @ Rated Load		35°C		
S.F. Amps				Temp. Rise @ S.F. Load		41°C		
				Locked-rotor Power Factor		28.7		
				Rotor inertia		0.413 LB-FT2		

Load Characteristics 460 V, 60 Hz, 2 HP

% of Rated Load	25	50	75	100	125	150	S.F.
Power Factor	24	40	52	60	66	70	64
Efficiency	76.9	85.6	88.3	89	89	88.4	89
Speed	1197	1191	1186	1179	1173	1165	1175
Line amperes	2.52	2.75	3.08	3.5	3.98	4.52	3.79

ABB Motors and Mechanical Inc.

WINDING # 36WGS917

Typical performance - not guaranteed values.

2 HP 3 PH 60 HZ 1175 RPM 460 V 3644M

TORQUES (LB-FT) : PO=41.8 PU=21.4 LR=26.1 LRA=27.7





