

ABB BALDOR RELIANCE III

Customer information packet

D2301

.33HP, 1750RPM, DC, 56, 3513D, TEFC, F1

Class - None

Division -

Specifications

Armature Voltage	230 V
Base Speed	1750 rpm
Enclosure	TEFC
Frame	56
Frame Material	Steel
Haz Area Class and Group	None
Output Power	0.330 HP
Agency Approvals	CSA UR
Ambient Temperature	40 °C
Armature Current	1.7 a
Armature Inertia	5.073 lb-ft2
Base Indicator	Rigid
Bearing Grease Type	Polyrex EM (-20F +300F)
Drip Cover	No Drip Cover
Duty Rating	CONT
Feedback Device	NO FEEDBACK
Field Winding Type	COMPOUND
Heater Indicator	No Heater
Lifting Lugs	No Lifting Lugs
Motor Lead Exit	Ko Box
Motor Lead Quantity/Wire Size	2 @ 18 AWG 2 @ 14 AWG
Motor Lead Termination	Flying Leads
Motor Standards	NEMA
Mounting Arrangement	F1
Overall Length	13.06 IN
Product Family	General Purpose
Pulley End Bearing Type	Sealed Bearing
RoHS Status	ROHS COMPLIANT
Service Factor	1.00
Shaft Diameter	0.625 IN

Part Detail

Revision	Y
Type	DC
Mech. spec.	35P316
Base	
Status	PRD/A
Elec. spec.	35WGZ393
Layout	35LYP316
Eff. date	10-28-2024
CD Diagram	CD0862B01
Poles	00
Leads	
Proprietary	False
Created date	01-01-0001

Shaft Extension Location	Pulley End
Shaft Ground Indicator	No Shaft Grounding
Shaft Rotation	Reversible
Shaft Slinger Indicator	No Slinger

Nameplate

NP0111L			
CAT.NO.	D2301		
SPEC.	35P316Z393		
HP	.33	ENCL	TEFC
RPM	1750		
FRAME	56	TYPE	3513D
ARM V	230	ARM A	1.7
FLD V		FLD A	
INSUL	F	AMB.	40
DUTY	CONT	SUPPLY	A
BRG/DE	6205	BRG/ODE	6203
BRUSHES	2/BP5000T15		
	BLANK		
SER.			
BLANK			
APRV-CSA		APRV-UL	

DC Motor Performance Data

Record # 1416

Typical performance - not guaranteed values

Winding: 35WGZ393-R001		Type: 3413D	Enclosure: TEFC
Nameplate Data		General Characteristics	
Rated Output (HP)	0.33	Armature Resistance @ 25°C	8.194 Ω
R.P.M.	1750	Commutating Winding Resistance @ 25°C	6.818 Ω
Armature Volts	230	Series Winding Resistance @ 25°C	2.516 Ω
Armature Amps	1.7	Shunt Winding Resistance @ 25°C	705.6 Ω
Field Volts		Armature Inductance	75.832 mH
Field Amps			
Rating - Duty	40C AMB-CONT		
Power Supply Code	A		

Load Characteristics at 230 Armature Volts

Load Point	1	2	3	4	5	6	7
Armature Amps	0.5	1.01	1.35	1.66	2.03	2.38	2.73
R.P.M.	2249	2146	2077	2032	1964	1881	1795
Torque (LB-FT)	0	0.25	0.5	0.75	1	1.25	1.5

ABB Motors and Mechanical Inc.

WINDING # 35WGZ393

Typical performance - not guaranteed values.

0.33 HP DC 1750 RPM 230 V 3413D

ENCL: TEFC DUTY: CONT CL: F





