

ABB BALDOR RELIANCE III

Customer information packet

DRX32524T-5

50HP, 3560RPM, 3PH, 60HZ, 326TS, XPFC, F1

Class - CLI GP C,D

Division - Division I

Specifications

Enclosure	XPFC
Frame	326TS
Frame Material	Iron
Frequency	60.00 Hz
Haz Area Class and Group	CLI GP C,D
Haz Area Division	Division I
Motor Letter Type	Three Phase
Output @ Frequency	50.000 HP @ 60 HZ
Phase	3
Synchronous Speed @ Frequency	3600 RPM @ 60 HZ
Voltage @ Frequency	575.0 V @ 60 HZ
Agency Approvals	CSA EEV UL
Ambient Temperature	40 °C
Auxiliary Box	NO AUXILLARY BOX
Auxiliary Box Lead Termination	None
Base Indicator	Rigid
Bearing Grease Type	Polyrex EM (-20F +300F)
Blower	None
Constant Torque Speed Range	6
Current @ Voltage	45.000 A @ 575.0 V
Design Code	A
Drip Cover	No Drip Cover
Duty Rating	CONT
Efficiency @ 100% Load	93.0 %
Electrically Isolated Bearing	Not Electrically Isolated
Feedback Device	NO FEEDBACK
Haz Area Temp Code	T3C
Heater Indicator	No Heater
High Voltage Full Load Amps	45.0 a
Insulation Class	F
Inverter Code	Inverter Duty

Part Detail

Revision	E
Type	AC
Mech. spec.	
Base	
Status	PRD/A
Elec. spec.	12WGY735
Layout	12LYT060
Eff. date	12-10-2024
CD Diagram	CD0006
Poles	02
Leads	3#8
Proprietary	False
Created date	07-16-2019

IP Rating	NONE
KVA Code	K
Lifting Lugs	Standard Lifting Lugs
Locked Bearing Indicator	Locked Bearing
Max Speed	5400 rpm
Motor Lead Termination	Flying Leads
Motor Standards	NEMA
Motor Type	1264M
Mounting Arrangement	F1
Number of Poles	2
Overall Length	30.50 IN
Power Factor	89
Product Family	Hazardous Location Motor
Pulley Face Code	Standard
Rodent Screen	None
RoHS Status	ROHS NON-COMPLIANT
Service Factor	1.00
Shaft Diameter	1.875 IN
Shaft Ground Indicator	No Shaft Grounding
Shaft Rotation	Reversible
Speed	3560 rpm
Speed Code	Single Speed
Starting Method	Direct on line
Thermal Device - Bearing	None
Thermal Device - Winding	Normally Closed Thermostat
Vibration Sensor Indicator	No Vibration Sensor
Winding Thermal 1	None
Winding Thermal 2	None

Nameplate

NP1401XPSLEV											
NO.						CC	010A				
S/N						TEMP CODE			T3C		
SPEC.	12-0000-0855					INV.TYPE		PWM			
CAT.NO.	DRX32524T-5					C HP FR	60	C HP TO	90		
HP	50					CT HZ FROM		6	CT HZ TO		60
VOLTS	575					VT HZ FROM		6	VT HZ TO		60
AMPS	45				MAG CUR		14.1				
RPM	3560				MX RPM		5400				
HZ	60	PH	3	CL	F	NOM.EFF.		93			
SER.F.	1.00	DES		A	SL HZ	0.67	WK2	5.01			
FRAME	326TS		RATING		40C AMB-CONT						
	55C AMB @ 1.0 SF, 60C RISE										
	1.15SF ON SINEWAVE					NEMA MG-1 PT.5,IP55					

AC Induction Motor Performance Data

Record # 77589

Typical performance - not guaranteed values

Winding: 12WGY735-R002			Type: 1264M		Enclosure: XPFC		
Nameplate Data			575 V, 60 Hz: Single Voltage Motor				
Rated Output (HP)		50	Full Load Torque		74.1 LB-FT		
Volts		575	Start Configuration		direct on line		
Full Load Amps		45	Breakdown Torque		287 LB-FT		
R.P.M.		3560	Pull-up Torque		107 LB-FT		
Hz	60	Phase	3	Locked-rotor Torque		137 LB-FT	
NEMA Design Code		A	KVA Code	K	Starting Current		404 A
Service Factor (S.F.)			1	No-load Current		14.1 A	
NEMA Nom. Eff.		93	Power Factor	89	Line-line Res. @ 25°C		0.132 Ω
Rating - Duty			40C	AMB-CONT	Temp. Rise @ Rated Load		53°C
S.F. Amps					Temp. Rise @ S.F. Load		64°C
					Locked-rotor Power Factor		21.5
					Rotor inertia		4.98 LB-FT2

Load Characteristics 575 V, 60 Hz, 50 HP

% of Rated Load	25	50	75	100	125	150
Power Factor	58	79	86	89	90	91
Efficiency	91.4	94.2	94.6	94.5	94	93.4
Speed	3590	3581	3570	3560	3549	3539
Line amperes	17.9	25.4	34.8	44.5	55.2	65.9


ABB Motors and Mechanical Inc.


WINDING # 12WGY735

Typical performance - not guaranteed values.




50 HP 3 PH 60 HZ 3560 RPM 575 V 1264M

TORQUES (LB-FT): PO=287 PU=107 LR=137 LRA=404





CD0006


NOTES:

1. THREE LEAD MOTOR MAY BE EITHER WYE CONNECTED OR DELTA CONNECTED.
2. INTERCHANGE ANY TWO LINE LEADS TO REVERSE ROTATION.
3. OPTIONAL THERMOSTATS ARE PROVIDED WHEN SPECIFIED.
4. ACTUAL NUMBER OF INTERNAL PARALLEL CIRCUITS MAY VARY.
5. LEAD COLORS ARE OPTIONAL. LEADS MUST BE NUMBERED AS SHOWN.

CD0006

REV. DESC: ADD CLASS CONN00000007

REV. LTR: E

VERSION: 01

TDR: 000001099922

FILE: \AAA\00005\141

REVISED: 10:24:49 02/19/2019

BY: ENBRIRO

MTL: -


BALDOR - RELIANCE®

3PH, SV, 3 LEADS, WYE OR DELTA CONNECTED

SH 1 of 1