

ABB BALDOR RELIANCE III

Customer information packet

DRX36624T

60HP, 3560RPM, 3PH, 60HZ, 364TS, TEFC, F1

Class - CLI GP C,D

Division - Division I

Specifications

Enclosure	TEFC
Frame	364TS
Frame Material	Iron
Frequency	60.00 Hz
Haz Area Class and Group	CLI GP C,D
Haz Area Division	Division I
Motor Letter Type	Three Phase
Output @ Frequency	60.000 HP @ 60 HZ
Phase	3
Synchronous Speed @ Frequency	3600 RPM @ 60 HZ
Voltage @ Frequency	230.0 V @ 60 HZ 460.0 V @ 60 HZ
Agency Approvals	CCSAUSEEV CSA UL
Ambient Temperature	40 °C
Auxiliary Box	NO AUXILLARY BOX
Base Indicator	Rigid
Bearing Grease Type	Polyrex EM (-20F +300F)
Constant Torque Speed Range	6-60
Current @ Voltage	130.000 A @ 230.0 V 65.100 A @ 460.0 V
Design Code	B
Drip Cover	No Drip Cover
Duty Rating	CONT
Efficiency @ 100% Load	93.6 %
Feedback Device	NO FEEDBACK
Haz Area Temp Code	T3C
Heater Indicator	No Heater
High Voltage Full Load Amps	65.1 a
Insulation Class	F
Inverter Code	Inverter Ready

Part Detail

Revision	-
Type	AC
Mech. spec.	
Base	
Status	PRD/A
Elec. spec.	A36WG1558
Layout	611742-779
Eff. date	05-29-2019
CD Diagram	416820-002
Poles	02
Leads	3#4,6#6
Proprietary	False
Created date	04-30-2019

IP Rating	NONE
KVA Code	G
Lifting Lugs	Standard Lifting Lugs
Max Speed	4200 rpm
Motor Lead Quantity/Wire Size	3 @ 4 AWG
Motor Standards	NEMA
Motor Type	A36056M
Mounting Arrangement	F1
Number of Poles	2
Overall Length	31.35 IN
Power Factor	91
Product Family	General Industrial
Pulley End Bearing Type	Ball
Pulley Face Code	Standard
Service Factor	1.00
Shaft Diameter	1.875 IN
Shaft Ground Indicator	No Shaft Grounding
Shaft Rotation	Reversible
Shaft Slinger Indicator	Shaft Slinger
Speed	3560 rpm
Speed Code	Single Speed
Starting Method	Direct on line
Thermal Device - Bearing	None
Thermal Device - Winding	Normally Closed Thermostat

Nameplate

NP2496L	
MOBIL POLYREX EM	

000692000FX



000613006PC		
CLASS I GROUP	C D X	NO.
CLASS II GROUP	X X X	
OPERATING TEMP CODE	T3C	

NP3140L

SPEC NO.	A36-7814-1558			CAT.NO.	DRX36624T					FRAME	364TS
HP	60	VOLTS	230/460		PHASE	3	DESIGN	B	TYPE	P	
RPM	3560	AMPS	130/65.1		HZ	60	AMB	40	SF	1.00	
DRIVE END BEARING	65BC03J30X		DUTY	CONT	INSUL.CLASS			F			
OPP D.E. BEARING	65BC03J30X		ENCL	TEFC	CODE	G					
SF	1.15	WK2	MAG CUR		28.8/14.4		RPM MAX	4200			
CT HZ	6-60	VT HZ	0-60	CHP HZ	60-70		NEMA-NOM-EFF		93.6		
	SUIT FOR 55C AMB AT 1.00 SF					IP55					
SER.NO.				MOTOR WEIGHT		1023					

REL. S.O.	FRAME	HP	TYPE	PHASE/ HERTZ	RPM	VOLTS
	364TS	60	P	3/60	3560	230/460
AMPS	DUTY	AMB °C/ INSUL.	S.F.	NEMA DESIGN	CODE LETTER	ENCL.
130/65.1	CONT	40/F	1.00	B	G	TEFC
E/S	ROTOR	TEST S.O.	TEST DATE	STATOR RES. @25 °C OHMS (BETWEEN LINES)		
491281	418141005XE	---	---	.0254/.101		
PERFORMANCE						
LOAD	HP	AMPERES	RPM	% POWER FACTOR	% EFFICIENCY	
NO LOAD	0	14.4	3600	12.7	0	
1/4	15.0	21.3	3590	74.9	87.8	
2/4	30.0	34.0	3580	89.4	92.4	
3/4	45.0	48.8	3569	92.4	93.5	
4/4	60.0	65.1	3558	92.1	93.6	
5/4	75.0	82.5	3546	91.3	93.3	
SPEED TORQUE						
		RPM	TORQUE % FULL LOAD	TORQUE LB.-FT.	AMPERES	
LOCKED ROTOR		0	203	180	435	
PULL UP		1565	175	155	355	
BREAKDOWN		3397	231	205	212	
FULL LOAD		3558	100	88.6	65.1	
AMPERES SHOWN FOR 460. VOLT CONNECTION. IF OTHER VOLTAGE CONNECTIONS ARE AVAILABLE, THE AMPERES WILL VARY INVERSELY WITH THE RATED VOLTAGE REMARKS: TYPICAL DATA XE MOTOR-NEMA NOM. EFF. 93.6 % GUARANTEED MIN. EFF. 92.4%						
		DR. BY	W. L. SMITH	A-C MOTOR PERFORMANCE DATA		
		CK. BY	G. R. WEBB			
		APP. BY	D. M. BYRD			
		DATE	03/11/02			
			A36WG1558-R012 ISSUE DATE 04/30/19			

REL S.O.

 RPM **3560**

 S.F. **1.00**

 ROTOR **418141005XE**

 FRAME **364TS**

 VOLTS **230/460**

 NEMA DESIGN **B**

 TEST S.O. **TYPICAL DATA**

 HP **60**

 AMPS **130/65.1**

 CODE LETTER **G**

 TEST DATE **---**

 TYPE **P**

 DUTY **CONT**

 ENCLOSURE **TEFC**


 STATOR RES. @ 25 °C **.0254/.101**

 PHASE/HERTZ **3/60**

 AMB °C/INSUL **40/F**

 E/S **491281**

OHMS (BETWEEN LINES)



AMPERES SHOWN FOR 460 VOLT CONNECTION, IF OTHER VOLTAGE CONNECTIONS ARE AVAILABLE, THE
 AMPERES WILL VARY INVERSELY WITH THE RATED VOLTAGE.

BALDOR
 A MEMBER OF THE ABB GROUP

DR. BY W. L. SMITH
 CK. BY G. R. WEBB
 APP. BY D. M. BYRD
 DATE 03/11/02

**A-C MOTOR
PERFORMANCE
CURVES**

A36WG1558-R012

ISSUE DATE 04/30/19

Page 9 of 13

REL. S.O.

 FRAME **364TS**

 HP **60**

 TYPE **P**

 PHASE/HERTZ **3/60**

 RPM **3560**

 VOLTS **230/460**

 AMPS **130/65.1**

 DUTY **CONT**

 AMB °C/INSUL **40/F**

 S.F. **1.00**

 NEMA DESIGN **B**

 CODE LETTER **G**

 ENCLOSURE **TEFC**

 E/S **491281**


 ROTOR **418141005XE**

 TEST S.O. **TYPICAL DATA**

 TEST DATE **---**

 STATOR RES. @ 25 °C **.0254/.101**

OHMS (BETWEEN LINES)



THERMAL LIMIT CURVE

REMARKS:

XE MOTOR-NEMA NOM. EFF. 93.6 %


GUARANTEED MIN. EFF. 92.4%

 AMPERES SHOWN FOR 460 VOLT CONNECTION, IF OTHER VOLTAGE CONNECTIONS ARE AVAILABLE, THE AMPERES WILL VARY INVERSELY WITH THE RATED VOLTAGE.

BALDOR
A MEMBER OF THE ABB GROUP


 DR. BY W. L. SMITH
 CK. BY G. R. WEBB
 APP. BY D. M. BYRD
 DATE 03/11/02
**A-C MOTOR
PERFORMANCE
CURVES**
A36WG1558-R012

 ISSUE DATE 04/30/19 Page 10 of 13



CONNECTION DIAGRAM
ACCESSORIES

MOTOR WINDING THERMOSTATS		
CONTACTS _____ @ _____ °C		
FIGURE NUMBER _____		
CONTACT RATING		
VOLTS	CONTINUOUS AMPERES	INRUSH AMPERES
110-120	3.0	30
220-240	1.5	15
440-480	0.75	7.5
550-600	0.60	6.0



CUSTOMER _____ CUSTOMER ORDER NO. _____ S.O. NO. _____

REV. DESC: LOADED TO BUS		
REV. LTR: A	VERSION: 01	TDR: 000000570390
FILE: \RAG\00013\849	REVISED: 10:16:21 12/07/2010	BY: RAGDRF
MTL: -		

BALDOR

A-C MOTOR CONNECTION ACCESSORIES



SH 1 of 1

418174-006

418174-006

416820-002

A-C MOTOR
CONNECTION DIAGRAM
STANDARD 9 LEAD DELTA-CONNECTED



(N. P. 1575-B)

416820-002

REV. DESC: ADJUST TEXT DARKNESS		
REV. LTR: B	VERSION: 02	TDR: 000001285318
FILE: \RAG\00022\453	REVISED: 09:36:26 09/24/2026	BY: USJOSUL
MTL: -	© □	



CONN DIAG - STANDARD 9 LEAD, DELTA-CONNECTED
SH1 of 1