

ABB BALDOR RELIANCE III

Customer information packet

ECP82394T-4

15HP, 3520RPM, 3PH, 60HZ, 254T, TEFC, F1

Class - CLI GP A,B,C,D

Division - Division II

Specifications

Enclosure	TEFC
Frame	254T
Frame Material	Iron
Frequency	60.00 Hz
Haz Area Class and Group	CLI GP A,B,C,D
Haz Area Division	Division II
Motor Letter Type	Three Phase
Output @ Frequency	15.000 HP @ 60 HZ
Phase	3
Synchronous Speed @ Frequency	3600 RPM @ 60 HZ
Voltage @ Frequency	460.0 V @ 60 HZ
Agency Approvals	CCSA US CSA EEV NEMA PREMIUM NEMA_PREMIUM UR
Ambient Temperature	40 °C
Auxiliary Box	NO AUXILLARY BOX
Auxiliary Box Lead Termination	None
Base Indicator	Rigid
Bearing Grease Type	Polyrex EM (-20F +300F)
Blower	None
Constant Torque Speed Range	6
Current @ Voltage	17.000 A @ 460.0 V
Design Code	B
Drip Cover	No Drip Cover
Duty Rating	CONT
Efficiency @ 100% Load	91.0 %
Electrically Isolated Bearing	Not Electrically Isolated
Enclosure Modification	841
Feedback Device	NO FEEDBACK
Haz Area Temp Code	T3C

Part Detail

Revision	N
Type	AC
Mech. spec.	
Base	
Status	PRD/A
Elec. spec.	09WGY948
Layout	09LYJ286
Eff. date	11-14-2023
CD Diagram	CD00006
Poles	02
Leads	3#12
Proprietary	False
Created date	11-27-2018

Heater Indicator	No Heater
High Voltage Full Load Amps	17.0 a
Insulation Class	F
Inverter Code	Inverter Duty
IP Rating	IP56
KVA Code	G
Lifting Lugs	Standard Lifting Lugs
Locked Bearing Indicator	Locked Bearing
Max Speed	5400 rpm
Motor Lead Termination	Ring Terminals
Motor Standards	NEMA
Motor Type	0934M
Mounting Arrangement	F1
Number of Poles	2
Overall Length	24.78 IN
Power Factor	89
Product Family	Chem Process S/P 32-8 IEEE 841
Pulley Face Code	Standard
Rodent Screen	None
Service Factor	1.15
Shaft Diameter	1.625 IN
Shaft Ground Indicator	No Shaft Grounding
Shaft Rotation	Reversible
Speed	3520 rpm
Speed Code	Single Speed
Starting Method	Direct on line
Thermal Device - Bearing	None
Thermal Device - Winding	None
Vibration Sensor Indicator	No Vibration Sensor
Winding Thermal 1	None
Winding Thermal 2	None

Nameplate
NP4332

CAT.NO.	ECP82394T-4			P/N		ENCLOSURE			TEFC					
SPEC.	09-0000-0859		CC	010A	FRAME	254T		S/N						
HP	15			CLASS	F	HZ	60	ODE BRG	6309	DE BRG	6309			
RPM	3520	RPM MAX	5400	PH	3	DES	B	D.E. BRG.	45BC03X30X					
VOLT	460			KVA-CODE	G		O.D.E. BRG.	45BC03X30X						
AMP	17			MOTOR WEIGHT			295	GREASE	POLYREX EM					
RATING	40C AMB-CONT			MAX. KVAR			1.6	BLANK						
NEMA-NOM-EFF	91	# OF ROTOR BARS			28	SER.F.	1.15	IP	56					
G.MIN.EFF	89.5	# OF STATOR SLOTS			36	PF	89	INV.TYPE	PWM					
TEMP CODE	T3C	INVERTER-TEMP-CODE			180									
TEMP =	160	C HP FR	60	C HP TO	90									
CT HZ FROM	6	CT HZ TO	60											
HTR-VOLTS		HTR-AMPS		HTR-WATTS				MAX. SPACE HEATER TEMP.			VT HZ FROM	0-	VT HZ TO	60

AC Induction Motor Performance Data

Record # 49591

Typical performance - not guaranteed values

Winding: 09WGY948-R035			Type: 0934M		Enclosure: TEFC			
Nameplate Data			460 V, 60 Hz: Single Voltage Motor					
Rated Output (HP)		15	Full Load Torque		22.4 LB-FT			
Volts		460	Start Configuration		direct on line			
Full Load Amps		17	Breakdown Torque		87.8 LB-FT			
R.P.M.		3520	Pull-up Torque		26 LB-FT			
Hz	60	Phase	3	Locked-rotor Torque		32.7 LB-FT		
NEMA Design Code		B	KVA Code	G	Starting Current		114 A	
Service Factor (S.F.)		1.15	No-load Current		5.1 A			
NEMA Nom. Eff.		91	Power Factor		89	Line-line Res. @ 25°C		0.622 Ω
Rating - Duty		40C	AMB-CONT		Temp. Rise @ Rated Load		54°C	
S.F. Amps			Temp. Rise @ S.F. Load		67°C			
			Locked-rotor Power Factor		28.4			
			Rotor inertia		0.868 lb-ft²			

Load Characteristics 460 V, 60 Hz, 15 HP

% of Rated Load	25	50	75	100	125	150	S.F.
Power Factor	61	80	88	89	90	90	90
Efficiency	87.4	91.1	91.7	91.3	90.1	88.7	90.5
Speed	3581	3563	3544	3522	3499	3472	3508
Line amperes	6.66	9.71	13.1	17.3	21.7	26.5	19.9


ABB Motors and Mechanical Inc.


WINDING # 09WGY948

Typical performance - not guaranteed values.



15 HP 3 PH 60 HZ 3520 RPM 460 V 0934M

TORQUES (LB-FT): PO=87.8 PU=26 LR=32.7 LRA=114





CD0006


NOTES:

1. THREE LEAD MOTOR MAY BE EITHER WYE CONNECTED OR DELTA CONNECTED.
2. INTERCHANGE ANY TWO LINE LEADS TO REVERSE ROTATION.
3. OPTIONAL THERMOSTATS ARE PROVIDED WHEN SPECIFIED.
4. ACTUAL NUMBER OF INTERNAL PARALLEL CIRCUITS MAY VARY.
5. LEAD COLORS ARE OPTIONAL. LEADS MUST BE NUMBERED AS SHOWN.

CD0006

REV. DESC: ADD CLASS CONN00000007

REV. LTR: E

VERSION: 01

TDR: 000001099922

FILE: \AAA\00005\141

REVISED: 10:24:49 02/19/2019

BY: ENBRIRO

MTL: -


BALDOR - RELIANCE®

3PH, SV, 3 LEADS, WYE OR DELTA CONNECTED

SH 1 of 1