

ABB BALDOR RELIANCE III

Customer information packet

ECP844156T-4

150HP, 1190RPM, 3PH, 60HZ, 447T, TEFC, FOOT,

Class - CLI GP A,B,C,D

Division - Division II

Specifications

Enclosure	TEFC
Frame	447T
Frame Material	Iron
Frequency	60.00 Hz
Haz Area Class and Group	CLI GP A,B,C,D
Haz Area Division	Division II
Motor Letter Type	Three Phase
Output @ Frequency	150.000 HP @ 60 HZ
Phase	3
Synchronous Speed @ Frequency	1200 RPM @ 60 HZ
Voltage @ Frequency	460.0 V @ 60 HZ
Agency Approvals	UR CCSA US
Ambient Temperature	40 °C
Auxiliary Box	NO AUXILLARY BOX
Base Indicator	Rigid
Bearing Grease Type	Polyrex EM (-20F +300F)
Constant Torque Speed Range	15-60
Current @ Voltage	170.000 A @ 460.0 V
Design Code	B
Drip Cover	No Drip Cover
Duty Rating	CONT
Efficiency @ 100% Load	95.8 %
Enclosure Modification	841
Feedback Device	NO FEEDBACK
Haz Area Temp Code	T3
Heater Indicator	No Heater
High Voltage Full Load Amps	170.0 a
Insulation Class	F
Inverter Code	Inverter Ready
IP Rating	IP56
KVA Code	F

Part Detail

Revision	F
Type	AC
Mech. spec.	
Base	
Status	PRD/A
Elec. spec.	A44WG1496
Layout	617434-662
Eff. date	12-11-2023
CD Diagram	416820-036
Poles	06
Leads	3#1/0
Proprietary	False
Created date	12-11-2018

Lifting Lugs	No Lifting Lugs
Motor Lead Quantity/Wire Size	3 @ 1/0 AWG
Motor Standards	None
Motor Type	A44120M
Mounting Arrangement	F1
No Load Current	42.5 a
Number of Poles	6
Overall Length	48.47 IN
Power Factor	86
Pulley End Bearing Type	Ball
Pulley Face Code	Standard
Service Factor	1.15
Shaft Diameter	3.375 IN
Shaft Ground Indicator	No Shaft Grounding
Shaft Rotation	Phase Seq-Std Rot (CCWODE)
Shaft Slinger Indicator	No Slinger
Speed	1190 rpm
Speed Code	Single Speed
Starting Method	Direct on line
Thermal Device - Bearing	None
Thermal Device - Winding	None

Nameplate

NP4566																
CAT NO	ECP844156T-4			SPEC NO.		A44-8392-1496										
HP	150	AMPS		170	VOLTS		460		DESIGN		B					
FRAME SIZE	447T	RPM		1190	HZ		60	AMB		40	SF		1.15			
D.E. BRG.DATA	6318			O.D.E. BRG.DATA		6318			PH		3	DUTY		CONT	INSUL.CLASS	F
D.E. BRG.	90BC03J30X			TYPE		ENCL		TEFC		CODE		F				
O.D.E. BRG.	90BC03J30X			POWER FACTOR				86		NEMA-NOM-EFFICIENCY				95.8		
3/4 LOAD EFF.	96.2	IP		56	MAX CORR KVAR				25.0		GUARANTEED EFFICIENCY				95	
TEMP CODE	T3	TEMP =		200												
CHP HZ	60-90	CT HZ		15-60	VT HZ		0-60									
INVERTER-TEMP-CODE	T3															
SER.NO.					MOTOR WEIGHT											

000613007EX				
CAT NO	ECP844156T-4	SPEC NO.	A44-8392-1496	
NO. ROTOR BARS	71	GREASE TYPE	POLYREX EM	
NO. SLOTS	90	NL AMPS AT RATED VOLTAGE	42.5	
5 YEAR WARRANTY		WINDING RES @25 C	.03239	OHMS
MFG. DATE		SER.NO		

REL. S.O.	FRAME	HP	TYPE	PHASE/ HERTZ	RPM	VOLTS
	447T	150	P	3/60	1190	460
AMPS	DUTY	AMB °C/ INSUL.	S.F.	NEMA DESIGN	CODE LETTER	ENCL.
170	CONT	40/F	1.15	B	F	TEFC
E/S	ROTOR	TEST S.O.	TEST DATE	STATOR RES. @25 °C OHMS (BETWEEN LINES)		
833241	418143080ME	---	---	.0324		
PERFORMANCE						
LOAD	HP	AMPERES	RPM	% POWER FACTOR	% EFFICIENCY	
NO LOAD	0	42.5	1200	3.70	0	
1/4	37.6	65.5	1197	56.6	94.9	
2/4	75.1	94.9	1194	76.9	96.3	
3/4	112	130	1191	83.9	96.2	
4/4	150	170	1188	86.3	95.8	
5/4	188	213	1184	86.8	95.1	
SPEED TORQUE						
		RPM	TORQUE % FULL LOAD	TORQUE LB.-FT.	AMPERES	
LOCKED ROTOR		0	121	799	1025	
PULL UP		180	97.2	644	1002	
BREAKDOWN		1150	236	1563	592	
FULL LOAD		1188	100	663	170	
AMPERES SHOWN FOR 460. VOLT CONNECTION. IF OTHER VOLTAGE CONNECTIONS ARE AVAILABLE, THE AMPERES WILL VARY INVERSELY WITH THE RATED VOLTAGE						
REMARKS: TYPICAL DATA NEMA NOMINAL EFFICIENCY = 95.4 PCT.						
		DR. BY W. L. SMITH CK. BY J. J. HARRISON APP. BY W. L. SMITH DATE 04/27/10		A-C MOTOR PERFORMANCE A44WG1496-R001 DATA ISSUE DATE 12/18/10		

FRAME 447T

RPM 1190

VOLTS 460

NEMA DESIGN B

HP 150

AMPS 170

CODE LETTER F

TEST S.O. TYPICAL DATA

TYPE P

DUTY CONT

ENCLOSURE TEFC


TEST DATE ---

PHASE/HERTZ 3/60

AMB °C/INSUL 40/F

E/S 833241

STATOR RES. @ 25 °C .0324
OHMS (BETWEEN LINES)



AMPERES SHOWN FOR 460 VOLT CONNECTION, IF OTHER VOLTAGE CONNECTIONS ARE AVAILABLE, THE AMPERES WILL VARY INVERSELY WITH THE RATED VOLTAGE.

BALDOR

DR. BY W. L. SMITH
CK. BY J.J. HARRISON
APP. BY W. L. SMITH
DATE 04/27/10

**A-C MOTOR
PERFORMANCE CURVES** A44WG1496-R001
ISSUE DATE 12/18/10

REL. S.O.

RPM 1190

S.F. 1.15

ROTOR 418143080ME

FRAME 447T

VOLTS 460

NEMA DESIGN B

TEST S.O. TYPICAL DATA

HP 150

AMPS 170

CODE LETTER F

TEST DATE ---

TYPE P

DUTY CONT

ENCLOSURE TEFC


STATOR RES. @ 25 °C .0324

PHASE/HERTZ 3/60

AMB °C/INSUL 40/F

E/S 833241

OHMS (BETWEEN LINES)



THERMAL LIMIT CURVE


REMARKS: NEMA NOMINAL EFFICIENCY = 95.4 PCT.


AMPERES SHOWN FOR 460 VOLT CONNECTION, IF OTHER VOLTAGE CONNECTIONS ARE AVAILABLE, THE AMPERES WILL VARY INVERSELY WITH THE RATED VOLTAGE.

BALDOR

DR. BY W. L. SMITH
CK. BY J.J.HARRISON
APP. BY W. L. SMITH
DATE 04/27/10


**A-C MOTOR
PERFORMANCE A44WG1496-R001
CURVES** ISSUE DATE 12/18/10





416820-036

A-C MOTOR
CONNECTION DIAGRAM
STANDARD 3 LEAD CONNECTED



(N.P. 1575-BA)

416820-036

REV. DESC: LOADED TO BUS, C/R 335225		
REV. LTR: -	VERSION: 00	TDR: 000000538207
FILE: \MGA\00000\682		REVISED: 11: 54: 06 04/30/2010
MTL: -		BY: RAGRA

BALDOR

CONN DIAG - STANDARD 3 LEAD
SH 1 of 1