

ABB BALDOR RELIANCE III

Customer information packet

ECS101M0K7P5FE4

7.5KW, 1500RPM, 3PH, 50HZ, D132D, 3740B, TEFC

Class - None

Division - Not Applicable

Specifications

Enclosure	TEFC
Frame	D132D
Frame Material	Steel
Frequency	50.00 Hz
Haz Area Class and Group	None
Haz Area Division	Not Applicable
Motor Letter Type	Brushless Wound Field PM Rotor
Output @ Frequency	7.500 KW @ 50 HZ
Phase	3
Synchronous Speed @ Frequency	1500 RPM @ 50 HZ
Voltage @ Frequency	190.0 V @ 50 HZ 380.0 V @ 50 HZ
Agency Approvals	CE WEEE UKCA CULUS
Ambient Temperature	40 °C
Auxiliary Box	NO AUXILLARY BOX
Auxiliary Box Lead Termination	None
Base Indicator	Rigid
Bearing Grease Type	Polyrex EM (-20F +300F)
Blower	None
Constant Torque Speed Range	5
Current @ Voltage	13.800 A @ 380.0 V 27.600 A @ 190.0 V
Design Code	B
Drip Cover	No Drip Cover
Duty Rating	S1
Efficiency @ 100% Load	93.7 %
Electrically Isolated Bearing	Not Electrically Isolated
Feedback Device	NO FEEDBACK
Frame Prefix	D

Part Detail

Revision	G
Type	AC
Mech. spec.	
Base	
Status	PRD/A
Elec. spec.	37WGA0017
Layout	37LYT621
Eff. date	02-12-2026
CD Diagram	CD0005A25
Poles	04
Leads	9#12
Proprietary	False
Created date	01-11-2023

Heater Indicator	No Heater
High Voltage Full Load Amps	13.8 a
Insulation Class	F
Inverter Code	Inverter Duty
Lifting Lugs	Standard Lifting Lugs
Locked Bearing Indicator	Locked Bearing
Motor Lead Termination	Terminal Block
Motor Standards	IEC
Motor Type	3740B
Mounting Arrangement	B5
Number of Poles	4
Overall Length	18.75 IN
Power Factor	94
Product Family	General Purpose
Pulley Face Code	D-Flange
Rodent Screen	None
Service Factor	1.00
Shaft Diameter	1.497 IN
Shaft Ground Indicator	Shaft Grounding
Shaft Rotation	Reversible
Speed	1500 rpm
Speed Code	Single Speed
Starting Method	INVERTER SPECIAL
Thermal Device - Bearing	None
Thermal Device - Winding	None
Vibration Sensor Indicator	No Vibration Sensor
Winding Thermal 1	None
Winding Thermal 2	None

Nameplate

NP3968B01A01										
CAT.NO.	ECS101M0K7P5FE4									
SPEC.	37-0000-0492				YR					
FRAME	D132D		IP	55	WT.		131			
KW	7.5	HZ	50	PH		3	DUTY-IPM		S1	
INS CL	F	CLASS RISE				AMB-C		40		
EFF. CL	IE5	EFF	93.7		COSφ		94			
VOLTS	190/380		FLA		28.15/14.08					
1/MIN	1500			1/MIN MAX			3000			
BEMF (V)	200			RS (OHMS)			0.93			
LD (MH)	23.21			LQ (MH)			75.933			
VPWM	CP =		50	TO		100				
CT	5	TO	50	VT		1	TO	50		
MATCHED INV										
DE	6208		ODE		6206					
SERIAL #										

Volts	190/380	Max RPM	3000	Conn Diag.	CD0005A25	Leads	9
Amps	28.71/14.36	Max Amps		Cs Diagram	CS0576	BEMF	184
KW	7.5	VFD#	ACS380-040S-17			LD	23.21
RPM	1500	S.F.	1.00			LQ	75.933
Phase/Hz	3/50	Rating	40C AMB-S1			Rs	0.9585 Meas. L-L

60034-2-3 Motor Performance at Standardized Operating Points

	RPM	% Speed	LB-FT	% Torque	KW	Efficiency	Loss (% FL)	Watts Loss (W)
P1	1350	90%	35.2	100%	9.0	93.9	5.88%	441
P2	750	50%	35.2	100%	5.0	91.1	4.93%	370
P3	375	25%	35.2	100%	2.5	85.2	4.33%	325
P4	1350	90%	17.6	50%	4.5	94.8	2.47%	185
P5	750	50%	17.6	50%	2.5	92.9	1.93%	144
P6	750	50%	8.8	25%	1.3	93.4	0.89%	67
P7	375	25%	8.8	25%	0.6	90.5	0.66%	49

61800-9-2 PDS Performance at Reference Operating Points


	RPM	% Speed	LB-FT	% Torque	KW	System Efficiency	Loss (% FL)	Watts Loss (W)
P1	1500	100%	35.2	100%	10.1	92.0	8.71%	653
P2	750	50%	35.2	100%	5.0	87.9	6.89%	517
P3	255	17%	35.2	100%	1.7	74.2	5.91%	443
P4	1500	100%	17.6	50%	5.0	92.7	3.95%	296
P5	750	50%	17.6	50%	2.5	89.2	3.02%	226
P6	255	17%	17.6	50%	0.9	77.5	2.47%	185
P7	750	50%	8.8	25%	1.3	88.5	1.62%	121
P8	255	17%	8.8	25%	0.4	76.9	1.28%	96

Points not taken in certified order.

	DR By:	R & D	AC MOTOR PERFORMANCE CURVES	37WGA0017 37-0000-0488 Test - 111844
	CK By:	USTOSAN		
	APP By:	USJAROB1		
	Date:	01/28/2025		

Volts	190/380	Max RPM	3000	Conn Diag.	CD0005A25	Leads	9
Amps	28.71/14.36	Max Amps		Cs Diagram	CS0576	BEMF	184
KW	7.5	VFD #	ACS380-040S-17			LD	23.21
RPM	1500	S.F.	1.00			LQ	75.933
Phase/Hz	3/50	Rating	40C AMB-S1			Rs	0.9585 Meas L-L

Constant Duty Operating Range


BALDOR • RELIANCE

DR By: R & D

CK By: USTOSAN

APP By: USJAROB1

Date: 01/28/2025
**AC MOTOR
PERFORMANCE
CURVES**
37WGA0017

37-0000-0488

Test - 111844

