

ABB BALDOR RELIANCE III

Customer information packet

ECTM2276T-G

7.5HP, 1180RPM, 3PH, 60HZ, 254T, 0954M, TEFC, F

Class - None

Division - Not Applicable

Specifications

Enclosure	TEFC
Frame	254T
Frame Material	Iron
Frequency	60.00 Hz
Haz Area Class and Group	None
Haz Area Division	Not Applicable
Motor Letter Type	Three Phase
Output @ Frequency	7.500 HP @ 60 HZ
Phase	3
Synchronous Speed @ Frequency	1200 RPM @ 60 HZ
Voltage @ Frequency	230.0 V @ 60 HZ 460.0 V @ 60 HZ
Agency Approvals	CSA EEV NEMA PREMIUM NEMA_PREMIUM UR
Ambient Temperature	40 °C
Auxiliary Box	NO AUXILLARY BOX
Auxiliary Box Lead Termination	None
Base Indicator	Rigid
Bearing Grease Type	Polyrex EM (-20F +300F)
Blower	None
Current @ Voltage	23.000 A @ 208.0 V 22.000 A @ 230.0 V 11.000 A @ 460.0 V
Design Code	A
Drip Cover	No Drip Cover
Duty Rating	CONT
Efficiency @ 100% Load	91.0 %
Electrically Isolated Bearing	Not Electrically Isolated
Feedback Device	NO FEEDBACK
Front Shaft Indicator	Tapped & Key

Part Detail

Revision	J
Type	AC
Mech. spec.	09N188
Base	
Status	PRD/A
Elec. spec.	09WGT118
Layout	09LYN188
Eff. date	09-11-2025
CD Diagram	CD0005
Poles	06
Leads	9#12
Proprietary	False
Created date	04-11-2022

Heater Indicator	Heater Included, 115 V
High Voltage Full Load Amps	11.0 a
Insulation Class	F
Inverter Code	Inverter Ready
KVA Code	J
Lifting Lugs	Vertical Lifting Lugs
Locked Bearing Indicator	Locked Bearing
Motor Lead Quantity/Wire Size	9 @ 12 AWG
Motor Lead Termination	Flying Leads
Motor Standards	NEMA
Motor Type	0954M
Mounting Arrangement	F1
Number of Poles	6
Overall Length	23.55 IN
Power Factor	70
Product Family	Chemical Processing (Not DC)
Pulley End Bearing Type	Sealed Bearing
Pulley Face Code	Standard
Pulley Shaft Indicator	Tapped & Key
Rodent Screen	None
RoHS Status	ROHS COMPLIANT
Service Factor	1.15
Shaft Diameter	1.625 IN
Shaft Ground Indicator	Shaft Grounding
Shaft Rotation	Reversible
Shaft Slinger Indicator	Shaft Slinger
Speed	1180 rpm
Speed Code	Single Speed
Starting Method	Direct on line
Thermal Device - Bearing	None
Thermal Device - Winding	None
Vibration Sensor Indicator	No Vibration Sensor
Winding Thermal 1	None
Winding Thermal 2	None

Nameplate

NP1260									
CAT.NO.	ECTM2276T-G								
SPEC.	09N188T118G1								
HP	7.5								
VOLTS	230/460								
AMP	22/11								
RPM	1180								
FRAME	254T		HZ	60		PH		3	
SER.F.	1.15		CODE	J	DES	A		CL	F
NEMA-NOM-EFF	91		PF	70					
RATING	40C AMB-CONT								
CC	010A								
DE	6309		ODE	6208					
ENCL	TEFC		SN						
	INV DUTY 20:1 VT								

AC Induction Motor Performance Data

Record # 47544

Typical performance - not guaranteed values

Winding: 09WGT118-R001			Type: 0954M		Enclosure: TEFC		
Nameplate Data			460 V, 60 Hz: High Voltage Connection				
Rated Output (HP)		7.5	Full Load Torque		33.2 LB-FT		
Volts		230/460	Start Configuration		direct on line		
Full Load Amps		22/11	Breakdown Torque		113 LB-FT		
R.P.M.		1180	Pull-up Torque		41.3 LB-FT		
Hz	60	Phase	3	Locked-rotor Torque		57.4 LB-FT	
NEMA Design Code		A	KVA Code	J	Starting Current		74.8 A
Service Factor (S.F.)		1.15	No-load Current		6.06 A		
NEMA Nom. Eff.		91	Power Factor	70	Line-line Res. @ 25°C		0.87037 Ω
Rating - Duty		40C	AMB-CONT		Temp. Rise @ Rated Load		36°C
S.F. Amps					Temp. Rise @ S.F. Load		42°C
					Locked-rotor Power Factor		25.8

Load Characteristics 460 V, 60 Hz, 7.5 HP

% of Rated Load	25	50	75	100	125	150	S.F.
Power Factor	32	52	63	70	74	75	72
Efficiency	83.2	89.4	90.9	91.1	90.7	89.9	90.9
Speed	1196.5	1192.4	1188.3	1183.7	1178.7	1173.2	1181
Line amperes	6.49	7.59	9.09	11	13.1	15.5	12.3

ABB Motors and Mechanical Inc.

WINDING # 09WGT118

Typical performance - not guaranteed values.

7.5 HP 3 PH 60 HZ 1180 RPM 460 V 0954M

TORQUES (LB-FT): PO=113 PU=41.3 LR=57.4 LRA=74.8



