

ABB BALDOR RELIANCE III

Customer information packet

EFM3212T-G

5HP, 3465RPM, 3PH, 60HZ, 182T, 3622M, OPSB, F2

Class - None

Division - Not Applicable

Specifications

Enclosure	OPSB
Frame	182T
Frame Material	Steel
Frequency	60.00 Hz
Haz Area Class and Group	None
Haz Area Division	Not Applicable
Motor Letter Type	Three Phase
Output @ Frequency	5.000 HP @ 60 HZ
Phase	3
Synchronous Speed @ Frequency	3600 RPM @ 60 HZ
Voltage @ Frequency	230.0 V @ 60 HZ 460.0 V @ 60 HZ
Agency Approvals	NEMA PREMIUM UR CSA EEV
Ambient Temperature	40 °C
Auxiliary Box	NO AUXILLARY BOX
Auxiliary Box Lead Termination	None
Base Indicator	Rigid
Bearing Grease Type	Polyrex EM (-20F +300F)
Blower	None
Current @ Voltage	11.800 A @ 230.0 V 12.400 A @ 208.0 V 5.900 A @ 460.0 V
Design Code	A
Drip Cover	No Drip Cover
Duty Rating	CONT
Efficiency @ 100% Load	86.5 %
Electrically Isolated Bearing	Not Electrically Isolated
Feedback Device	NO FEEDBACK
Front Shaft Indicator	None
Heater Indicator	No Heater

Part Detail

Revision	E
Type	AC
Mech. spec.	36Q125
Base	
Status	PRD/A
Elec. spec.	36WGQ033
Layout	36LYQ125
Eff. date	04-02-2026
CD Diagram	CD0005
Poles	02
Leads	9#16
Proprietary	False
Created date	03-30-2023

High Voltage Full Load Amps	5.9 a
Insulation Class	H
Inverter Code	Inverter Ready
KVA Code	J
Lifting Lugs	No Lifting Lugs
Locked Bearing Indicator	Locked Bearing
Motor Lead Quantity/Wire Size	9 @ 16 AWG
Motor Lead Termination	Flying Leads
Motor Standards	NEMA
Motor Type	3622M
Mounting Arrangement	F2
Number of Poles	2
Overall Length	13.62 IN
Power Factor	91
Product Family	General Purpose
Pulley End Bearing Type	Ball
Pulley Face Code	Standard
Pulley Shaft Indicator	Standard
Rodent Screen	None
Service Factor	1.15
Shaft Diameter	1.125 IN
Shaft Ground Indicator	Shaft Grounding
Shaft Rotation	Reversible
Shaft Slinger Indicator	No Slinger
Speed	3465 rpm
Speed Code	Single Speed
Starting Method	Direct on line
Thermal Device - Bearing	None
Thermal Device - Winding	None
Vibration Sensor Indicator	No Vibration Sensor
Winding Thermal 1	None
Winding Thermal 2	None

Nameplate

NP3553L									
CAT.NO.	EFM3212T-G								
SPEC	36Q125Q033G1								
HP	5								
VOLTS	230/460								
AMPS	11.8/5.9								
RPM	3465								
FRAME	182T		HZ	60			PH	3	
SF	1.15	CODE	J	DES	A	CLASS	H		
NEMA NOM. EFF	86.5	PF	91						
RATING	40C AMB-CONT								
CC	010A								
ENCL	OPSB	SER							
DE	6206		ODE	6205					
VPWM INVERTER READY									
CT30-60(2:1) VT3-60(20:1)									

AC Induction Motor Performance Data

Record # 85737

Preliminary Data Sheet

Winding: 36WGQ033-RXXX			Type: 3622M		Enclosure: OPSB	
Nameplate Data			460 V, 60 Hz: High Voltage Connection			
Rated Output (HP)		5	Full Load Torque		7.57 LB-FT	
Volts		230/460	Start Configuration		direct on line	
Full Load Amps		11.8/5.9	Breakdown Torque		28.9 LB-FT	
R.P.M.		3465	Pull-up Torque		20.2 LB-FT	
Hz	60	Phase	3	Locked-rotor Torque		22.2 LB-FT
NEMA Design Code		A	KVA Code		J	Starting Current
Service Factor (S.F.)		1.15	No-load Current		2 A	
NEMA Nom. Eff.		86.5	Power Factor		91	Line-line Res. @ 25°C
Rating - Duty		40C	AMB-CONT		Temp. Rise @ Rated Load	
S.F. Amps		13.4/6.7			Temp. Rise @ S.F. Load	
					Locked-rotor Power Factor	
					Rotor inertia	
					0.0988 lb-ft²	

Load Characteristics 460 V, 60 Hz, 5 HP

% of Rated Load	25	50	75	100	125	150	S.F.
Power Factor	57	78	87	90	92	93	92
Efficiency	85.7	89.5	89.4	88.1	86.3	83.9	87
Speed	3568	3538	3504	3467	3425	3379	3435
Line amperes	2.44	3.38	4.56	5.89	7.38	9.02	6.76


ABB Motors and Mechanical Inc.


WINDING # 36WGQ033

Typical performance - not guaranteed values.




5 HP 3 PH 60 HZ 3465 RPM 460 V 3622M

TORQUES (LB-FT): PO=28.9 PU=20.2 LR=22.2 LRA=46.1





CD0005



- NOTES:
- 1. INTERCHANGE ANY TWO LINE LEADS TO REVERSE ROTATION.
 - 2. OPTIONAL THERMOSTATS ARE PROVIDED WHEN SPECIFIED.
 - 3. ACTUAL NUMBER OF INTERNAL PARALLEL CIRCUITS MAY BE A MULTIPLE OF THOSE SHOWN ABOVE.
 - 4. LEAD COLORS ARE OPTIONAL. LEADS MUST ALWAYS BE NUMBERED AS SHOWN.

REV. DESC: REVISE TO SHOW OPTIONAL COLORS			
REV. LTR: E	BY: JLP	REVISED: 01/19/99 10:15	TDR: 0171435
900000		FILE: AAA00005140	MDL: -
		MTL: -	

BALDOR ELECTRIC Co.

3PH, DV, 9 LEADS

CD0005