

ABB BALDOR RELIANCE III

Customer information packet

EJMM3211T-8

3HP, 1765RPM, 3PH, 60HZ, 182JM, 3630M, OPSB, F1

Class - None

Division - Not Applicable

Specifications

Enclosure	OPSB
Frame	182JM
Frame Material	Steel
Frequency	60.00 Hz
Haz Area Class and Group	None
Haz Area Division	Not Applicable
Motor Letter Type	Three Phase
Output @ Frequency	3.000 HP @ 60 HZ
Phase	3
Synchronous Speed @ Frequency	1800 RPM @ 60 HZ
Voltage @ Frequency	200.0 V @ 60 HZ
Agency Approvals	UR CSA CSA EEV
Ambient Temperature	40 °C
Auxiliary Box	NO AUXILLARY BOX
Auxiliary Box Lead Termination	None
Base Indicator	Rigid
Bearing Grease Type	Polyrex EM (-20F +300F)
Blower	None
Current @ Voltage	9.700 A @ 200.0 V
Design Code	B
Drip Cover	No Drip Cover
Duty Rating	CONT
Efficiency @ 100% Load	89.5 %
Electrically Isolated Bearing	Not Electrically Isolated
Feedback Device	NO FEEDBACK
Front Face Code	Standard
Front Shaft Indicator	None
Heater Indicator	No Heater
High Voltage Full Load Amps	9.7 a
Insulation Class	F

Part Detail

Revision	L
Type	AC
Mech. spec.	36G687
Base	
Status	PRD/A
Elec. spec.	36WGS760
Layout	36LYG687
Eff. date	07-12-2024
CD Diagram	CD0006
Poles	04
Leads	3#14
Proprietary	False
Created date	09-19-2012

Inverter Code	Inverter Ready
KVA Code	K
Lifting Lugs	No Lifting Lugs
Locked Bearing Indicator	Locked Bearing
Motor Lead Exit	Ko Box
Motor Lead Quantity/Wire Size	3 @ 14 AWG
Motor Lead Termination	Flying Leads
Motor Standards	NEMA
Motor Type	3630M
Mounting Arrangement	F1
Number of Poles	4
Overall Length	16.50 IN
Power Factor	74
Product Family	General Purpose
Pulley End Bearing Type	Ball
Pulley Face Code	C-Face
Pulley Shaft Indicator	Tapped & Key
Rodent Screen	Included
Service Factor	1.15
Shaft Diameter	0.875 IN
Shaft Extension Location	Pulley End
Shaft Ground Indicator	No Shaft Grounding
Shaft Rotation	Reversible
Shaft Slinger Indicator	Shaft Slinger
Speed	1765 rpm
Speed Code	Single Speed
Starting Method	Direct on line
Thermal Device - Bearing	None
Thermal Device - Winding	None
Vibration Sensor Indicator	No Vibration Sensor
Winding Thermal 1	None
Winding Thermal 2	None

Nameplate

NP1259L											
CAT.NO.	EJMM3211T-8										
SPEC.	36G687S760G1										
HP	3										
VOLTS	200										
AMP	9.7										
RPM	1765										
FRAME	182JM		HZ	60				PH	3		
SER.F.	1.15		CODE	K	DES	B	CL	F			
NEMA-NOM-EFF	89.5		PF	74							
RATING	40C AMB-CONT										
CC	010A										
DE	6207		ODE	6205							
ENCL	OPSB		SN								

AC Induction Motor Performance Data

Record # 34571

Typical performance - not guaranteed values

Winding: 36WGS760-R001			Type: 3630M		Enclosure: OPSB		
Nameplate Data			200 V, 60 Hz: Single Voltage Motor				
Rated Output (HP)		3	Full Load Torque		8.85 LB-FT		
Volts		200	Start Configuration		direct on line		
Full Load Amps		9.7	Breakdown Torque		37.6 LB-FT		
R.P.M.		1765	Pull-up Torque		17.5 LB-FT		
Hz	60	Phase	3	Locked-rotor Torque		21.4 LB-FT	
NEMA Design Code		B	KVA Code	K	Starting Current		75.1 A
Service Factor (S.F.)		1.15	No-load Current		5.72 A		
NEMA Nom. Eff.		89.5	Power Factor	74	Line-line Res. @ 25°C		0.731 Ω
Rating - Duty		40C AMB-CONT		Temp. Rise @ Rated Load		24°C	
S.F. Amps				Temp. Rise @ S.F. Load		28°C	
				Locked-rotor Power Factor		43.6	
				Rotor inertia		0.279 LB-FT2	

Load Characteristics 200 V, 60 Hz, 3 HP

% of Rated Load	25	50	75	100	125	150	S.F.
Power Factor	32	53	66	73	78	81	76
Efficiency	79.6	87.3	89.3	89.6	89.5	88.3	89.6
Speed	1791	1783	1775	1766	1756	1745	1760
Line amperes	6.1	6.99	8.24	9.7	11.5	13.5	10.8


ABB Motors and Mechanical Inc.

WINDING # 36WGS760




Typical performance - not guaranteed values.

3 HP 3 PH 60 HZ 1765 RPM 200 V 3630M

TORQUES (LB-FT): PO=37.6 PU=17.5 LR=21.4 LRA=75.1



CD0006


NOTES:

1. THREE LEAD MOTOR MAY BE EITHER WYE CONNECTED OR DELTA CONNECTED.
2. INTERCHANGE ANY TWO LINE LEADS TO REVERSE ROTATION.
3. OPTIONAL THERMOSTATS ARE PROVIDED WHEN SPECIFIED.
4. ACTUAL NUMBER OF INTERNAL PARALLEL CIRCUITS MAY VARY.
5. LEAD COLORS ARE OPTIONAL. LEADS MUST BE NUMBERED AS SHOWN.

CD0006

REV. DESC: ADD CLASS CONN00000007

REV. LTR: E

VERSION: 01

TDR: 000001099922

FILE: \AAA\00005\141

REVISED: 10:24:49 02/19/2019

BY: ENBRIRO

MTL: -


BALDOR - RELIANCE®

3PH, SV, 3 LEADS, WYE OR DELTA CONNECTED

SH 1 of 1