

ABB BALDOR RELIANCE III

Customer information packet

EJMM3219T

7.5HP, 3480RPM, 3PH, 60HZ, 184JM, 3632M, OPSB

Class - None

Division - Not Applicable

Specifications

Enclosure	OPSB
Frame	184JM
Frame Material	Steel
Frequency	60.00 Hz
Haz Area Class and Group	None
Haz Area Division	Not Applicable
Motor Letter Type	Three Phase
Output @ Frequency	7.500 HP @ 60 HZ
Phase	3
Synchronous Speed @ Frequency	3600 RPM @ 60 HZ
Voltage @ Frequency	208.0 V @ 60 HZ 230.0 V @ 60 HZ 460.0 V @ 60 HZ
Agency Approvals	CURUSEEV NEMA PREMIUM
Ambient Temperature	40 °C
Auxiliary Box	NO AUXILLARY BOX
Auxiliary Box Lead Termination	None
Base Indicator	Rigid
Bearing Grease Type	Polyrex EM (-20F +300F)
Blower	None
Current @ Voltage	8.810 A @ 460.0 V 19.500 A @ 208.0 V 17.600 A @ 230.0 V
Design Code	A
Drip Cover	No Drip Cover
Duty Rating	CONT
Efficiency @ 100% Load	88.5 %
Electrically Isolated Bearing	Not Electrically Isolated
Feedback Device	NO FEEDBACK
Front Shaft Indicator	None
Heater Indicator	No Heater

Part Detail

Revision	A
Type	AC
Mech. spec.	36G687
Base	
Status	PRD/A
Elec. spec.	36WGZ653
Layout	36LYG687
Eff. date	01-07-2026
CD Diagram	CD0005
Poles	02
Leads	9#16
Proprietary	False
Created date	11-06-2025

High Voltage Full Load Amps	8.8 a
Insulation Class	F
Inverter Code	Not Inverter
KVA Code	L
Lifting Lugs	No Lifting Lugs
Locked Bearing Indicator	Locked Bearing
Motor Lead Quantity/Wire Size	9 @ 16 AWG
Motor Lead Termination	Flying Leads
Motor Standards	NEMA
Motor Type	3632M
Mounting Arrangement	F1
Number of Poles	2
Overall Length	16.50 IN
Power Factor	90
Product Family	General Purpose
Pulley End Bearing Type	Ball
Pulley Face Code	C-Face
Pulley Shaft Indicator	Tapped & Key
Rodent Screen	Included
Service Factor	1.15
Shaft Diameter	0.875 IN
Shaft Ground Indicator	No Shaft Grounding
Shaft Rotation	Reversible
Shaft Slinger Indicator	Shaft Slinger
Speed	3480 rpm
Speed Code	Single Speed
Starting Method	Direct on line
Thermal Device - Bearing	None
Thermal Device - Winding	None
Vibration Sensor Indicator	No Vibration Sensor
Winding Thermal 1	None
Winding Thermal 2	None

Nameplate

NP1259L											
CAT.NO.	EJMM3219T										
SPEC.	36G687Z653										
HP	7.5										
VOLTS	208-230/460										
AMP	19.5-17.6/8.81										
RPM	3480										
FRAME	184JM		HZ	60				PH	3		
SER.F.	1.15	CODE	L	DES	A	CL	F				
NEMA-NOM-EFF	88.5	PF	90								
RATING	40C AMB-CONT										
CC	010A										
DE	6207		ODE	6205							
ENCL	OPSB	SN									
	SFA 22.3-20.1/10.1										

AC Induction Motor Performance Data

Record # 115763

Typical performance - not guaranteed values

Winding: 36WGZ653-R001			Type: 3632M		Enclosure: OPSB	
Nameplate Data			460 V, 60 Hz: High Voltage Connection			
Rated Output (HP)		7.5	Full Load Torque		11.36 LB-FT	
Volts		208-230/460	Start Configuration		direct on line	
Full Load Amps		19.5-17.6/8.81	Breakdown Torque		70.5 LB-FT	
R.P.M.		3480	Pull-up Torque		39.5 LB-FT	
Hz	60 Phase	3	Locked-rotor Torque		45.1 LB-FT	
NEMA Design Code		A KVA Code	Starting Current		88.3 A	
Service Factor (S.F.)		1.15	No-load Current		3.3 A	
NEMA Nom. Eff.		88.5 Power Factor	Line-line Res. @ 25°C		1.6854 Ω	
Rating - Duty		40C AMB-CONT	Temp. Rise @ Rated Load		46°C	
S.F. Amps		22.3-20.1/10.1	Temp. Rise @ S.F. Load		58°C	
			Locked-rotor Power Factor		49.9	

Load Characteristics 460 V, 60 Hz, 7.5 HP

% of Rated Load	25	50	75	100	125	150	S.F.
Power Factor	53	76	85	90	92	93	91
Efficiency	87.3	91	91.2	90.3	89	87.3	89.5
Speed	3571.7	3544.8	3514.9	3484	3450	3414	3464
Line amperes	3.82	5.12	6.8	8.69	10.7	13	9.9

ABB Motors and Mechanical Inc.

WINDING # 36WGZ653

Typical performance - not guaranteed values.

7.5 HP 3 PH 60 HZ 3480 RPM 460 V 3632M

TORQUES (LB-FT): PO=70.5 PU=39.5 LR=45.1 LRA=88.3





