

ABB BALDOR RELIANCE III

Customer information packet

EL1319T

1.5HP, 1725RPM, 1PH, 60HZ, 145T, 3536LC, OPEN

Class - None

Division - Not Applicable

Specifications

Enclosure	OPEN
Frame	145T
Frame Material	Steel
Frequency	60.00 Hz
Haz Area Class and Group	None
Haz Area Division	Not Applicable
Motor Letter Type	Cap Start, Cap Run
Output @ Frequency	1.500 HP @ 60 HZ
Phase	1
Synchronous Speed @ Frequency	1800 RPM @ 60 HZ
Voltage @ Frequency	230.0 V @ 60 HZ 208.0 V @ 60 HZ 115.0 V @ 60 HZ
Agency Approvals	C UR US
Ambient Temperature	40 °C
Auxiliary Box	NO AUXILLARY BOX
Auxiliary Box Lead Termination	None
Base Indicator	Rigid
Bearing Grease Type	Polyrex EM (-20F +300F)
Blower	None
Current @ Voltage	6.300 A @ 208.0 V 5.800 A @ 230.0 V 12.800 A @ 115.0 V
Design Code	L
Drip Cover	No Drip Cover
Duty Rating	CONT
Efficiency @ 100% Load	83.8 %
Electrically Isolated Bearing	Not Electrically Isolated
Feedback Device	NO FEEDBACK
Front Shaft Indicator	None
Heater Indicator	No Heater
High Voltage Full Load Amps	5.8 a

Part Detail

Revision	J
Type	AC
Mech. spec.	35EE002
Base	
Status	PRD/A
Elec. spec.	35WGG129
Layout	35LYEE002
Eff. date	10-01-2024
CD Diagram	CD0016A01
Poles	04
Leads	7#18
Proprietary	False
Created date	08-01-2022

Insulation Class	F
Inverter Code	Not Inverter
IP Rating	NONE
KVA Code	K
Lifting Lugs	No Lifting Lugs
Locked Bearing Indicator	No Locked Bearing
Motor Lead Quantity/Wire Size	7 @ 18 AWG
Motor Lead Termination	Flying Leads
Motor Standards	NEMA
Motor Type	3536LC
Mounting Arrangement	F1
Number of Poles	4
Overall Length	13.00 IN
Power Factor	90
Product Family	General Purpose
Pulley End Bearing Type	Ball
Pulley Face Code	Standard
Pulley Shaft Indicator	Standard
Rodent Screen	None
Service Factor	1.15
Shaft Diameter	0.875 IN
Shaft Ground Indicator	No Shaft Grounding
Shaft Rotation	Reversible
Shaft Slinger Indicator	No Slinger
Speed	1750 rpm
Speed Code	Single Speed
Starting Method	Direct on line
Thermal Device - Bearing	None
Thermal Device - Winding	None
Vibration Sensor Indicator	No Vibration Sensor
Winding Thermal 1	None
Winding Thermal 2	None

Nameplate

NP2116L									
CAT.NO.	EL1319T								
SPEC.	35EE002G129								
HP	1.5								
VOLTS	115/208-230								
AMP	12.8/6.3-5.8								
RPM	1750								
FRAME	145T			HZ	60			PH	1
SER.F.	1.15		CODE	K		DES	L	CL	F
NEMA-NOM-EFF	83.8		PF	90					
RATING	40C AMB-CONT								
CC									
DE	6205		ODE	6203					
ENCL	OPEN		SN						
	SFA 14.3/7.8-7.15								

Accessories

Part number	Description	Multiplier
35-8764	C FACE KIT	A8
35EP1506A01SP	D-FLANGE KIT	A8

AC Induction Motor Performance Data

Record # 108313

Typical performance - not guaranteed values

Winding: 35WGG129-R002			Type: 3536LC		Enclosure: OPEN		
Nameplate Data			115 V, 60 Hz: Low Voltage Connection				
Rated Output (HP)		1.5	Full Load Torque		4.502 LB-FT		
Volts		115/208-230	Start Configuration		direct on line		
Full Load Amps		12.8/6.3-5.8	Breakdown Torque		12.8 LB-FT		
R.P.M.		1750	Pull-up Torque		10.2 LB-FT		
Hz	60	Phase	1	Locked-rotor Torque		15.7 LB-FT	
NEMA Design Code		L	KVA Code		K		
Service Factor (S.F.)		1.15	Starting Current		105 A		
NEMA Nom. Eff.		83.8	Power Factor		90		
Rating - Duty		40C	AMB-CONT		Temp. Rise @ Rated Load		34°C
S.F. Amps					Temp. Rise @ S.F. Load		41°C

Load Characteristics 115 V, 60 Hz, 1.5 HP

% of Rated Load	25	50	75	100	125	150	S.F.
Power Factor	63	79	86	90	92	93	91
Efficiency	67.5	79.8	83.5	84.2	83.2	80.9	83.6
Speed	1787	1777	1766.1	1753.9	1739.6	1722.1	1745
Line amperes	5.8	7.77	10.1	12.8	15.9	19.4	14.7


ABB Motors and Mechanical Inc.


WINDING # 35WGG129

Typical performance - not guaranteed values.

1.5 HP 1 PH 60 HZ 1750 RPM 115 V 3536LC

TORQUES (LB-FT): PO=12.8 PU=10.2 LR=15.7 LRA=105





CD0016A01

