

ABB BALDOR RELIANCE III

Customer information packet

EL1405T

2HP, 1740RPM, 1PH, 60HZ, 182T, 3623LC, OPSB, F1

Class - None

Division - Not Applicable

Specifications

Enclosure	OPSB
Frame	182T
Frame Material	Steel
Frequency	60.00 Hz
Haz Area Class and Group	None
Haz Area Division	Not Applicable
Motor Letter Type	Cap Start, Cap Run
Output @ Frequency	2.000 HP @ 60 HZ
Phase	1
Synchronous Speed @ Frequency	1800 RPM @ 60 HZ
Voltage @ Frequency	230.0 V @ 60 HZ 115.0 V @ 60 HZ
Agency Approvals	CSA EEV CURUS CURUSEEV NEMA PREMIUM (OLD LOGO) C U R U S
Ambient Temperature	40 °C
Auxiliary Box	NO AUXILLARY BOX
Auxiliary Box Lead Termination	None
Base Indicator	Rigid
Bearing Grease Type	Polyrex EM (-20F +300F)
Blower	None
Current @ Voltage	17.600 A @ 115.0 V 8.800 A @ 230.0 V
Design Code	L
Drip Cover	No Drip Cover
Duty Rating	CONT
Efficiency @ 100% Load	82.5 %
Electrically Isolated Bearing	Not Electrically Isolated
Feedback Device	NO FEEDBACK
Front Face Code	Standard

Part Detail

Revision	AN
Type	AC
Mech. spec.	36G967
Base	
Status	PRD/A
Elec. spec.	36WGY526
Layout	36LYG967
Eff. date	05-01-2024
CD Diagram	CD0055
Poles	04
Leads	6#16
Proprietary	False
Created date	01-01-0001

Front Shaft Indicator	None
Heater Indicator	No Heater
High Voltage Full Load Amps	8.8 a
Insulation Class	F
Inverter Code	Not Inverter
KVA Code	J
Lifting Lugs	No Lifting Lugs
Locked Bearing Indicator	No Locked Bearing
Motor Lead Exit	Ko Box
Motor Lead Quantity/Wire Size	6 @ 16 AWG
Motor Lead Termination	Flying Leads
Motor Standards	NEMA
Motor Type	3623LC
Mounting Arrangement	F1
Number of Poles	4
Overall Length	15.87 IN
Power Factor	90
Product Family	General Purpose
Pulley End Bearing Type	Ball
Pulley Face Code	Standard
Pulley Shaft Indicator	Standard
Rodent Screen	None
Service Factor	1.15
Shaft Diameter	1.125 IN
Shaft Extension Location	Pulley End
Shaft Ground Indicator	No Shaft Grounding
Shaft Rotation	Reversible
Shaft Slinger Indicator	No Slinger
Speed	1740 rpm
Speed Code	Single Speed
Starting Method	Direct on line
Thermal Device - Bearing	None
Thermal Device - Winding	None
Vibration Sensor Indicator	No Vibration Sensor

Winding Thermal 1	None
Winding Thermal 2	None

Nameplate

NP2116L									
CAT.NO.	EL1405T								
SPEC.	36G967Y526G1								
HP	2								
VOLTS	115/230								
AMP	17.6/8.8								
RPM	1740								
FRAME	182T		HZ	60		PH	1		
SER.F.	1.15	CODE	J	DES	L	CL	F		
NEMA-NOM-EFF	82.5	PF	90						
RATING	40C AMB-CONT								
CC									
DE	6206	ODE	6205						
ENCL	OPSB	SN							
	SFA 20.4/10.2								

Accessories

Part number	Description	Multiplier
36-3403	C FACE KIT	A8
36EP1405A09SP	D-FLANGE KIT	

AC Induction Motor Performance Data

Record # 11390

Typical performance - not guaranteed values

Winding: 36WGY526-R001			Type: 3623LC		Enclosure: OPSB			
Nameplate Data			230 V, 60 Hz: High Voltage Connection					
Rated Output (HP)		2	Full Load Torque		6.1 LB-FT			
Volts		115/230	Start Configuration		direct on line			
Full Load Amps		17.6/8.8	Breakdown Torque		13.2 LB-FT			
R.P.M.		1740	Pull-up Torque		9.2 LB-FT			
Hz	60	Phase	1	Locked-rotor Torque		14.7 LB-FT		
NEMA Design Code		L	KVA Code	J	Starting Current		62.4 A	
Service Factor (S.F.)		1.15		No-load Current		3.5 A		
NEMA Nom. Eff.		82.5	Power Factor		90	Line-line Res. @ 25°C		1.27 Ω A Ph 0.65 Ω B Ph
Rating - Duty		40C		AMB-CONT		Temp. Rise @ Rated Load		48°C
S.F. Amps		20.4/10.2		Temp. Rise @ S.F. Load				62°C

Load Characteristics 230 V, 60 Hz, 2 HP

% of Rated Load	25	50	75	100	125	150	S.F.
Power Factor	72	85	90	92	92	91	92
Efficiency	70.9	81.6	83.9	82.6	79.6	74.3	80.8
Speed	1787	1773	1758	1742	1722	1688	1730
Line amperes	3.46	4.83	6.61	8.6	11.08	17.38	10.1


ABB Motors and Mechanical Inc.


WINDING # 36WGY526

Typical performance - not guaranteed values.

2 HP 1 PH 60 HZ 1740 RPM 230 V 3623LC

TORQUES (LB-FT): PO=13.2 PU=9.2 LR=14.7 LRA=62.4





CD0055

