

ABB BALDOR RELIANCE III

Customer information packet

EM2514T

20HP, 3510RPM, 3PH, 60HZ, 254T, 3928M, OPSB, F1

Class - None

Division - Not Applicable

Specifications

Enclosure	OPSB
Frame	254T
Frame Material	Steel
Frequency	60.00 Hz
Haz Area Class and Group	None
Haz Area Division	Not Applicable
Motor Letter Type	Three Phase
Output @ Frequency	20.000 HP @ 60 HZ
Phase	3
Synchronous Speed @ Frequency	3600 RPM @ 60 HZ
Voltage @ Frequency	460.0 V @ 60 HZ 230.0 V @ 60 HZ
Agency Approvals	CURUSEEV NEMA PREMIUM NEMA PREMIUM (OLD LOGO)
Ambient Temperature	40 °C
Auxiliary Box	NO AUXILLARY BOX
Auxiliary Box Lead Termination	None
Base Indicator	Rigid
Bearing Grease Type	Polyrex EM (-20F +300F)
Blower	None
Current @ Voltage	47.000 A @ 230.0 V 51.000 A @ 208.0 V 23.500 A @ 460.0 V
Design Code	A
Drip Cover	No Drip Cover
Duty Rating	CONT
Efficiency @ 100% Load	91.0 %
Electrically Isolated Bearing	Not Electrically Isolated
Feedback Device	NO FEEDBACK
Front Face Code	Standard
Front Shaft Indicator	None

Part Detail

Revision	AA
Type	AC
Mech. spec.	39K57
Base	
Status	PRD/A
Elec. spec.	39WGX101
Layout	39LYK057
Eff. date	12-12-2025
CD Diagram	CD0180
Poles	02
Leads	9#10
Proprietary	False
Created date	10-22-2010

Heater Indicator	No Heater
High Voltage Full Load Amps	23.5 a
Insulation Class	F
Inverter Code	Inverter Ready
IP Rating	NONE
KVA Code	G
Lifting Lugs	Standard Lifting Lugs
Locked Bearing Indicator	No Locked Bearing
Motor Lead Exit	Ko Box
Motor Lead Quantity/Wire Size	9 @ 10 AWG
Motor Lead Termination	Flying Leads
Motor Standards	NEMA
Motor Type	3928M
Mounting Arrangement	F1
Number of Poles	2
Overall Length	21.69 IN
Power Factor	88
Product Family	General Purpose
Pulley End Bearing Type	Ball
Pulley Face Code	Standard
Pulley Shaft Indicator	Standard
Rodent Screen	None
Service Factor	1.15
Shaft Diameter	1.625 IN
Shaft Extension Location	Pulley End
Shaft Ground Indicator	No Shaft Grounding
Shaft Rotation	Reversible
Shaft Slinger Indicator	No Slinger
Speed	3510 rpm
Speed Code	Single Speed
Starting Method	Direct on line
Thermal Device - Bearing	None
Thermal Device - Winding	None
Vibration Sensor Indicator	No Vibration Sensor



Winding Thermal 1	None
Winding Thermal 2	None

Nameplate

NP3554LUA											
CAT.NO.	EM2514T			P/N						ENCL	OPSE
SPEC.	39K057X101G1		CC	010A		FRAME	254T		SER.NO.		
HP	20			CLASS		F	HZ	60			
RPM	3510			PH	3		DES	A			
VOLTS	230/460			CODE		G		ODE BRG	6208	DE BRG	6309
AMPS	47/23.5										
RATING	40C AMB-CONT			NEMA-NOM-EFF				91	GREASE	POLYREX EM	
PF	88	SER.F.	1.15		CT30-60(2:1) VT3-60(20:1)						
USABLE AT	50HZ 20HP 190/380V 56/28A				SF 1.0						
HTR-VOLTS	HTR-AMPS	MAX. SPACE HEATER TEMP.									

Accessories

Part number	Description	Multiplier
39-3400	C FACE KIT	A8

AC Induction Motor Performance Data

Record # 13049

Typical performance - not guaranteed values

Winding: 39WGX101-R004			Type: 3928M		Enclosure: OPSB		
Nameplate Data			460 V, 60 Hz: High Voltage Connection				
Rated Output (HP)		20	Full Load Torque		29.6 LB-FT		
Volts		230/460	Start Configuration		direct on line		
Full Load Amps		47/23.5	Breakdown Torque		111 LB-FT		
R.P.M.		3510	Pull-up Torque		36.1 LB-FT		
Hz	60	Phase	3	Locked-rotor Torque		50.6 LB-FT	
NEMA Design Code		B	KVA Code	G	Starting Current		153 A
Service Factor (S.F.)		1.15		No-load Current		8.61 A	
NEMA Nom. Eff.		91	Power Factor	88	Line-line Res. @ 25°C		0.512 Ω
Rating - Duty		40C AMB-CONT		Temp. Rise @ Rated Load		44°C	
S.F. Amps				Temp. Rise @ S.F. Load		54°C	
				Locked-rotor Power Factor		30	
				Rotor inertia		0.715 lb-ft²	

Load Characteristics 460 V, 60 Hz, 20 HP

% of Rated Load	25	50	75	100	125	150	S.F.
Power Factor	52	74	83	87	89	89	88
Efficiency	84.7	90.1	91.2	91	90.1	89.1	90.5
Speed	3581	3563	3544	3522	3496	3472	3506
Line amperes	10.2	13.9	18.1	23.3	29.1	35	26.78


ABB Motors and Mechanical Inc.


WINDING # 39WGX101

Typical performance - not guaranteed values.


20 HP 3 PH 60 HZ 3510 RPM 460 V 3928M

TORQUES (LB-FT): PO=111 PU=36.1 LR=50.6 LRA=153







CD0180



LOW VOLTAGE
(2D)



HIGH VOLTAGE
(1D)



NOTES:

1. INTERCHANGE ANY TWO LINE LEADS TO REVERSE ROTATION.
2. OPTIONAL THERMOSTATS ARE PROVIDED WHEN SPECIFIED.
3. ACTUAL NUMBER OF INTERNAL PARALLEL CIRCUITS MAY BE A MULTIPLE OF THOSE SHOWN ABOVE.
4. LEAD COLORS ARE OPTIONAL. LEADS MUST ALWAYS BE NUMBERED AS SHOWN.

REV. DESC: ADD CLASS CONN00000007

REV. LTR: D

VERSION: 01

TDR: 000001099922

FILE: \AAA\00005\148

REVISED: 10: 25: 29 02/19/2019

BY: ENBRIRO

MTL: -



BALDOR - RELIANCE®

3PH, DV, 9 LEADS, DELTA CONNECTION

SH 1 of 1

CD0180