

ABB BALDOR RELIANCE III

Customer information packet

EM2542T-8

50HP, 3525RPM, 3PH, 60HZ, 324TS, 4058M, OPSB, F

Specifications

Enclosure	OPSB
Frame	324TS
Frame Material	Steel
Frequency	60.00 Hz
Motor Letter Type	Three Phase
Output @ Frequency	50.000 HP @ 60 HZ
Phase	3
Synchronous Speed @ Frequency	3600 RPM @ 60 HZ
Voltage @ Frequency	200.0 V @ 60 HZ
Agency Approvals	CURUSEEV
	NEMA PREMIUM
	NEMA PREMIUM (OLD LOGO)
Ambient Temperature	40 °C
Auxiliary Box	NO AUXILLARY BOX
Auxiliary Box Lead Termination	None
Base Indicator	Rigid
Bearing Grease Type	Polyrex EM (-20F +300F)
Blower	None
Current @ Voltage	129.000 A @ 200.0 V
Design Code	A
Drip Cover	No Drip Cover
Duty Rating	CONT
Efficiency @ 100% Load	93.0 %
Electrically Isolated Bearing	Not Electrically Isolated
Feedback Device	NO FEEDBACK
Front Face Code	Standard
Front Shaft Indicator	None
Heater Indicator	No Heater
High Voltage Full Load Amps	129.0 a
Insulation Class	F
Inverter Code	Inverter Ready
IP Rating	NONE

Part Detail

Revision	K
Type	AC
Mech. spec.	40E213
Base	
Status	PRD/A
Elec. spec.	40WGX311
Layout	40LYE213
Eff. date	06-27-2024
CD Diagram	CD0695
Poles	02
Leads	6#6
Proprietary	False
Created date	08-12-2015

KVA Code	G
Lifting Lugs	Standard Lifting Lugs
Locked Bearing Indicator	No Locked Bearing
Motor Lead Exit	Ko Box
Motor Lead Quantity/Wire Size	6 @ 6 AWG
Motor Lead Termination	Flying Leads
Motor Standards	NEMA
Motor Type	4058M
Mounting Arrangement	F1
Number of Poles	2
Overall Length	25.69 IN
Power Factor	90
Product Family	General Purpose
Pulley End Bearing Type	Ball
Pulley Face Code	Standard
Pulley Shaft Indicator	Standard
Rodent Screen	None
Service Factor	1.15
Shaft Diameter	1.875 IN
Shaft Extension Location	Pulley End
Shaft Ground Indicator	No Shaft Grounding
Shaft Rotation	Reversible
Shaft Slinger Indicator	No Slinger
Speed	3525 rpm
Speed Code	Single Speed
Starting Method	Part Winding
Thermal Device - Bearing	None
Thermal Device - Winding	None
Vibration Sensor Indicator	No Vibration Sensor
Winding Thermal 1	None
Winding Thermal 2	None

Nameplate

NP3554L														
CAT.NO.	EM2542T-8				P/N				ENCL				OPSB	
SPEC.	40E213X311		CC	010A		FRAME		324TS		SER.NO.				
HP	50			CLASS		F		HZ		60				
RPM	3525			PH	3		DES		A					
VOLTS	200				CODE		G		ODE BRG		6309	DE BRG		6312
AMPS	129													
RATING	40C AMB-CONT			NEMA-NOM-EFF				93		GREASE		POLYREX EM		
PF	90		SER.F.	1.15		VPWM INVERTER READY								
HTR-VOLTS	HTR-AMPS		MAX. SPACE HEATER TEMP.											

AC Induction Motor Performance Data

Record # 52219

Typical performance - not guaranteed values

Winding: 40WGX311-R001			Type: 4058M		Enclosure: OPSB			
Nameplate Data			200 V, 60 Hz: Single Voltage Motor					
Rated Output (HP)		50	Full Load Torque		74.7 LB-FT			
Volts		200	Start Configuration		direct on line			
Full Load Amps		129	Breakdown Torque		174 LB-FT			
R.P.M.		3525	Pull-up Torque		119 LB-FT			
Hz	60	Phase	3	Locked-rotor Torque		139 LB-FT		
NEMA Design Code		A	KVA Code	G	Starting Current		892 A	
Service Factor (S.F.)		1.15	No-load Current		34.3 A			
NEMA Nom. Eff.		93	Power Factor		90	Line-line Res. @ 25°C		0.0243 Ω
Rating - Duty		40C	AMB-CONT		Temp. Rise @ Rated Load		46°C	
S.F. Amps					Temp. Rise @ S.F. Load		57°C	
					Locked-rotor Power Factor		23	
					Rotor inertia		2.49 LB-FT2	

Load Characteristics 200 V, 60 Hz, 50 HP

% of Rated Load	25	50	75	100	125	150	S.F.
Power Factor	63	82	88	90	90	90	90
Efficiency	92.5	94.5	94.2	93.4	92.2	90.5	92.7
Speed	3582	3566	3547	3529	3508	3479	3516
Line amperes	46.8	70	98.2	129	162	205	149


ABB Motors and Mechanical Inc.


WINDING # 40WGX311

Typical performance - not guaranteed values.



50 HP 3 PH 60 HZ 3525 RPM 200 V 4058M

TORQUES (LB-FT): PO=174 PU=119 LR=139 LRA=892







CD0695



START CONNECTION



RUN CONNECTION



NOTES:

1. MOTOR MAY BE WYE CONNECTED OR DELTA CONNECTED.
2. INTERCHANGE ANY TWO LINE LEADS TO REVERSE ROTATION.
3. OPTIONAL THERMOSTATS ARE PROVIDED WHEN SPECIFIED.
4. ACTUAL NUMBER OF INTERNAL PARALLEL CIRCUITS MAY VARY.
5. LEAD COLORS ARE OPTIONAL. LEADS MUST ALWAYS BE NUMBERED AS SHOWN.

REV. DESC: REVISE TO SHOW OPTIONAL COLORS

REV. LTR: C

BY: JLP

REVISED: 01/21/99 3:19

TDR: 0171435

S69000

FILE: AAA00005151

MDL: -

MTL: -

BALDOR ELECTRIC Co.

3PH, SV, 6 LEADS, PART WINDING START

CD0695