

ABB BALDOR RELIANCE III

Customer information packet

EM3116-57

1/.75KWHP, 1470RPM, 3PH, 50HZ, 56, 3520M, OPEN

Class - None

Division - Not Applicable

Specifications

Enclosure	OPEN
Frame	56
Frame Material	Steel
Frequency	50.00 Hz
Haz Area Class and Group	None
Haz Area Division	Not Applicable
Motor Letter Type	Three Phase
Output @ Frequency	1.000 HP @ 50 HZ
Phase	3
Synchronous Speed @ Frequency	1500 RPM @ 50 HZ
Voltage @ Frequency	400.0 V @ 50 HZ 230.0 V @ 50 HZ
Agency Approvals	C UR US CE CURUS IE3 UKCA WEEE
Ambient Temperature	40 °C
Auxiliary Box	NO AUXILLARY BOX
Auxiliary Box Lead Termination	None
Base Indicator	Rigid
Bearing Grease Type	Polyrex EM (-20F +300F)
Blower	None
Current @ Voltage	3.450 A @ 230.0 V 2.000 A @ 400.0 V
Design Code	B
Drip Cover	No Drip Cover
Duty Rating	CONT
Efficiency @ 100% Load	82.5 %
Electrically Isolated Bearing	Not Electrically Isolated
Feedback Device	NO FEEDBACK

Part Detail

Revision	E
Type	AC
Mech. spec.	35B011
Base	
Status	PRD/A
Elec. spec.	35WGZ921
Layout	35LYB011
Eff. date	07-01-2024
CD Diagram	CD0022
Poles	04
Leads	6#18
Proprietary	False
Created date	03-11-2022

Front Shaft Indicator	None
Heater Indicator	No Heater
High Voltage Full Load Amps	2.0 a
Insulation Class	F
Inverter Code	Not Inverter
IP Rating	NONE
KVA Code	N
Lifting Lugs	No Lifting Lugs
Locked Bearing Indicator	No Locked Bearing
Motor Lead Quantity/Wire Size	6 @ 18 AWG
Motor Lead Termination	Flying Leads
Motor Standards	NEMA
Motor Type	3520M
Mounting Arrangement	F1
Number of Poles	4
Overall Length	11.07 IN
Power Factor	65
Product Family	General Purpose
Pulley End Bearing Type	Ball
Pulley Face Code	Standard
Pulley Shaft Indicator	Standard
Rodent Screen	None
Service Factor	1.15
Shaft Diameter	0.625 IN
Shaft Ground Indicator	No Shaft Grounding
Shaft Rotation	Reversible
Shaft Slinger Indicator	No Slinger
Speed	1470 rpm
Speed Code	Single Speed
Starting Method	Direct on line
Thermal Device - Bearing	None
Thermal Device - Winding	None
Vibration Sensor Indicator	No Vibration Sensor
Winding Thermal 1	None

Winding Thermal 2

None

Nameplate

NP2716L									
CAT NO	EM3116-57								
SPEC.	35B011Z921G1								
HP	1/.75KW					PH	3		
VOLTS	230/400								
AMP	3.45/2								
R.P.M. (1/MIN)	1470								
FRAME	56		HZ	50		I.P.		23	
SER.F.	1.15	CODE	N	DES	B	CL		F	
NOM.EFF.	82.5		% (100%)						
PF	65								
RATING	40C AMB-S1 CONT				CC				
DE BRG	6205		ODE	6203					
ENCL	OPEN	SN							
BLANK	SFA 3.7/2.15								
	IC01 15KG								

AC Induction Motor Performance Data

Record # 88663

Typical performance - not guaranteed values

Winding: 35WGZ921-R002			Type: 3520M		Enclosure: OPEN	
Nameplate Data			400 V, 50 Hz: High Voltage Connection			
Rated Output (HP)		1	Full Load Torque			3.56 LB-FT
Volts		230/400	Start Configuration			direct on line
Full Load Amps		3.45/2	Breakdown Torque			17.3 LB-FT
R.P.M.		1470	Pull-up Torque			11 LB-FT
Hz	50	Phase	Locked-rotor Torque			12.7 LB-FT
NEMA Design Code	B	KVA Code	Starting Current			18.2 A
Service Factor (S.F.)		1.15	No-load Current			1.65 A
NEMA Nom. Eff.	82.5	Power Factor	Line-line Res. @ 25°C			13.5 Ω
Rating - Duty		40C AMB-CONT	Temp. Rise @ Rated Load			32°C
S.F. Amps		3.7/2.15	Temp. Rise @ S.F. Load			36°C
			Locked-rotor Power Factor			68
			Rotor inertia			0.144 lb-ft²

Load Characteristics 400 V, 50 Hz, 1 HP

% of Rated Load	25	50	75	100	125	150	S.F.
Power Factor	26	40	53	62	70	75	68
Efficiency	62.7	75.6	80.6	82.5	83.1	82.9	82.6
Speed	1494	1488	1483	1477	1470	1463	1467
Line amperes	1.67	1.77	1.9	2.09	2.32	2.59	2.18

ABB Motors and Mechanical Inc.

WINDING # 35WGZ921

Typical performance - not guaranteed values.

1 HP 3 PH 50 HZ 1470 RPM 400 V 3520M

TORQUES (LB-FT): PO=17.3 PU=11 LR=12.7 LRA=18.2





