

ABB BALDOR RELIANCE III

Customer information packet

EM3215T-G

2HP, 1165RPM, 3PH, 60HZ, 184T, 3636M, OPSB, F1

Class - None

Division - Not Applicable

Specifications

Enclosure	OPSB
Frame	184T
Frame Material	Steel
Frequency	60.00 Hz
Haz Area Class and Group	None
Haz Area Division	Not Applicable
Motor Letter Type	Three Phase
Output @ Frequency	2.000 HP @ 60 HZ
Phase	3
Synchronous Speed @ Frequency	1200 RPM @ 60 HZ
Voltage @ Frequency	460.0 V @ 60 HZ 230.0 V @ 60 HZ
Agency Approvals	CSA CSA EEV UR
Ambient Temperature	40 °C
Auxiliary Box	NO AUXILLARY BOX
Auxiliary Box Lead Termination	None
Base Indicator	Rigid
Bearing Grease Type	Polyrex EM (-20F +300F)
Blower	None
Current @ Voltage	6.800 A @ 208.0 V 6.800 A @ 230.0 V 3.400 A @ 460.0 V
Design Code	B
Drip Cover	No Drip Cover
Duty Rating	CONT
Efficiency @ 100% Load	87.5 %
Electrically Isolated Bearing	Not Electrically Isolated
Feedback Device	NO FEEDBACK
Front Face Code	Standard
Front Shaft Indicator	None

Part Detail

Revision	T
Type	AC
Mech. spec.	36M526
Base	
Status	PRD/A
Elec. spec.	36WGS947
Layout	36LYM526
Eff. date	03-13-2026
CD Diagram	CD0005
Poles	06
Leads	9#16
Proprietary	False
Created date	07-03-2012

Heater Indicator	No Heater
High Voltage Full Load Amps	3.4 a
Insulation Class	H
Inverter Code	Inverter Ready
KVA Code	L
Lifting Lugs	No Lifting Lugs
Locked Bearing Indicator	Locked Bearing
Motor Lead Exit	Ko Box
Motor Lead Quantity/Wire Size	9 @ 16 AWG
Motor Lead Termination	Flying Leads
Motor Standards	NEMA
Motor Type	3636M
Mounting Arrangement	F1
Number of Poles	6
Overall Length	16.50 IN
Power Factor	63
Product Family	General Purpose
Pulley End Bearing Type	Ball
Pulley Face Code	Standard
Pulley Shaft Indicator	Standard
Rodent Screen	None
Service Factor	1.15
Shaft Diameter	1.125 IN
Shaft Extension Location	Pulley End
Shaft Ground Indicator	Shaft Grounding
Shaft Rotation	Reversible
Shaft Slinger Indicator	No Slinger
Speed	1165 rpm
Speed Code	Single Speed
Starting Method	Direct on line
Thermal Device - Bearing	None
Thermal Device - Winding	None
Vibration Sensor Indicator	No Vibration Sensor
Winding Thermal 1	None

Winding Thermal 2

None

Nameplate

NP1259L											
CAT.NO.	EM3215T-G										
SPEC.	36M526S947G1										
HP	2										
VOLTS	230/460										
AMP	6.8/3.4										
RPM	1165										
FRAME	184T		HZ	60				PH	3		
SER.F.	1.15	CODE	L	DES	B	CL	H				
NEMA-NOM-EFF	87.5	PF	63								
RATING	40C AMB-CONT										
CC	010A										
DE	6206		ODE	6205							
ENCL	OPSB	SN									

AC Induction Motor Performance Data

Record # 39004

Typical performance - not guaranteed values

Winding: 36WGS947-R002			Type: 3636M		Enclosure: OPSB			
Nameplate Data			460 V, 60 Hz: High Voltage Connection					
Rated Output (HP)		2	Full Load Torque		9.01 LB-FT			
Volts		230/460	Start Configuration		direct on line			
Full Load Amps		6.8/3.4	Breakdown Torque		35.3 LB-FT			
R.P.M.		1165	Pull-up Torque		19.7 LB-FT			
Hz	60	Phase	3	Locked-rotor Torque		25.1 LB-FT		
NEMA Design Code		B	KVA Code	L	Starting Current		23.9 A	
Service Factor (S.F.)		1.15	No-load Current		2.26 A			
NEMA Nom. Eff.		87.5	Power Factor		63	Line-line Res. @ 25°C		4.9075 Ω
Rating - Duty		40C	AMB-CONT		Temp. Rise @ Rated Load		24°C	
S.F. Amps					Temp. Rise @ S.F. Load		28°C	

Load Characteristics 460 V, 60 Hz, 2 HP

% of Rated Load	25	50	75	100	125	150	S.F.
Power Factor	27	43	55	62	68	72	66
Efficiency	77.9	85.5	87.6	88	87.6	86.8	87.8
Speed	1193.3	1187	1180.2	1173.2	1165.2	1155.9	1168
Line amperes	2.37	2.62	2.99	3.43	3.96	4.54	3.75

ABB Motors and Mechanical Inc.

WINDING # 36WGS947

Typical performance - not guaranteed values.

2 HP 3 PH 60 HZ 1165 RPM 460 V 3636M

TORQUES (LB-FT): PO=35.3 PU=19.7 LR=25.1 LRA=23.9





