

ABB BALDOR RELIANCE III

Customer information packet

EM3312T

10HP, 3485RPM, 3PH, 60HZ, 213T, 3728M, OPSB, F1

Class - None

Division - Not Applicable

Specifications

Enclosure	OPSB
Frame	213T
Frame Material	Steel
Frequency	60.00 Hz
Haz Area Class and Group	None
Haz Area Division	Not Applicable
Motor Letter Type	Three Phase
Output @ Frequency	10.000 HP @ 60 HZ
Phase	3
Synchronous Speed @ Frequency	3600 RPM @ 60 HZ
Voltage @ Frequency	230.0 V @ 60 HZ 460.0 V @ 60 HZ
Agency Approvals	CURUSEEV NEMA PREMIUM
Ambient Temperature	40 °C
Auxiliary Box	NO AUXILLARY BOX
Auxiliary Box Lead Termination	None
Base Indicator	Rigid
Bearing Grease Type	Polyrex EM (-20F +300F)
Blower	None
Current @ Voltage	24.000 A @ 230.0 V 12.000 A @ 460.0 V
Design Code	B
Drip Cover	No Drip Cover
Duty Rating	CONT
Efficiency @ 100% Load	90.2 %
Electrically Isolated Bearing	Not Electrically Isolated
Feedback Device	NO FEEDBACK
Front Shaft Indicator	None
Heater Indicator	No Heater
High Voltage Full Load Amps	12.0 a
Insulation Class	F

Part Detail

Revision	D
Type	AC
Mech. spec.	37F614
Base	
Status	PRD/A
Elec. spec.	37WGL967
Layout	37LYF614
Eff. date	01-22-2026
CD Diagram	CD0005
Poles	02
Leads	9#14
Proprietary	False
Created date	06-28-2023

Inverter Code	Inverter Ready
KVA Code	G
Lifting Lugs	Standard Lifting Lugs
Locked Bearing Indicator	No Locked Bearing
Motor Lead Quantity/Wire Size	9 @ 14 AWG
Motor Lead Termination	Flying Leads
Motor Standards	NEMA
Motor Type	3728M
Mounting Arrangement	F1
Number of Poles	2
Overall Length	16.32 IN
Power Factor	87
Product Family	General Purpose
Pulley End Bearing Type	Ball
Pulley Face Code	Standard
Pulley Shaft Indicator	Standard
Rodent Screen	None
Service Factor	1.15
Shaft Diameter	1.375 IN
Shaft Ground Indicator	No Shaft Grounding
Shaft Rotation	Reversible
Shaft Slinger Indicator	No Slinger
Speed	3485 rpm
Speed Code	Single Speed
Starting Method	Direct on line
Thermal Device - Bearing	None
Thermal Device - Winding	None
Vibration Sensor Indicator	No Vibration Sensor
Winding Thermal 1	None
Winding Thermal 2	None

Nameplate

NP3553LUA									
CAT.NO.	EM3312T								
SPEC.	37F614L967G1								
HP	10								
VOLTS	230/460								
AMPS	24/12								
RPM	3485								
FRAME	213T		HZ	60		PH	3		
SF	1.15	CODE	G	DES	B	CLASS	F		
NEMA NOM. EFF	90.2	PF	87						
RATING	40C AMB-CONT								
CC	010A								
ENCL	OPSB	SN							
DE	6307		ODE	6206					
VPWM INVERTER READY									
CT30-60(2:1) VT3-60(20:1)									
USABLE AT	50HZ 10HP 190/380V 28.4/14.2A						SF1.0		

Accessories

Part number	Description	Multiplier
37-1404	C FACE KIT	A8

AC Induction Motor Performance Data

Record # 101969

Typical performance - not guaranteed values

Winding: 37WGL967-R001			Type: 3728M	Enclosure: OPSB	
Nameplate Data			460 V, 60 Hz: High Voltage Connection		
Rated Output (HP)		10	Full Load Torque		15.16 LB-FT
Volts		230/460	Start Configuration		direct on line
Full Load Amps		24/12	Breakdown Torque		58 LB-FT
R.P.M.		3485	Pull-up Torque		18.2 LB-FT
Hz	60	Phase	3	Locked-rotor Torque	26.8 LB-FT
NEMA Design Code	B	KVA Code	G	Starting Current	73.6 A
Service Factor (S.F.)		1.15	No-load Current		3.99 A
NEMA Nom. Eff.	90.2	Power Factor	87	Line-line Res. @ 25°C	1.0211 Ω
Rating - Duty		40C AMB-CONT	Temp. Rise @ Rated Load		34°C
S.F. Amps			Temp. Rise @ S.F. Load		44°C
			Locked-rotor Power Factor		34.9
			Rotor inertia		0.255 lb-ft²

Load Characteristics 460 V, 60 Hz, 10 HP

% of Rated Load	25	50	75	100	125	150	S.F.
Power Factor	55	76	84	87	88	88	88
Efficiency	89.4	91.7	91.8	90.9	89.3	87.7	89.9
Speed	3569.9	3528.3	3508.4	3481	3443.8	3410.2	3459
Line amperes	4.89	6.8	9.19	11.9	14.9	18.2	13.7

ABB Motors and Mechanical Inc.

WINDING # 37WGL967

Typical performance - not guaranteed values.

10 HP 3 PH 60 HZ 3485 RPM 460 V 3728M

TORQUES (LB-FT): PO=58 PU=18.2 LR=26.8 LRA=73.6





