

ABB BALDOR RELIANCE III

Customer information packet

EM3660T-G

3HP, 3470RPM, 3PH, 60HZ, 182T, TEFC, F1

Class - None

Division - Not Applicable

Specifications

Enclosure	TEFC
Frame	182T
Frame Material	Iron
Frequency	60.00 Hz
Haz Area Class and Group	None
Haz Area Division	Not Applicable
Motor Letter Type	Three Phase
Output @ Frequency	3.000 HP @ 60 HZ
Phase	3
Synchronous Speed @ Frequency	3600 RPM @ 60 HZ
Voltage @ Frequency	460.0 V @ 60 HZ 230.0 V @ 60 HZ
Agency Approvals	CSA CSA EEV NEMA PREMIUM UR
Ambient Temperature	40 °C
Auxiliary Box	NO AUXILLARY BOX
Auxiliary Box Lead Termination	None
Base Indicator	Rigid
Bearing Grease Type	Polyrex EM (-20F +300F)
Blower	None
Current @ Voltage	8.200 A @ 208.0 V 7.600 A @ 230.0 V 3.800 A @ 460.0 V
Design Code	B
Drip Cover	No Drip Cover
Duty Rating	CONT
Efficiency @ 100% Load	86.5 %
Electrically Isolated Bearing	Not Electrically Isolated
Feedback Device	NO FEEDBACK
Heater Indicator	No Heater

Part Detail

Revision	C
Type	AC
Mech. spec.	
Base	
Status	PRD/A
Elec. spec.	06WGY471
Layout	06LYG729
Eff. date	04-29-2024
CD Diagram	CD0005
Poles	02
Leads	9#16
Proprietary	False
Created date	04-09-2019

High Voltage Full Load Amps	3.8 a
Insulation Class	H
Inverter Code	Inverter Ready
IP Rating	NONE
KVA Code	K
Lifting Lugs	Standard Lifting Lugs
Locked Bearing Indicator	Locked Bearing
Motor Lead Termination	Flying Leads
Motor Standards	NEMA
Motor Type	0618M
Mounting Arrangement	F1
Number of Poles	2
Overall Length	15.23 IN
Power Factor	89
Product Family	General Purpose
Pulley Face Code	Standard
Rodent Screen	None
Service Factor	1.15
Shaft Diameter	1.125 IN
Shaft Ground Indicator	Shaft Grounding
Shaft Rotation	Reversible
Speed	3470 rpm
Speed Code	Single Speed
Starting Method	Direct on line
Thermal Device - Winding	None
Vibration Sensor Indicator	No Vibration Sensor
Winding Thermal 1	None
Winding Thermal 2	None

Nameplate

NP3441LUA									
CAT.NO.	EM3660T-G								
SPEC	06-0000-0083								
HP	3								
VOLTS	230/460								
AMPS	7.6/3.8								
RPM	3470								
FRAME	182T		HZ	60		PH	3		
SF	1.15	CODE	K	DES	B	CLASS	H		
NEMA NOM. EFF	86.5	PF	89						
RATING	40C AMB-CONT								
CC	010A								
ENCL	TEFC	SER							
DE	6206		ODE	6205					
VPWM INVERTER READY									
CT6-60H(10:1)VT3-60H(20:1									
50HZ 3HP 190/380V 9/4.5A									SF1.0

AC Induction Motor Performance Data

Record # 75470

Typical performance - not guaranteed values

Winding: 06WGY471-R006			Type: 0618M	Enclosure: TEFC	
Nameplate Data			460 V, 60 Hz: High Voltage Connection		
Rated Output (HP)		3	Full Load Torque		4.51 LB-FT
Volts		230/460	Start Configuration		direct on line
Full Load Amps		7.6/3.8	Breakdown Torque		25.5 LB-FT
R.P.M.		3470	Pull-up Torque		9.08 LB-FT
Hz	60	Phase	Locked-rotor Torque		11.9 LB-FT
NEMA Design Code	B	KVA Code	Starting Current		29.3 A
Service Factor (S.F.)		1.15	No-load Current		1.64 A
NEMA Nom. Eff.	86.5	Power Factor	Line-line Res. @ 25°C		6.24 Ω
Rating - Duty		40C AMB-CONT	Temp. Rise @ Rated Load		45°C
S.F. Amps			Temp. Rise @ S.F. Load		56°C
			Locked-rotor Power Factor		59.2
			Rotor inertia		0.0795 LB-FT2

Load Characteristics 460 V, 60 Hz, 3 HP

% of Rated Load	25	50	75	100	125	150	S.F.
Power Factor	47	70	81	87	90	91	89
Efficiency	81.1	86.6	87.4	86.6	85.2	83.1	85.8
Speed	3568	3538	3505	3468	3430	3382	3445
Line amperes	1.82	2.29	2.94	3.71	4.53	5.5	4.2


ABB Motors and Mechanical Inc.


WINDING # 06WGY471

Typical performance - not guaranteed values.


3 HP 3 PH 60 HZ 3470 RPM 460 V 0618M

TORQUES (LB-FT): PO=25.5 PU=9.08 LR=11.9 LRA=29.3






CD0005




LOW VOLTAGE
(2Y)



LINE

HIGH VOLTAGE
(1Y)



LINE

NOTES:

1. INTERCHANGE ANY TWO LINE LEADS TO REVERSE ROTATION.
2. OPTIONAL THERMOSTATS ARE PROVIDED WHEN SPECIFIED.
3. ACTUAL NUMBER OF INTERNAL PARALLEL CIRCUITS MAY BE A MULTIPLE OF THOSE SHOWN ABOVE.
4. LEAD COLORS ARE OPTIONAL. LEADS MUST ALWAYS BE NUMBERED AS SHOWN.

REV. DESC: REVISE TO SHOW OPTIONAL COLORS

REV. LTR: E BY: JLP REVISED: 01/19/99 10:15 TDR: 0171435

900000

FILE: AAA00005140

MDL: -

MTL: -

BALDOR ELECTRIC Co.

3PH, DV, 9 LEADS

CD0005