

ABB BALDOR RELIANCE III

Customer information packet

EWDM23932T

10HP, 1180RPM, 3PH, 60HZ, 256T, TEFC, F1

Class - None

Division - Not Applicable

Specifications

Enclosure	TEFC
Frame	256T
Frame Material	Steel
Frequency	60.00 Hz
Haz Area Class and Group	None
Haz Area Division	Not Applicable
Motor Letter Type	Three Phase
Output @ Frequency	10.000 HP @ 60 HZ
Phase	3
Synchronous Speed @ Frequency	1200 RPM @ 60 HZ
Voltage @ Frequency	230.0 V @ 60 HZ 460.0 V @ 60 HZ
Agency Approvals	CSA EEV NEMA PREMIUM UR
Ambient Temperature	40 °C
Auxiliary Box	NO AUXILLARY BOX
Auxiliary Box Lead Termination	None
Base Indicator	Rigid
Bearing Grease Type	Polyrex EM (-20F +300F)
Blower	None
Current @ Voltage	30.600 A @ 208.0 V 29.400 A @ 230.0 V 14.700 A @ 460.0 V
Design Code	A
Drip Cover	No Drip Cover
Duty Rating	CONT
Efficiency @ 100% Load	91.0 %
Electrically Isolated Bearing	Not Electrically Isolated
Feedback Device	NO FEEDBACK
Heater Indicator	No Heater
High Voltage Full Load Amps	14.7 a

Part Detail

Revision	H
Type	AC
Mech. spec.	
Base	
Status	PRD/A
Elec. spec.	39WGX611
Layout	39LYS015
Eff. date	02-14-2024
CD Diagram	CD0005
Poles	06
Leads	9#12
Proprietary	False
Created date	08-13-2019

Insulation Class	F
Inverter Code	Inverter Duty
IP Rating	IP55
KVA Code	J
Lifting Lugs	Standard Lifting Lugs
Locked Bearing Indicator	Locked Bearing
Max Speed	1800 rpm
Motor Lead Termination	Flying Leads
Motor Standards	NEMA
Motor Type	3956M
Mounting Arrangement	F1
Number of Poles	6
Overall Length	24.57 IN
Power Factor	70
Product Family	Wash Down
Pulley Face Code	Standard
Rodent Screen	None
Service Factor	1.00
Shaft Diameter	1.625 IN
Shaft Ground Indicator	No Shaft Grounding
Shaft Rotation	Reversible
Speed	1180 rpm
Speed Code	Single Speed
Starting Method	Direct on line
Thermal Device - Bearing	None
Thermal Device - Winding	None
Vibration Sensor Indicator	No Vibration Sensor
Winding Thermal 1	None
Winding Thermal 2	None

Nameplate

NP1669L									
CAT.NO.	EWDM23932T								
SPEC.	39-0000-0186								
HP	10								
VOLTS	230/460								
AMP	29.4/14.7								
RPM	1180								
FRAME	256T		HZ	60			PH	3	
SER.F.	1.00	CODE	J	DES	A	CLASS		F	
NEMA-NOM-EFF	91	PF	70						
RATING	40C AMB-CONT								
CC	010A								
DE	6309		ODE	6208					
ENCL	TEFC	SN							
BLANK	20:1 CT/VT								

AC Induction Motor Performance Data

Record # 78156

Typical performance - not guaranteed values

Winding: 39WGX611-R004			Type: 3956M		Enclosure: TEFC		
Nameplate Data			460 V, 60 Hz: High Voltage Connection				
Rated Output (HP)		10	Full Load Torque		44.4 LB-FT		
Volts		230/460	Start Configuration		direct on line		
Full Load Amps		29.4/14.7	Breakdown Torque		146 LB-FT		
R.P.M.		1180	Pull-up Torque		53.5 LB-FT		
Hz	60	Phase	3	Locked-rotor Torque		73.4 LB-FT	
NEMA Design Code		A	KVA Code	J	Starting Current		95.1 A
Service Factor (S.F.)			1	No-load Current		7.85 A	
NEMA Nom. Eff.		91	Power Factor	70	Line-line Res. @ 25°C		0.66 Ω
Rating - Duty		40C AMB-CONT		Temp. Rise @ Rated Load		45°C	
				Locked-rotor Power Factor		24.2	
				Rotor inertia		4.5 LB-FT2	

Load Characteristics 460 V, 60 Hz, 10 HP

% of Rated Load	25	50	75	100	125	150
Power Factor	32	52	63	70	72	73
Efficiency	84.1	90	91.5	91.7	91.2	90.4
Speed	1196	1191	1186	1182	1176	1169
Line amperes	8.68	10	12.2	14.6	17.6	21

ABB Motors and Mechanical Inc.

WINDING # 39WGX611

Typical performance - not guaranteed values.

10 HP 3 PH 60 HZ 1180 RPM 460 V 3956M

TORQUES (LB-FT): PO=146 PU=53.5 LR=73.4 LRA=95.1





