

ABB BALDOR RELIANCE III

Customer information packet

GNEM2513T-G

15HP//11KW, 1770//1470 1/MINRPM, 3PH, 60//5

Class - None

Division - Not Applicable

Specifications

Enclosure	OPSB
Frame	254T
Frame Material	Steel
Frequency	50.00 Hz 60.00 Hz
Haz Area Class and Group	None
Haz Area Division	Not Applicable
Motor Letter Type	Three Phase
Output @ Frequency	15.000 HP @ 60 HZ 11.000 KW @ 50 HZ
Phase	3
Synchronous Speed @ Frequency	1800 RPM @ 60 HZ
Voltage @ Frequency	208.0 V @ 60 HZ 190.0 V @ 50 HZ 230.0 V @ 60 HZ 380.0 V @ 50 HZ 460.0 V @ 60 HZ
Agency Approvals	WEEE UKCA NEMA_PREMIUM NEMA PREMIUM IE3 CURUS CE
Ambient Temperature	40 °C
Auxiliary Box	NO AUXILLARY BOX
Auxiliary Box Lead Termination	None
Base Indicator	Rigid
Bearing Grease Type	Polyrex EM (-20F +300F)
Blower	None
Current @ Voltage	44.000 A @ 190.0 V 40.000 A @ 208.0 V

Part Detail

Revision	J
Type	AC
Mech. spec.	39E366
Base	
Status	PRD/A
Elec. spec.	39WGX952
Layout	39LYE366
Eff. date	02-11-2026
CD Diagram	CD0180
Poles	04
Leads	9#10
Proprietary	False
Created date	04-12-2023

38.000 A @ 230.0 V

22.000 A @ 380.0 V

19.000 A @ 460.0 V

Design Code	A
Drip Cover	No Drip Cover
Duty Rating	CONT
Efficiency @ 100% Load	93.0 %
Electrically Isolated Bearing	Not Electrically Isolated
Feedback Device	NO FEEDBACK
Front Shaft Indicator	None
Heater Indicator	No Heater
High Voltage Full Load Amps	19.0 a
Insulation Class	H
Inverter Code	Inverter Ready
KVA Code	K
Lifting Lugs	Standard Lifting Lugs
Locked Bearing Indicator	No Locked Bearing
Motor Lead Quantity/Wire Size	9 @ 10 AWG
Motor Lead Termination	Flying Leads
Motor Standards	NEMA
Motor Type	3948M
Mounting Arrangement	F1
Number of Poles	4
Overall Length	23.19 IN
Power Factor	81
Product Family	General Purpose
Pulley End Bearing Type	Ball
Pulley Face Code	Standard
Pulley Shaft Indicator	Standard
Rodent Screen	None
RoHS Status	ROHS COMPLIANT
Service Factor	1.15
Shaft Diameter	1.625 IN
Shaft Ground Indicator	Shaft Grounding

Shaft Rotation	Reversible
Shaft Slinger Indicator	No Slinger
Speed	1470 rpm 1770 rpm
Speed Code	Single Speed
Starting Method	Direct on line
Thermal Device - Bearing	None
Thermal Device - Winding	None
Vibration Sensor Indicator	No Vibration Sensor
Winding Thermal 1	None
Winding Thermal 2	None

Nameplate

NP4304L									
CAT.NO.	GNEM2513T-G								
SPEC.	39E366X952G4								
HP	15HP//11KW					PH	3		
VOLTS	208-230/460//190/380								
AMPS	40-38/19//44/22								
R.P.M. (1/MIN)	1770//1470					WT.	113KG		KG
FRAME	254T		HZ	60//50		I.P.	22		
SER.F.	1.15	CODE	K	DES.	A	CLASS	H		
NOM.EFF.	93//91.5		% (100%)						
P.F.	81	IC01, 10:1 VT							
RATING	40C AMB-CONT				CC	010A			
DE	6309		ODE	6208					
ENCL	OPSB	SN							
	IE3-50HZ 93.1(75%),92.9(50%)								
	IE3-60HZ 93.0(75%),92.0 (50%)								
	SFA 44-42/21//50/25								

AC Induction Motor Performance Data

Record # 102553

Typical performance - not guaranteed values

Winding: 39WGX952-R009				Type: 3948M		Enclosure: OPSB	
Nameplate Data				460 V, 60 Hz: High Voltage Connection			
Rated Output (HP)		15HP//11KW		Full Load Torque		44.39 LB-FT	
Volts		208-230/460//190/380		Start Configuration		direct on line	
Full Load Amps		40-38/19//44/22		Breakdown Torque		176 LB-FT	
R.P.M.		1770//1470		Pull-up Torque		94.8 LB-FT	
Hz	60//50	Phase	3	Locked-rotor Torque		106 LB-FT	
NEMA Design Code		A	KVA Code	K	Starting Current		154 A
Service Factor (S.F.)		1.15		No-load Current		9.37 A	
NEMA Nom. Eff.		93	Power Factor	81	Line-line Res. @ 25°C		0.48293 Ω
Rating - Duty		40C AMB-CONT		Temp. Rise @ Rated Load		25°C	
S.F. Amps		44-42/21//50/25		Temp. Rise @ S.F. Load		30°C	
				Locked-rotor Power Factor		33.2	
				Rotor inertia		2.1 lb-ft²	

Load Characteristics 460 V, 60 Hz, 15 HP

% of Rated Load	25	50	75	100	125	150	S.F.
Power Factor	39	61	73	80	83	85	82
Efficiency	87.3	92	93	93.4	93.1	92.5	93.2
Speed	1794.8	1789.9	1784.6	1778.8	1772.3	1765.4	1775
Line amperes	10.4	12.5	15.5	18.9	22.6	26.8	21.1


ABB Motors and Mechanical Inc.

WINDING # 39WGX952

Typical performance - not guaranteed values.

15 HP 3 PH 60 HZ 1778.8 RPM 460 V 3948M

TORQUES (LB-FT): PO=176 PU=94.8 LR=106 LRA=154



AC Induction Motor Performance Data

Record # 102554

Typical performance - not guaranteed values

Winding: 39WGX952-R009				Type: 3948M		Enclosure: OPSB	
Nameplate Data				380 V, 50 Hz: High Voltage Connection			
Rated Output (HP)		15HP//11KW		Full Load Torque		53.67 LB-FT	
Volts		208-230/460//190/380		Start Configuration		direct on line	
Full Load Amps		40-38/19//44/22		Breakdown Torque		174 LB-FT	
R.P.M.		1770//1470		Pull-up Torque		92.3 LB-FT	
Hz	60//50	Phase	3	Locked-rotor Torque		103 LB-FT	
NEMA Design Code		A	KVA Code	K	Starting Current		150 A
Service Factor (S.F.)		1.15		No-load Current		9.12 A	
NEMA Nom. Eff.		93	Power Factor	81	Line-line Res. @ 25°C		0.47956 Ω
Rating - Duty		40C AMB-CONT		Temp. Rise @ Rated Load		34°C	
S.F. Amps		44-42/21//50/25		Temp. Rise @ S.F. Load		39°C	
				Locked-rotor Power Factor		36.7	
				Rotor inertia		2.1 lb-ft²	

Load Characteristics 380 V, 50 Hz, 15 HP

% of Rated Load	25	50	75	100	125	150	S.F.
Power Factor	45	68	79	83	85	86	84
Efficiency	89.5	92.8	93.1	92.5	92	91.6	92.2
Speed	1493.4	1486.4	1478.9	1470.8	1465.3	1461.5	1468
Line amperes	10.5	13.5	17.5	22	25	27.1	23.8


ABB Motors and Mechanical Inc.

WINDING # 39WGX952

Typical performance - not guaranteed values.

15 HP 3 PH 50 HZ 1470.8 RPM 380 V 3948M

TORQUES (LB-FT): PO=174 PU=92.3 LR=103 LRA=150



10/6/2026 ACPERF, record # 102554

