

ABB BALDOR RELIANCE III

Customer information packet

GNEM3614T-G

2HP//1.5KW, 1175//970RPM, 3PH, 60//50HZ, 184

Class - None

Division - Not Applicable

Specifications

Enclosure	TEFC
Frame	184T
Frame Material	Steel
Frequency	50.00 Hz 60.00 Hz
Haz Area Class and Group	None
Haz Area Division	Not Applicable
Motor Letter Type	Three Phase
Output @ Frequency	2.000 HP @ 60 HZ 1.500 KW @ 50 HZ
Phase	3
Synchronous Speed @ Frequency	1200 RPM @ 60 HZ
Voltage @ Frequency	190.0 V @ 50 HZ 208.0 V @ 60 HZ 230.0 V @ 60 HZ 380.0 V @ 50 HZ 460.0 V @ 60 HZ
Agency Approvals	CE WEEE UKCA CURUSEEV IE3 NEMA PREMIUM
Ambient Temperature	40 °C
Auxiliary Box	NO AUXILLARY BOX
Auxiliary Box Lead Termination	None
Base Indicator	Rigid
Bearing Grease Type	Polyrex EM (-20F +300F)
Blower	None
Current @ Voltage	7.600 A @ 190.0 V 6.800 A @ 208.0 V 6.600 A @ 230.0 V

Part Detail

Revision	F
Type	AC
Mech. spec.	36M524
Base	
Status	PRD/A
Elec. spec.	36WGR900
Layout	36LYM524
Eff. date	04-25-2025
CD Diagram	CD0005
Poles	06
Leads	9#16
Proprietary	False
Created date	09-12-2023

	3.800 A @ 380.0 V
	3.300 A @ 460.0 V
Design Code	B
Drip Cover	No Drip Cover
Duty Rating	CONT
Efficiency @ 100% Load	88.5 %
Electrically Isolated Bearing	Not Electrically Isolated
Feedback Device	NO FEEDBACK
Front Shaft Indicator	None
Heater Indicator	No Heater
High Voltage Full Load Amps	3.3 a
Insulation Class	F
Inverter Code	Inverter Duty
KVA Code	L
Lifting Lugs	No Lifting Lugs
Locked Bearing Indicator	Locked Bearing
Motor Lead Quantity/Wire Size	9 @ 16 AWG
Motor Lead Termination	Flying Leads
Motor Standards	NEMA
Motor Type	3646M
Mounting Arrangement	F1
Number of Poles	6
Overall Length	18.04 IN
Power Factor	64
Product Family	General Purpose
Pulley End Bearing Type	Ball
Pulley Face Code	Standard
Pulley Shaft Indicator	Standard
Rodent Screen	None
RoHS Status	ROHS COMPLIANT
Service Factor	1.15
Shaft Diameter	1.125 IN
Shaft Ground Indicator	Shaft Grounding
Shaft Rotation	Reversible

Shaft Slinger Indicator	No Slinger
Speed	1175 rpm
	970 rpm
Speed Code	Single Speed
Starting Method	Direct on line
Thermal Device - Bearing	None
Thermal Device - Winding	None
Vibration Sensor Indicator	No Vibration Sensor
Winding Thermal 1	None
Winding Thermal 2	None

Nameplate

NP4304L									
CAT.NO.	GNEM3614T-G								
SPEC.	36M524R900G1								
HP	2HP//1.5KW					PH	3		
VOLTS	208-230/460//190/380								
AMPS	6.8-6.6/3.3//7.6/3.8								
R.P.M. (1/MIN)	1175//970					WT.	46KG		KG
FRAME	184T		HZ	60//50		I.P.	44		
SER.F.	1.15	CODE	L	DES.	B	CLASS	H		
NOM.EFF.	88.5//82.5		% (100%)						
P.F.	64	IC411, 10:1 VT							
RATING	40C AMB-S1 CONT				CC	010A			
DE	6206		ODE	6205					
ENCL	TEFC	SN							
	SFA 7.6-7.2/3.6//8.4/4.2								
	IE3-50HZ 88.3(75%),87.3(50%)								
	IE3-60HZ 88.2(75%),86.1(50%)								



