

ABB BALDOR RELIANCE III

Customer information packet

GNEM3764T

3HP//2.2KW, 1165//960RPM, 3PH, 60//50HZ, 213

Class - None

Division - Not Applicable

Specifications

Enclosure	TEFC
Frame	213T
Frame Material	Iron
Frequency	50.00 Hz 60.00 Hz
Haz Area Class and Group	None
Haz Area Division	Not Applicable
Motor Letter Type	Three Phase
Output @ Frequency	3.000 HP @ 60 HZ 2.200 KW @ 50 HZ
Phase	3
Synchronous Speed @ Frequency	1200 RPM @ 60 HZ
Voltage @ Frequency	190.0 V @ 50 HZ 208.0 V @ 60 HZ 230.0 V @ 60 HZ 380.0 V @ 50 HZ 460.0 V @ 60 HZ
Agency Approvals	CE WEEE UKCA CURUSEEV IE3 NEMA PREMIUM
Ambient Temperature	40 °C
Auxiliary Box	NO AUXILLARY BOX
Auxiliary Box Lead Termination	None
Base Indicator	Rigid
Bearing Grease Type	Polyrex EM (-20F +300F)
Blower	None
Current @ Voltage	9.300 A @ 208.0 V 9.000 A @ 230.0 V 5.200 A @ 380.0 V

Part Detail

Revision	C
Type	AC
Mech. spec.	07H002
Base	
Status	PRD/A
Elec. spec.	07WGX822
Layout	07LYH002
Eff. date	10-02-2024
CD Diagram	CD0005
Poles	06
Leads	9#14
Proprietary	False
Created date	09-12-2023

	4.500 A @ 460.0 V
	10.400 A @ 190.0 V
Design Code	B
Drip Cover	No Drip Cover
Duty Rating	CONT
Efficiency @ 100% Load	89.5 %
Electrically Isolated Bearing	Not Electrically Isolated
Feedback Device	NO FEEDBACK
Front Shaft Indicator	None
Heater Indicator	No Heater
High Voltage Full Load Amps	4.5 a
Insulation Class	F
Inverter Code	Inverter Duty
KVA Code	K
Lifting Lugs	Standard Lifting Lugs
Locked Bearing Indicator	No Locked Bearing
Motor Lead Quantity/Wire Size	9 @ 14 AWG
Motor Lead Termination	Flying Leads
Motor Standards	NEMA
Motor Type	0738M
Mounting Arrangement	F1
Number of Poles	6
Overall Length	18.45 IN
Power Factor	70
Product Family	General Purpose
Pulley End Bearing Type	Ball
Pulley Face Code	Standard
Pulley Shaft Indicator	Standard
Rodent Screen	None
RoHS Status	ROHS COMPLIANT
Service Factor	1.15
Shaft Diameter	1.375 IN
Shaft Ground Indicator	No Shaft Grounding
Shaft Rotation	Reversible

Shaft Slinger Indicator	No Slinger
Speed	1165 rpm
	960 rpm
Speed Code	Single Speed
Starting Method	Direct on line
Thermal Device - Bearing	None
Thermal Device - Winding	None
Vibration Sensor Indicator	No Vibration Sensor
Winding Thermal 1	None
Winding Thermal 2	None

Nameplate

NP4304L									
CAT.NO.	GNEM3764T								
SPEC.	07H002X822G1								
HP	3HP//2.2KW						PH	3	
VOLTS	208-230/460//190/380								
AMPS	9.3-9/4.5//10.4/5.2								
R.P.M. (1/MIN)	1165//960						WT.	77KG	KG
FRAME	213T		HZ		60//50		I.P.		44
SER.F.	1.15	CODE	K	DES.	B	CLASS	F		
NOM.EFF.	89.5//84.4		% (100%)						
P.F.	70	IC411, 10:1 VT							
RATING	40C AMB-S1 CONT				CC	010A			
DE	6307		ODE	6206					
ENCL	TEFC	SN							
	SFA 10.6-10/5//11.8/5.9								
	IE3-50HZ 90.6(75%),89.7(50%)								
	IE3-60HZ 90.7(75%),88.7(50%)								

AC Induction Motor Performance Data

Record # 101075

Typical performance - not guaranteed values

Winding: 07WGX822-R056		Type: 0738M	Enclosure: TEFC
Nameplate Data		460 V, 60 Hz: High Voltage Connection	
Rated Output (HP)	3HP//2.2KW	Full Load Torque	13.46 LB-FT
Volts	208-230/460//190/380	Start Configuration	direct on line
Full Load Amps	9.3-9/4.5//10.4/5.2	Breakdown Torque	46.79 LB-FT
R.P.M.	1165//960	Pull-up Torque	30.52 LB-FT
Hz	60//50 Phase	Locked-rotor Torque	34.44 LB-FT
NEMA Design Code	B KVA Code	Starting Current	32 A
Service Factor (S.F.)	1.15	No-load Current	2.35 A
NEMA Nom. Eff.	89.5 Power Factor	Line-line Res. @ 25°C	2.62 Ω
Rating - Duty	40C AMB-CONT	Temp. Rise @ Rated Load	31°C
S.F. Amps	10.6-10/5//11.8/5.9	Temp. Rise @ S.F. Load	37°C
		Locked-rotor Power Factor	22.7
		Rotor inertia	0.945 lb-ft ²

Load Characteristics 460 V, 60 Hz, 3 HP

% of Rated Load	25	50	75	100	125	150	S.F.
Power Factor	33	51	62	69	73	75	72
Efficiency	83.1	88.7	90.7	90.3	89.4	87.7	89.6
Speed	1191	1184	1176	1170	1160	1147	1162
Line amperes	2.62	3.11	3.75	4.51	5.38	6.39	5


ABB Motors and Mechanical Inc.

WINDING # 07WGX822

Typical performance - not guaranteed values.

3 HP 3 PH 60 HZ 1170 RPM 460 V 0738M

TORQUES (LB-FT) : PO=46.79 PU=30.52 LR=34.44 LRA=32



10/6/2026 ACPERF, record # 101075

AC Induction Motor Performance Data

Record # 101076

Typical performance - not guaranteed values

Winding: 07WGX822-R001			Type: 0738M		Enclosure: TEFC		
Nameplate Data			380 V, 50 Hz: High Voltage Connection				
Rated Output (HP)		3	Full Load Torque		16.37 LB-FT		
Volts		230/460	Start Configuration		direct on line		
Full Load Amps		9/4.5	Breakdown Torque		44.4 LB-FT		
R.P.M.		1165	Pull-up Torque		33.2 LB-FT		
Hz	60	Phase	3	Locked-rotor Torque		37.4 LB-FT	
NEMA Design Code		B	KVA Code	K	Starting Current		30.8 A
Service Factor (S.F.)		1.15		No-load Current		2.29 A	
NEMA Nom. Eff.		90.2	Power Factor	70	Line-line Res. @ 25°C		2.62 Ω
Rating - Duty		40C AMB-CONT		Temp. Rise @ Rated Load		40°C	
S.F. Amps				Temp. Rise @ S.F. Load		50°C	
				Locked-rotor Power Factor		22.7	
				Rotor inertia		0.945 lb-ft²	

Load Characteristics 380 V, 50 Hz, 3 HP

% of Rated Load	25	50	75	100	125	150	S.F.
Power Factor	38	59	69	74	76	76	72
Efficiency	86.1	89.7	90.6	89.1	87.2	84.2	89.6
Speed	990	981	972	962	949	931	1162
Line amperes	2.62	3.26	4.13	5.18	6.42	7.96	5

ABB Motors and Mechanical Inc.

WINDING # 07WGX822

Typical performance - not guaranteed values.

3 HP 3 PH 50 HZ 1165 RPM 380 V 0738M

TORQUES (LB-FT) : PO=44.4 PU=33.2 LR=37.4 LRA=30.8

