

ABB BALDOR RELIANCE III

Customer information packet

IDBRPM403004R1

300HP, 1785/3570RPM, 460V, 3PH, TEBC, FL4034

Specifications

Enclosure	TEBC
Frame	FL4034
Frame Material	Exposed Laminations
Frequency	60.00 Hz
Output @ Frequency	300.000 @ 60 HZ 300.000 HP @ 60 HZ
Phase	3
Synchronous Speed @ Frequency	1800 RPM @ 60 HZ
Voltage @ Frequency	460.0 V @ 60 HZ 460 V @ 60 HZ
Agency Approvals	CCSA US
Auxiliary Box	NO AUXILLARY BOX
Base Indicator	Rigid
Bearing Grease Type	Polyrex EM (-20F +300F)
Current @ Voltage	341.000 A @ 460.0 V
Duty Rating	CONT
Feedback Device	NO FEEDBACK
Frame Prefix	FL
Heater Indicator	No Heater
High Voltage Full Load Amps	341.0 a
Insulation Class	H
Motor Standards	NEMA
Mounting Arrangement	F3
Overall Length	65.46 IN
Product Family	General Industrial
Pulley End Bearing Type	Ball
Pulley Face Code	Standard
Service Factor	1.00
Shaft Diameter	3.624 IN
Shaft Ground Indicator	Shaft Grounding
Shaft Rotation	Reversible
Speed	1785 rpm

Part Detail

Revision	E
Type	AC
Mech. spec.	
Base	
Status	PRD/A
Elec. spec.	L6190A
Layout	619653-001
Eff. date	05-03-2022
CD Diagram	422927-001
Poles	04
Leads	
Proprietary	False
Created date	04-09-2015

Thermal Device - Bearing	None
Thermal Device - Winding	Normally Closed Thermostat

Nameplate

000613006MY									
	DUTY	HP	RPM	AMPS	VOLTS	HZ			
	CONT	300	1785		341	460		60	
	CONT	300	3570		334	460		120	
CAT.NO.	IDBRPM403004R1			SPEC. NO.	P40T1331				
SER.NO			FR	FL 4034	INSUL	H			
PH.	3	MAX SAFE SPEED		3750	AMB.	40	MIN. AMB.		-25
DESIGN NO.	L6190A		TYPE		ENCL.	TEAO-BC			
S.F.	1.00			D.E. BRG.	95BC02J30X				
ENCL MOD				O.D.E. BRG.	6316/C3VL0241				

REL S.O.	-	VOLTS	460	ENCLOSURE	TEBC	WYE CONN EQ CKT OHMS PER PHASE			
FRAME	FL4034	AMPS	341	MAX SAFE RPM	3750	(AT BASE RATING, 25 °C)			
HP	300	DUTY	CONT	IM (AMPS)	112	R1	.00622	X1	.0596
BASE SPEED	1785	S.F.	1.0	P.F.@NL/FL	.042/.874	R2	.00444	X2	.0774
PHASE/HERTZ	3/60	AMB °C/INSUL	40/H	WK ² (Lb-Ft ²)	73			XM	2.17

RATED FULL LOAD DATA

	RPM	HP	TORQUE LB-FT	FUND VOLTS	FREQ-HZ	AMPS
BASE SPEED	1787	300	882	460	60	341
MAX SPEED	3571	300	441	460	120	335
MIN SPEED	0	0	882	6.23	.441	341

LOAD PERFORMANCE AT BASE SPEED

	RPM	HP	TORQUE LB-FT	FUND VOLTS	FREQ-HZ	AMPS
NO LOAD	1800	0	0	460	60	112
1/4	1797	75.1	219	460	60	147
1/2	1794	150	440	460	60	201
3/4	1790	225	660	460	60	268
FULL LOAD	1787	300	882	460	60	341
O/L	1772	595	1764	460	60	663

REMARKS: TYPICAL DATA




DR. BY	K. GREEN
CK. BY	B. D. GRANT
APP. BY	J. MARTIN
DATE	6-10-14

**A-C MOTOR
PERFORMANCE DATA** L6190A

ISSUE DATE 9-7-16

Page 5 of 9

REL S.O.	-	VOLTS	460	ENCLOSURE	TEBC	WYE CONN EQ CKT OHMS PER PHASE	
FRAME	FL4034	AMPS	341	MAX SAFE RPM	3750	(AT BASE RATING, 25 °C)	
HP	300	DUTY	CONT	IM (AMPS)	112	R1 .00622	X1 .0596
BASE SPEED	1785	S.F.	1.0	P.F. @NL/FL	.042/.874	R2 .00444	X2 .0774
PHASE/HERTZ	3/60	AMB °C/INSUL	40/H	WK ² (Lb-Ft ²)	73	XM 2.17	

VARIABLE SPEED AC MOTOR CURVES


REMARKS: TYPICAL DATA
DATA VALID FOR NAMEPLATE SPEED RANGE ONLY

BALDOR
A MEMBER OF THE ABB GROUP


DR. BY K. GREEN
CK. BY B. D. GRANT
APP. BY J. MARTIN
DATE 6-10-14

**A-C MOTOR
PERFORMANCE
CURVES**

L6190A
SH 1 OF 2
ISSUE DATE 9-7-16 Page 6 of 9

REL S.O.	-	VOLTS	460	ENCLOSURE	TEBC	WYE CONN EQ CKT OHMS PER PHASE	
FRAME	FL4034	AMPS	341	MAX SAFE RPM	3750	(AT BASE RATING, 25 °C)	
HP	300	DUTY	CONT	IM (AMPS)	112	R1 .00622	X1 .0596
BASE SPEED	1785	S.F.	1.0	P.F. @NL/FL	.042/.874	R2 .00444	X2 .0774
PHASE/HERTZ	3/60	AMB °C/INSUL	40/H	WK ² (Lb-Ft ²)	73	XM 2.17	

LOAD PERFORMANCE (CONSTANT V/HZ RANGE)




REMARKS: TYPICAL DATA
DATA VALID FOR NAMEPLATE SPEED RANGE ONLY




DR. BY K. GREEN
CK. BY B. D. GRANT
APP. BY J. MARTIN
DATE 6-10-14

**A-C MOTOR
PERFORMANCE
CURVES**

L6190A
SH 2 OF 2
ISSUE DATE 9-7-16



422927-001



NOTE:
DATA TO BE SIZED
SO THAT IT FITS INTO
MATERIAL DECAL
DIMENSIONS. MAKE
LETTERS & NUMBERS
AS LARGE AS POSSIBLE.

MATERIAL: CERAMATIC DGF-P4
PERMA GRIP ADHESIVE

ALL LETTERS, NUMBERS
AND LINES TO BE BLACK
ON WHITE BACKGROUND.

422927-001

REV. DESC: CHANGE BACKGROUND COLOR FROM GOLD TO WHITE		
REV. LTR: B	VERSION: 02	TDR: 000000788708
FILE: \RGG\00000\203	REVISED: 08:09:29 03/04/2013	
MTL: -	BY: RGGWT	

BALDOR
EXTERNAL CONNECTION LABEL
SH 1 of 1