

ABB BALDOR RELIANCE III

Customer information packet

IDVSNM3587T-5

2HP, 1760RPM, 3PH, 60HZ, 143TC, 0534M, TENV, F1

Class - None

Division - Not Applicable

Specifications

Enclosure	TENV
Frame	145TC
Frame Material	Iron
Frequency	60.00 Hz
Haz Area Class and Group	None
Haz Area Division	Not Applicable
Motor Letter Type	Three Phase
Output @ Frequency	2.000 HP @ 60 HZ
Phase	3
Synchronous Speed @ Frequency	1800 RPM @ 60 HZ
Voltage @ Frequency	575.0 V @ 60 HZ
Agency Approvals	CSA UR
Ambient Temperature	40 °C
Auxiliary Box	NO AUXILLARY BOX
Auxiliary Box Lead Termination	None
Base Indicator	Rigid
Bearing Grease Type	Polyrex EM (-20F +300F)
Blower	None
Current @ Voltage	2.200 A @ 575.0 V
Design Code	B
Drip Cover	No Drip Cover
Duty Rating	CONT
Efficiency @ 100% Load	86.5 %
Electrically Isolated Bearing	Not Electrically Isolated
Feedback Device	NO FEEDBACK
Front Shaft Indicator	None
Heater Indicator	No Heater
High Voltage Full Load Amps	2.2 a
Insulation Class	F
Inverter Code	Inverter Ready
KVA Code	M

Part Detail

Revision	C
Type	AC
Mech. spec.	05E534
Base	
Status	PRD/A
Elec. spec.	05WGX555
Layout	05LYE534
Eff. date	08-19-2026
CD Diagram	CD0006
Poles	04
Leads	3#18
Proprietary	False
Created date	03-11-2022

Lifting Lugs	Standard Lifting Lugs
Locked Bearing Indicator	Locked Bearing
Max Speed	5500 rpm
Motor Lead Quantity/Wire Size	3 @ 18 AWG
Motor Lead Termination	Flying Leads
Motor Standards	NEMA
Motor Type	0534M
Mounting Arrangement	F1
Number of Poles	4
Overall Length	14.65 IN
Power Factor	79
Product Family	General Purpose
Pulley End Bearing Type	Ball
Pulley Face Code	C-Face
Pulley Shaft Indicator	Standard
Rodent Screen	None
Service Factor	1.00
Shaft Diameter	0.875 IN
Shaft Ground Indicator	No Shaft Grounding
Shaft Rotation	Reversible
Shaft Slinger Indicator	No Slinger
Speed	1760 rpm
Speed Code	Single Speed
Starting Method	Direct on line
Thermal Device - Bearing	None
Thermal Device - Winding	Normally Closed Thermostat
Vibration Sensor Indicator	No Vibration Sensor
Winding Thermal 1	None
Winding Thermal 2	None

Nameplate

NP4564L									
CAT.NO.	IDVSNM3587T-5								
SPEC.	05E534X555G1								
FRAME	145TC			H.P.	2				
VOLTS	575								
MAG. CUR.	1.27				F.L. AMPS		2.2		
R.P.M.	1760			R.P.M. MAX			5500		
HZ.	60		PH.	3		CLASS	F		
SER.F.	1.00			SL HZ		1.33			
NEMA NOM. EFF.	86.5			WK2		0.245			
RATING	40C AMB-CONT							ENCL	TENV
DE	6205		ODE		6203				
CC	010A		SN						
	1000:1 CT/VT								

AC Induction Motor Performance Data

Record # 87284

Typical performance - not guaranteed values

Winding: 05WGX555-R003			Type: 0534M		Enclosure: TENV			
Nameplate Data			575 V, 60 Hz: Single Voltage Motor					
Rated Output (HP)		2	Full Load Torque		5.99 LB-FT			
Volts		575	Start Configuration		direct on line			
Full Load Amps		2.2	Breakdown Torque		25.71 LB-FT			
R.P.M.		1760	Pull-up Torque		15.03 LB-FT			
Hz	60	Phase	3	Locked-rotor Torque		18.22 LB-FT		
NEMA Design Code		B	KVA Code	M	Starting Current		21.07 A	
Service Factor (S.F.)		1	No-load Current		1.27 A			
NEMA Nom. Eff.		86.5	Power Factor		79	Line-line Res. @ 25°C		12.8 Ω
Rating - Duty		40C AMB-CONT		Temp. Rise @ Rated Load		60°C		
				Locked-rotor Power Factor		55.3		
				Rotor inertia		0.245 lb-ft²		

Load Characteristics 575 V, 60 Hz, 2 HP

% of Rated Load	25	50	75	100	125	150
Power Factor	36	58	71	79	83	86
Efficiency	79.2	86.2	87.4	86.9	85.6	83.8
Speed	1789	1780	1771	1760	1748	1735
Line amperes	1.32	1.52	1.82	2.2	2.64	3.12


ABB Motors and Mechanical Inc.

WINDING # 05WGX555




Typical performance - not guaranteed values.

2 HP 3 PH 60 HZ 1760 RPM 575 V 0534M

TORQUES (LB-FT): PO=25.71 PU=15.03 LR=18.22 LRA=21.07



CD0006


NOTES:

1. THREE LEAD MOTOR MAY BE EITHER WYE CONNECTED OR DELTA CONNECTED.
2. INTERCHANGE ANY TWO LINE LEADS TO REVERSE ROTATION.
3. OPTIONAL THERMOSTATS ARE PROVIDED WHEN SPECIFIED.
4. ACTUAL NUMBER OF INTERNAL PARALLEL CIRCUITS MAY VARY.
5. LEAD COLORS ARE OPTIONAL. LEADS MUST BE NUMBERED AS SHOWN.

CD0006

REV. DESC: ADD CLASS CONN00000007

REV. LTR: E

VERSION: 01

TDR: 000001099922

FILE: \AAA\00005\141

REVISED: 10:24:49 02/19/2019

BY: ENBRIRO

MTL: -


BALDOR - RELIANCE®

3PH, SV, 3 LEADS, WYE OR DELTA CONNECTED

SH 1 of 1