

ABB BALDOR RELIANCE III

Customer information packet

L3409-50

.5/.37KW, 1425RPM, 1PH, 50HZ, 48, 3424LC, TEFC

Class - None

Division - Not Applicable

Specifications

Enclosure	TEFC
Frame	48
Frame Material	Steel
Frequency	50.00 Hz
Haz Area Class and Group	None
Haz Area Division	Not Applicable
Motor Letter Type	Cap Start, Cap Run
Output @ Frequency	.370 KW @ 50 HZ
Phase	1
Synchronous Speed @ Frequency	1500 RPM @ 50 HZ
Voltage @ Frequency	110.0 V @ 50 HZ 220.0 V @ 50 HZ
Agency Approvals	C UR US CE CURUS UKCA WEEE
Ambient Temperature	40 °C
Auxiliary Box	NO AUXILLARY BOX
Auxiliary Box Lead Termination	None
Base Indicator	Rigid
Bearing Grease Type	Polyrex EM (-20F +300F)
Blower	None
Current @ Voltage	5.000 A @ 110.0 V 2.500 A @ 220.0 V
Design Code	-
Drip Cover	No Drip Cover
Duty Rating	CONT
Efficiency @ 100% Load	72.7 %
Electrically Isolated Bearing	Not Electrically Isolated
Feedback Device	NO FEEDBACK
Front Shaft Indicator	None

Part Detail

Revision	D
Type	AC
Mech. spec.	34G374
Base	
Status	PRD/A
Elec. spec.	34WGR778
Layout	34LYG374
Eff. date	10-25-2024
CD Diagram	CD0055
Poles	04
Leads	6#18
Proprietary	False
Created date	09-27-2023

Heater Indicator	No Heater
High Voltage Full Load Amps	2.5 a
Insulation Class	B
Inverter Code	Not Inverter
KVA Code	J
Lifting Lugs	No Lifting Lugs
Locked Bearing Indicator	No Locked Bearing
Motor Lead Quantity/Wire Size	6 @ 18 AWG
Motor Lead Termination	Flying Leads
Motor Standards	NEMA
Motor Type	3424LC
Mounting Arrangement	F1
Number of Poles	4
Overall Length	11.35 IN
Power Factor	93
Product Family	General Purpose
Pulley End Bearing Type	Ball
Pulley Face Code	Standard
Pulley Shaft Indicator	Standard
Rodent Screen	None
RoHS Status	ROHS COMPLIANT
Service Factor	1.25
Shaft Diameter	0.500 IN
Shaft Ground Indicator	No Shaft Grounding
Shaft Rotation	Reversible
Shaft Slinger Indicator	No Slinger
Speed	1425 rpm
Speed Code	Single Speed
Starting Method	Direct on line
Thermal Device - Bearing	None
Thermal Device - Winding	None
Vibration Sensor Indicator	No Vibration Sensor
Winding Thermal 1	None
Winding Thermal 2	None

Nameplate

NP1372L											
CAT.NO.	L3409-50										
SPEC.	34G374R778										
HP	.5/.37KW										
VOLTS	110/220										
AMP	5/2.5										
R.P.M. (1/MIN)	1425										
FRAME	48	HZ		50			PH		1		
SER.F.	1.25	CODE		J	DES		-	CL	B		
NEMA-NOM-EFF	72.7	PF		93							
RATING	40C AMB-S1 CONT										
CC			IP44 KG15 IC411								
DE	6203			ODE		6203					
ENCL	TEFC	SN									
	IE2-50HZ 68(75%),60 (50%)										

Accessories

Part number	Description	Multiplier
34-3900T	C-FACE KIT	A8

AC Induction Motor Performance Data

Record # 50675

Typical performance - not guaranteed values

Winding: 34WGY788-R004			Type: 3420LC		Enclosure: TEFC	
Nameplate Data			230 V, 60 Hz: High Voltage Connection			
Rated Output (HP)		.33	Full Load Torque		0.489 LB-FT	
Volts		115/208-230	Start Configuration		direct on line	
Full Load Amps		3.2/1.7-1.6	Breakdown Torque		2.5 LB-FT	
R.P.M.		3450	Pull-up Torque		1.4 LB-FT	
Hz	60 Phase	1	Locked-rotor Torque		1.8 LB-FT	
NEMA Design Code		N KVA Code	Starting Current		14.5 A	
Service Factor (S.F.)		1.35	No-load Current		0.55 A	
NEMA Nom. Eff.	72 Power Factor	96	Line-line Res. @ 25°C		4.32 Ω A Ph 6.27 Ω B Ph	
Rating - Duty		40C AMB-CONT	Temp. Rise @ Rated Load		33°C	
S.F. Amps		4/2.2-2	Temp. Rise @ S.F. Load		39°C	

Load Characteristics 230 V, 60 Hz, 0.33 HP

% of Rated Load	25	50	75	100	125	150	S.F.
Power Factor	83	88	93	94	93	91	92
Efficiency	41.1	57.6	66.3	70.3	72.5	73	72.7
Speed	3566	3544	3527	3502	3474	3439	3460
Line amperes	0.798	1.06	1.31	1.6	1.94	2.31	2.09


ABB Motors and Mechanical Inc.

WINDING # 34WGY788


Typical performance - not guaranteed values.

0.33 HP 1 PH 60 HZ 3450 RPM 230 V 3420LC

TORQUES (LB-FT): PO=2.5 PU=1.4 LR=1.8 LRA=14.5



10/7/2026 ACPERF, record # 50675



CD0055

