

ABB BALDOR RELIANCE III

Customer information packet

M1722T

2/.89HP, 1720/1150RPM, 3PH, 60HZ, 182T, 3538M

Class - None

Division - Not Applicable

Specifications

Enclosure	TEFC
Frame	182T
Frame Material	Steel
Frequency	60.00 Hz
Haz Area Class and Group	None
Haz Area Division	Not Applicable
Motor Letter Type	Three Phase
Output @ Frequency	2.000 HP @ 60 HZ .890 HP @ 60 HZ
Phase	3
Synchronous Speed @ Frequency	1200 RPM @ 60 HZ
Voltage @ Frequency	460.0 V @ 60 HZ
Agency Approvals	UR CSA
Ambient Temperature	40 °C
Auxiliary Box	NO AUXILLARY BOX
Auxiliary Box Lead Termination	None
Base Indicator	Rigid
Bearing Grease Type	Polyrex EM (-20F +300F)
Blower	None
Current @ Voltage	2.760 A @ 460.0 V
Design Code	B
Drip Cover	No Drip Cover
Duty Rating	CONT
Electrically Isolated Bearing	Not Electrically Isolated
Feedback Device	NO FEEDBACK
Front Shaft Indicator	None
Heater Indicator	No Heater
High Voltage Full Load Amps	1.6 a
Insulation Class	F
Inverter Code	Not Inverter
KVA Code	J

Part Detail

Revision	D
Type	AC
Mech. spec.	35L100
Base	
Status	PRD/A
Elec. spec.	35WGG365
Layout	35LYL100
Eff. date	07-27-2024
CD Diagram	CD0013
Poles	04/06
Leads	6#18
Proprietary	False
Created date	02-23-2023

Lifting Lugs	No Lifting Lugs
Locked Bearing Indicator	No Locked Bearing
Motor Lead Quantity/Wire Size	6 @ 18 AWG
Motor Lead Termination	Flying Leads
Motor Standards	NEMA
Motor Type	3538M
Mounting Arrangement	F1
Number of Poles	4 6
Overall Length	16.54 IN
Product Family	General Purpose
Pulley End Bearing Type	Ball
Pulley Face Code	Standard
Pulley Shaft Indicator	Standard
Rodent Screen	None
Service Factor	1.15
Shaft Diameter	1.125 IN
Shaft Ground Indicator	No Shaft Grounding
Shaft Rotation	Reversible
Shaft Slinger Indicator	No Slinger
Speed	1150 rpm 1720 rpm
Speed Code	2S-2W-VT
Starting Method	Direct on line
Thermal Device - Bearing	None
Thermal Device - Winding	None
Vibration Sensor Indicator	No Vibration Sensor
Winding Thermal 1	None
Winding Thermal 2	None

Nameplate

NP1256L									
CAT.NO.	M1722T								
SPEC.	35L100G365								
HP	2/.89								
VOLTS	460								
AMP	2.76/1.63								
RPM	1720/1150								
FRAME	182T		HZ	60			PH	3	
SER.F.	1.15	CODE	J	DES	B	CLASS	F		
NEMA-NOM-EFF		PF							
RATING	40C AMB-CONT								
CC									
DE	6206		ODE	6203					
ENCL	TEFC	SN							
	SFA 3.13								

AC Induction Motor Performance Data

Record # 87895

Preliminary Data Sheet

Winding: 35WGG365-R001			Type: 3538M		Enclosure: TEFC		
Nameplate Data			460 V, 60 Hz: High Speed Connection				
Rated Output (HP)		2/.89	Full Load Torque		6.02 LB-FT		
Volts		460	Start Configuration		direct on line		
Full Load Amps		2.76/1.63	Breakdown Torque		19.45 LB-FT		
R.P.M.		1720/1150	Pull-up Torque		10.14 LB-FT		
Hz	60	Phase	3	Locked-rotor Torque		14.82 LB-FT	
NEMA Design Code		B	KVA Code	J	Starting Current		18.37 A
Service Factor (S.F.)		1.15		No-load Current		1.47 A	
NEMA Nom. Eff.		0	Power Factor	0	Line-line Res. @ 25°C		16.1 Ω
Rating - Duty		40C AMB-CONT		Temp. Rise @ Rated Load		79°C	
S.F. Amps				Temp. Rise @ S.F. Load		100°C	
				Locked-rotor Power Factor		81.2	
				Rotor inertia		0.274 lb-ft²	

Load Characteristics 460 V, 60 Hz, 2 HP

% of Rated Load	25	50	75	100	125	150	S.F.
Power Factor	39	62	76	84	88	91	86
Efficiency	73.1	80.9	81.9	80.1	77.6	74.4	78.6
Speed	1783	1765	1746	1722	1698	1666	1708
Line amperes	1.57	1.84	2.23	2.76	3.38	4.14	3.13


ABB Motors and Mechanical Inc.

WINDING # 35WGG365

Typical performance - not guaranteed values.

2 HP 3 PH 60 HZ 1722 RPM 460 V 3538M

TORQUES (LB-FT): PO=19.45 PU=10.14 LR=14.82 LRA=18.37



AC Induction Motor Performance Data

Record # 87896

Preliminary Data Sheet

Winding: 35WGG365-R001			Type: 3538M		Enclosure: TEFC		
Nameplate Data				460 V, 60 Hz: Low Speed Connection			
Rated Output (HP)		2/.89		Full Load Torque		4.04 LB-FT	
Volts		460		Start Configuration		direct on line	
Full Load Amps		2.76/1.63		Breakdown Torque		11.1 LB-FT	
R.P.M.		1720/1150		Pull-up Torque		5.61 LB-FT	
Hz	60	Phase	3	Locked-rotor Torque		7.49 LB-FT	
NEMA Design Code		B	KVA Code	J	Starting Current		7.42 A
Service Factor (S.F.)		1.15		No-load Current		1.25 A	
NEMA Nom. Eff.		0	Power Factor	0	Line-line Res. @ 25°C		41.5 Ω
Rating - Duty		40C AMB-CONT		Temp. Rise @ Rated Load			
				Locked-rotor Power Factor		81.2	
				Rotor inertia		0.274 lb-ft²	

Load Characteristics 460 V, 60 Hz, 0.89 HP

% of Rated Load	25	50	75	100	125	150	S.F.
Power Factor	31	47	60	71	78	84	75
Efficiency	54	67.9	72.8	74.1	73.5	71.5	73.7
Speed	1190	1181	1170	1158	1144	1127	1150
Line amperes	1.26	1.31	1.43	1.59	1.81	2.09	1.72


ABB Motors and Mechanical Inc.


WINDING # 35WGG365

Typical performance - not guaranteed values.


0.89 HP 3 PH 60 HZ 1158 RPM 460 V 3538M

TORQUES (LB-FT): PO=11.1 PU=5.61 LR=7.49 LRA=7.42






CD0013



LOW SPEED


11 12 13



LINE

HIGH SPEED

1 2 3



LINE

- NOTES:
1. INTERCHANGE ANY TWO LINE LEADS TO REVERSE ROTATION.
 2. OPTIONAL THERMOSTATS ARE PROVIDED WHEN SPECIFIED.
 3. ACTUAL NUMBER OF INTERNAL PARALLEL CIRCUITS MAY VARY.
 4. LEAD COLORS ARE OPTIONAL. LEADS MUST ALWAYS BE NUMBERED AS SHOWN.

CD0013

REV. DESC: REVISE TO SHOW OPTIONAL COLORS			
REV. LTR: D	BY: JLP	REVISED: 01/22/99 8:50	TDR: 0171435
CD0013		FILE: AAA00005143	MDL: -
		MTL: -	

BALDOR ELECTRIC Co.

3PH, SV, 6 LEADS, 2-SPEED 2-WINDING