

ABB BALDOR RELIANCE III

Customer information packet

M1755T

1.5/.375HP, 1735/865RPM, 3PH, 60HZ, 145T, 352

Class - None

Division - Not Applicable

Specifications

Enclosure	TEFC
Frame	145T
Frame Material	Steel
Frequency	60.00 Hz
Haz Area Class and Group	None
Haz Area Division	Not Applicable
Motor Letter Type	Three Phase
Output @ Frequency	1.500 HP @ 60 HZ .375 HP @ 60 HZ
Phase	3
Synchronous Speed @ Frequency	1800 RPM @ 60 HZ
Voltage @ Frequency	460.0 V @ 60 HZ
Agency Approvals	UR CSA
Ambient Temperature	40 °C
Auxiliary Box	NO AUXILLARY BOX
Auxiliary Box Lead Termination	None
Base Indicator	Rigid
Bearing Grease Type	Polyrex EM (-20F +300F)
Blower	None
Current @ Voltage	2.560 A @ 460.0 V
Design Code	-
Drip Cover	No Drip Cover
Duty Rating	CONT
Electrically Isolated Bearing	Not Electrically Isolated
Feedback Device	NO FEEDBACK
Front Shaft Indicator	None
Heater Indicator	No Heater
High Voltage Full Load Amps	1.1 a
Insulation Class	F
Inverter Code	Not Inverter
KVA Code	L

Part Detail

Revision	D
Type	AC
Mech. spec.	35AA001
Base	
Status	PRD/A
Elec. spec.	35WGG357
Layout	35LYAA001
Eff. date	10-28-2025
CD Diagram	CD0032
Poles	04/08
Leads	6#18 Y
Proprietary	False
Created date	02-23-2023

Lifting Lugs	No Lifting Lugs
Locked Bearing Indicator	No Locked Bearing
Motor Lead Quantity/Wire Size	6 @ 18 AWG
Motor Lead Termination	Flying Leads
Motor Standards	NEMA
Motor Type	3524M
Mounting Arrangement	F1
Number of Poles	4 8
Overall Length	13.31 IN
Product Family	General Purpose
Pulley End Bearing Type	Ball
Pulley Face Code	Standard
Pulley Shaft Indicator	Standard
Rodent Screen	None
Service Factor	1.15
Shaft Diameter	0.875 IN
Shaft Ground Indicator	No Shaft Grounding
Shaft Rotation	Reversible
Shaft Slinger Indicator	No Slinger
Speed	1735 rpm 865 rpm
Speed Code	2S-1W-VT
Starting Method	Direct on line
Thermal Device - Bearing	None
Thermal Device - Winding	None
Vibration Sensor Indicator	No Vibration Sensor
Winding Thermal 1	None
Winding Thermal 2	None

Nameplate

NP1256L									
CAT.NO.	M1755T								
SPEC.	35AA001G357								
HP	1.5/.375								
VOLTS	460								
AMP	2.56/1.1								
RPM	1735/865								
FRAME	145T		HZ	60			PH	3	
SER.F.	1.15		CODE	L	DES	-	CLASS	F	
NEMA-NOM-EFF			PF						
RATING	40C AMB-CONT								
CC									
DE	6205		ODE	6203					
ENCL	TEFC		SN						
	SFA 2.79								

Accessories

Part number	Description	Multiplier
35-8762	C FACE KIT	A8
35EP1506A01SP	D-FLANGE KIT	A8

AC Induction Motor Performance Data

Record # 87858

Typical performance - not guaranteed values

Winding: 35WGG357-R001			Type: 3524M		Enclosure: TEFC			
Nameplate Data			460 V, 60 Hz: High Speed Connection					
Rated Output (HP)		1.5/.375	Full Load Torque		4.53 LB-FT			
Volts		460	Start Configuration		direct on line			
Full Load Amps		2.56/1.1	Breakdown Torque		15.28 LB-FT			
R.P.M.		1735/865	Pull-up Torque		7.79 LB-FT			
Hz	60	Phase	3	Locked-rotor Torque		12.39 LB-FT		
NEMA Design Code		-	KVA Code	L	Starting Current		16.67 A	
Service Factor (S.F.)		1.15	No-load Current		1.94 A			
NEMA Nom. Eff.		0	Power Factor		0	Line-line Res. @ 25°C		16 Ω
Rating - Duty		40C	AMB-CONT		Temp. Rise @ Rated Load		76°C	
S.F. Amps					Temp. Rise @ S.F. Load		88°C	
					Locked-rotor Power Factor		86.2	
					Rotor inertia		0.173 lb-ft²	

Load Characteristics 460 V, 60 Hz, 1.5 HP

% of Rated Load	25	50	75	100	125	150	S.F.
Power Factor	29	46	60	70	78	83	75
Efficiency	61.8	73.3	77	77.6	76.4	73.9	76.9
Speed	1784	1769	1753	1734	1713	1682	1721
Line amperes	1.93	2.05	2.26	2.56	2.94	3.52	2.79


ABB Motors and Mechanical Inc.

WINDING # 35WGG357

Typical performance - not guaranteed values.

1.5 HP 3 PH 60 HZ 1734 RPM 460 V 3524M

TORQUES (LB-FT): PO=15.28 PU=7.79 LR=12.39 LRA=16.67



AC Induction Motor Performance Data

Record # 87860

Typical performance - not guaranteed values

Winding: 35WGG357-R001			Type: 3524M		Enclosure: TEFC		
Nameplate Data				460 V, 60 Hz: Low Speed Connection			
Rated Output (HP)		1.5/.375		Full Load Torque		2.26 LB-FT	
Volts		460		Start Configuration		direct on line	
Full Load Amps		2.56/1.1		Breakdown Torque		8.68 LB-FT	
R.P.M.		1735/865		Pull-up Torque		4.64 LB-FT	
Hz	60	Phase	3	Locked-rotor Torque		6.29 LB-FT	
NEMA Design Code		- KVA Code		Starting Current		4.38 A	
Service Factor (S.F.)		1.15		No-load Current		1.11 A	
NEMA Nom. Eff.		0	Power Factor	0	Line-line Res. @ 25°C		64.1 Ω
Rating - Duty		40C AMB-CONT		Temp. Rise @ Rated Load			
				Locked-rotor Power Factor		86.2	
				Rotor inertia		0.173 lb-ft²	

Load Characteristics 460 V, 60 Hz, 0.375 HP

% of Rated Load	25	50	75	100	125	150	S.F.
Power Factor	25	33	41	49	56	62	53
Efficiency	31.8	47.6	56.5	61.7	64.7	66.1	63.5
Speed	893	886.9	880.4	873.4	865.8	857.3	869
Line amperes	1.11	1.12	1.14	1.17	1.21	1.28	1.19


ABB Motors and Mechanical Inc.


WINDING # 35WGG357

Typical performance - not guaranteed values.



0.375 HP 3 PH 60 HZ 873.4 RPM 460 V 3524M

TORQUES (LB-FT) : PO=8.68 PU=4.64 LR=6.29 LRA=4.38





CD0032



- NOTES:
- 1. INTERCHANGE ANY TWO LINE LEADS TO REVERSE ROTATION.
 - 2. OPTIONAL THERMOSTATS ARE PROVIDED WHEN SPECIFIED.
 - 3. ACTUAL NUMBER OF INTERNAL PARALLEL CIRCUITS MAY BE A MULTIPLE OF THOSE SHOWN ABOVE.
 - 4. LEAD COLORS ARE OPTIONAL. LEADS MUST ALWAYS BE NUMBERED AS SHOWN.

REV. DESC: REVISE TO SHOW OPTIONAL COLORS			
REV. LTR: E	BY: JLP	REVISED: 01/22/99 8:27	TDR: 0171435
CD0032		FILE: AAA00005145	MDL: -
		MTL: -	

BALDOR ELECTRIC Co.

3PH, SV, 6 LEADS, 2-SPEED 1-WINDING VARIABLE TORQUE

CD0032